

Rocky Mountain Forest District FSP Stocking Standards**

ROCKY MT	NAME	BGC	Regeneration Guide							Free Growing Guide					Post Spacing					
STOCKING		Classification	Species		Stocking(i)			Min	Regen	Assessment		Min. Height(ii)		Tree Height	Min	Max				
STANDARD		Zone/SZ Series	Conifer		Target MIN pσMIN p			Intertree	Delay	Earliest	Latest	Species	Ht	To Brush						
ID NUMBER			Preferred (p)	Acceptable (a)	(well-spaced/ha)												Distance	(Max yrs)	(yrs)	(yrs)
1001782	UWROF1	ESSFdk	01	PI Se Fd ¹⁴ Lw ¹⁴		Bl ¹⁴			1200	700	600	2.0	7	-	20	PI, Lw	1.6	125	1200	2200
												Fd	1.0							
												Others	0.8							
1001786		ESSFdk	02	Fd ¹⁴ Lw ¹⁴ PI		Se Pa ³¹ Bl ¹⁴			1000	500	400	2.0	7	-	20	PI,Lw	1.2	125	1200	2200
												Fd	0.8							
												Others	0.6							
1001783		ESSFdk	02	Fd ¹⁴ Lw ¹⁴ PI		Se Pa ³¹ Bl			U8	76 ^{U10}	U20	2.0 ¹⁴	-	-	20	PI,Lw	1.2	125	76	400 ^{U14}
												Fd	0.8							
												Others	0.6							
1001784		ESSFdk	03	PI Fd ¹⁴ Lw ¹⁴ Se		Bl ¹⁴			1200	700	600	2.0	7	-	20	PI, Lw	1.6	125	1200	2200
												Fd	1.0							
												Others	0.8							
1001787		ESSFdk	04	PI Se Fd ¹⁴ Lw ¹⁴		Bl ¹⁴ Pa ³¹			1200	700	600	2.0	7	-	20	PI, Lw	1.6	125	1200	2200
												Fd	1.0							
											Others	0.8								
1001788	ESSFdk	05	Bl ³² PI Se ³²					1200	700	600	2.0	4	-	20	PI	1.6	125	1200	2200	
											Others	0.8								
1001789	ESSFdk	06	Bl ³² PI Se ³²					1200	700	600	2.0	4	-	20	PI	1.6	125	1200	2200	
											Others	0.8								
		ESSFdk	07	non-forested					-	-	-	-	-	-	-	-	-			
1001790		ESSFwm	01	Bl Se Fd ¹⁴ Lw ¹⁴		PI ^{34,70}			1200	700	600	2.0	4	-	20	Lw, PI	2.0	125	1200	2200
												Others	1.0							
1001791		ESSFwm	02	Se PI ³⁴		Bl ¹⁴			1200	700	600	2.0	7	-	20	PI	2.0	125	1200	2200
												Others	1.0							
1001792		ESSFwm	03	Fd ¹⁴ Lw ¹⁴ Se		Bl ¹⁴ PI ^{34,70}			1200	700	600	2.0	4	-	20	PI, Pw	2.0	125	1200	2200
												Lw	2.0							
												Fd	1.4							
												Others	1.0							
1001793	ESSFwm	04	Bl Se		PI ³⁴			1200	700	600	2.0	4	-	20	PI	2.0	125	1200	2200	
											Others	1.0								

1,2 etc - see "Footnotes"

*Avoid logging

** Includes NDT4/ UWR standards; Additional information or requirements may be contained in the text of the footnotes.

August 3, 2010

1 of 8

Rocky Mountain Forest District FSP Stocking Standards**

ROCKY MT	NAME	BGC	Regeneration Guide								Free Growing Guide					Post Spacing	
STOCKING		Classification	Species		Stocking(i)			Min	Regen	Assessment		Min. Height(ii)		Tree Height	Min	Max	
STANDARD		Zone/SZ Series	Conifer		Target MIN	pa	MIN p	Intertree	Delay	Earliest	Latest	Species	Ht	To Brush			
ID NUMBER			Preferred (p)	Acceptable (a)	(well-spaced/ha)			Distance	(Max yrs)	(yrs)	(yrs)	(m)	(min%)				
1002925		ESSFdm	01	Se PI	Bl ^{1,7,8} Lw ^{14,32,76}	1200	700	600	2.0	4	-	20	PI	1.6	125	1200	2200
					Fd ¹⁴ Hw ¹⁴								Others	0.8			
1002926		ESSFdm	02	PI	Se ^{7,6,32,10} Bl ^{7,8}	1000	500	400	2.0	4	-	20	PI	1.6	125	1000	2200
					Fd ¹⁴ Lw ^{14,76}								Others	0.8			
1002927		ESSFdm	03	PI	Se ^{7,6} Bl ^{7,7,8} Fd ¹⁴	1200	700	600	2.0	4	-	20	PI	1.6	125	1200	2200
					Hw ¹⁴ Lw ^{14,76}								Others	0.8			
1002928		ESSFdm	04	Se PI	Bl ^{7,7,8} Hw ^{14,32}	1200	700	600	2.0	4	-	20	PI	1.6	125	1200	2200
													Others	0.8			
1002929	ESSFdm	05	Se	Bl ^{7,7,8} Hw ^{14,32} PI	1200	700	600	2.0	4	-	20	All	0.8	125	1200	2200	
1002930	ESSFdm	06	Se Bl PI ¹		1000	500	400	2.0	4	-	20	PI	1.6	125	1000	2200	
												Others	0.8				
1001794		ICHdw	01a	Fd ⁵⁸ Lw Py	Bg ²⁸ PI Cw Sx ^{10,13}	1200	700	600	2.0	7	-	20	PI, Pw	2.0	150	1200	2200
					Pw ^{31,49,57}								Lw	2.0			
													Fd	1.4			
													Others	1.0			
1001795		ICHdw	01b	Fd ⁵⁸ Lw PI Py ^{3,14}		1200	700	600	2.0	7	-	20	PI, Pw	2.0	150	1200	2200
					Cw Pw ^{31,49,57} Sx ^{10,13}								Lw	2.0			
													Fd	1.4			
													Others	1.0			
1001796		ICHdw	02	Fd ⁵⁸ Lw Py	Cw	1000	500	400	2.0	7	-	20	PI, Lw	1.4	150	1000	2200
													Fd	1.0			
													Others	0.8			
1001797		ICHdw	03	Fd ^{1,32,58} Lw ^{1,32} Sx	Bg ^{32,58} Hw ³² PI ¹	1200	700	600	2.0	4	-	20	PI, Pw	2.0	150	1200	2200
				Cw ³² Pw ^{31,49,57}								Lw	2.0				
												Fd	1.4				
												Others	1.0				
1001798	ICHdw	04	Cw ³² Sx Fd ^{1,32,58}	Bg ^{1,32} PI ¹	1200	700	600	2.0	4	-	20	PI, Pw	2.0	150	1200	2200	
				Lw ^{1,32} Pw ^{1,31,49,57}								Lw	2.0				
												Fd	1.4				
												Others	1.0				

1,2 etc - see "Footnotes"

*Avoid logging

** Includes NDT4/ UWR standards; Additional information or requirements may be contained in the text of the footnotes.

August 3, 2010

2 of 8

Rocky Mountain Forest District FSP Stocking Standards**

ROCKY MT	NAME	BGC		Regeneration Guide								Free Growing Guide					Post Spacing				
STOCKING		Classification		Species		Stocking(i)			Min	Regen	Assessment		Min. Height(ii)		Tree Height	Min	Max				
STANDARD		Zone/SZ	Series	Conifer		Target MIN pσMIN p			Intertree	Delay	Earliest	Latest	Species	Ht	To Brush						
ID NUMBER				Preferred (p)	Acceptable (a)	(well-spaced/ha)					Distance	(Max yrs)	(yrs)	(yrs)				(m)	(min%)		
1001800	UWROF2	ICHmk1	01	Fd ^{9,14,32}	Lw ^{9,14,32}	Bl ^{10,13}	Cw ^{10,13,32}	1200	700	600	2.0	7	-	20	PI, Lw	2.0	150	1200	2200		
					PI Sx ^{10,13}									Fd	1.4						
														Others	1.0						
1001801		ICHmk1	02	Fd	PI	Sx ^{10,13}	Py ^{9,14}	U8	76 ^{U10}	U20	2.0 ¹⁴	-		20	PI	1.4	125	76	400 ^{U14}		
														Fd	1.0						
														Others	0.8						
1001802		ICHmk1	02	Fd	PI	Sx ^{10,13}	Py ^{9,14}	600	400	400	2.0	7	-	20	PI	1.4	150	600	1000		
														Fd	1.0						
														Others	0.8						
1001803		ICHmk1	03	Fd	Lw	PI Sx ^{10,13}	Cw ^{10,13}	Py ^{9,14}	1000	500	400	2.0	7	-	20	PI, Lw	1.4	150	1000	2200	
														Fd	1.0						
														Others	0.8						
1001804		ICHmk1	04	Fd ³²	Lw ³²	PI Sx ^{10,13}	Cw ^{10,13}	Py ^{9,14}	Bl ¹³	1200	700	600	2.0	7	-	20	PI, Lw	2.0	150	1200	2200
															Fd	1.4					
														Others	1.0						
1001805	ICHmk1	05	PI Sx	Fd ^{9,14,32}		Bl	Cw ³²	1200	700	600	2.0	4	-	20	PI, Lw	2.0	150	1200	2200		
				Lw ^{9,14,32}										Fd	1.4						
														Others	1.0						
1001806	ICHmk1	06	PI Sx	Fd ^{9,14,32}		Bl	Lw ^{9,14,32}	Cw ³²	1200	700	600	2.0	4	-	20	PI, Lw	2.0	150	1200	2200	
														Fd	1.4						
														Others	1.0						
1001807	ICHmk1	07	PI ¹	Sx ¹	Fd ^{1,32}		Bl ¹	Cw ³²	1000	500	400	2.0	4	-	20	PI, Lw	1.4	150	1200	2200	
					Lw ^{1,32}									Fd	1.0						
														Others	0.8						

1,2 etc - see "Footnotes"

*Avoid logging

** Includes NDT4/ UWR standards; Additional information or requirements may be contained in the text of the footnotes.

August 3, 2010

3 of 8

Rocky Mountain Forest District FSP Stocking Standards**

ROCKY MT	NAME	BGC		Regeneration Guide						Free Growing Guide					Post Spacing		
STOCKING		Classification		Species		Stocking(i)		Min	Regen	Assessment		Min. Height(ii)		Tree Height	Min	Max	
STANDARD		Zone/SZ	Series	Conifer		Target MIN	paMIN p	Intertree	Delay	Earliest	Latest	Species	Ht	To Brush			
ID NUMBER				Preferred (p)	Acceptable (a)	(well-spaced/ha)	Distance			(Max yrs)	(yrs)		(yrs)	(m)			(min%)
1001808		ICHmw1	01	Fd PI Cw	Hw BI Lw ^{23,71}	1200	700	600	2.0	4	-	20	PI, Pw	2.0	150	1200	2200
				Pw ^{31,49} Sx								Lw	2.0				
												Fd	1.4				
												Others	1.0				
1001809		ICHmw1	02	Fd Pw ^{31,49}	PI ⁴⁹ Cw ²⁵ Sx ²⁵	1200	700	600	2.0	7	-	20	PI, Pw	2.0	150	1200	2200
													Lw	2.0			
													Fd	1.4			
													Others	1.0			
1001810		ICHmw1	03	Fd PI Pw ^{31,49}	BI ²⁵ Cw ²⁵ Hw	1200	700	600	2.0	7	-	20	PI, Pw	2.0	150	1200	2200
					Sx ^{10,13,25}	Lw ^{23,71}							Lw	2.0			
													Fd	1.4			
													Others	1.0			
1001811		ICHmw1	04	Fd PI Pw ^{31,49}	BI ²⁵ Cw ²⁵ Sx ²⁵	1200	700	600	2.0	7	-	20	PI, Pw	2.0	150	1200	2200
						Lw ^{23,71}							Lw	2.0			
													Fd	1.4			
													Others	1.0			
1001812	ICHmw1	05	Cw ³² Fd ^{1,32} Hw ³²	BI PI	1200	700	600	2.0	4	-	20	PI, Pw	2.0	150	1200	2200	
				Pw ^{1,32,49}								Fd	1.4				
												Others	1.0				
1001813	ICHmw1	06	BI Cw Fd ^{9,14} Hw	PI	1200	700	600	2.0	4	-	20	PI, Pw	2.0	150	1200	2200	
				Sx Pw ^{31,49}								Lw	2.0				
												Fd	1.4				
												Others	1.0				
1001814	ICHmw1	07	Cw ³² Hw ³²	BI PI	1000	500	400	2.0	4	-	20	PI	1.4	150	1000	2200	
				Sx Fd ^{1,14,32}								Fd	1.0				
												Others	0.8				

1,2 etc - see "Footnotes"

*Avoid logging

** Includes NDT4/ UWR standards; Additional information or requirements may be contained in the text of the footnotes.

August 3, 2010

4 of 8

Rocky Mountain Forest District FSP Stocking Standards**

ROCKY MT	NAME	BGC	Regeneration Guide								Free Growing Guide					Post Spacing		
STOCKING		Classification	Species		Stocking(i)			Min	Regen	Assessment		Min. Height(ii)		Tree Height	Min	Max		
STANDARD		Zone/SZ	Series	Conifer		Target MIN p a MIN p			Intertree	Delay	Earliest	Latest	Species	Ht	To Brush			
ID NUMBER				Preferred (p)	Acceptable (a)	(well-spaced/ha)												Distance
1035620		ICHdm	01	Fd ⁵⁸ Lw PI	Pw ^{31,57} Hw ¹⁰	1200	700	600	2.0	4	-	20	PI, Pw	2.0	150	1200		
				Sx ¹⁰	Cw ¹⁰ BI ¹³								Lw	2.0				
													Fd	1.4				
													Others	1.0				
			ICHdm	02	non-forested		-	-	-	-	-	-	-	-	-			
1035621			ICHdm	03	Fd ⁵⁸ Lw PI	Cw ¹⁰ BI ¹⁰	1200	700	600	2.0	7	-	20	PI, Pw	2.0	150	1200	
						Sx ^{10,13}								Lw	2.0			
														Fd	1.4			
														Others	1.0			
1035622			ICHdm	04	Fd ^{58,32} Lw ³² Sx	Pw ^{31,57} Hw	1200	700	600	2.0	7	-	20	PI, Pw	2.0	150	1200	
					PI Cw ³²	BI								Lw	2.0			
														Fd	1.4			
													Others	1.0				
1035623		ICHdm	05	Cw ³² Hw ³² Sx	BI PI Fd ^{32,1}	1200	700	600	2.0	4	-	20	PI, Pw	2.0	150	1200		
					Lw ^{32,1}								Lw	2.0				
													Fd	1.4				
													Others	1.0				
1035624		ICHdm	06	Cw ³² Sx Hw ³²	BI PI ¹² Fd ^{32,1}	1200	700	600	2.0	4	-	20	PI, Pw	2.0	150	1200		
					Lw ^{32,1}								Lw	2.0				
													Fd	1.4				
													Others	1.0				
1001822	UWRMF1	IDFdm2	01	Fd ³² Lw ³² Py	PI ^{10,13,73}	1000	500	400	2.0	7	-	20	PI, Lw	1.0	125	500	2000 ^{U14}	
		Note ^{U18}											Fd	0.8				
													Py	0.6				
1001823	UWROF3	IDFdm2	01	Fd ³² Lw ³² Py	PI ^{10,13}	U8	76 ^{U10}	U20	2.0 ¹⁴	-	-	20	PI, Lw	0.5	125	76	400 ^{U14}	
		Note ^{U19}											Fd	0.5				
													Py	0.5				
1001824	UWROR1	IDFdm2	02	Fd ²⁷ Py Lw ^{10,13}		U9	0 ^{U10}	U20	2.0 ¹⁴	-	-	20	Lw,Fd,Py	0.5	125	0	75 ^{U14}	
1001825	UWROR2	IDFdm2	03	Fd ²⁷ Py Lw ^{10,13}	PI ^{10,13}	U9	0 ^{U10}	U20	2.0 ¹⁴	-	-	20	PI, Lw	0.5	125	0	75 ^{U14}	
													Fd	0.5				
													Py	0.5				

1,2 etc - see "Footnotes"

*Avoid logging

** Includes NDT4/ UWR standards; Additional information or requirements may be contained in the text of the footnotes.

August 3, 2010

5 of 8

Rocky Mountain Forest District FSP Stocking Standards**

ROCKY MT	NAME	BGC	Regeneration Guide								Free Growing Guide					Post Spacing				
STOCKING		Classification	Species			Stocking(i)			Min	Regen	Assessment		Min. Height(ii)		Tree Height	Min	Max			
STANDARD		Zone/SZ	Series	Conifer			Target MIN	pa	MIN p	Intertree	Delay	Earliest	Latest	Species	Ht	To Brush				
ID NUMBER				Preferred (p)	Acceptable (a)		(well-spaced/ha)					Distance	(Max yrs)						(yrs)	(yrs)
1001826	UWRMF2	IDFdm2	04	Fd ^{3Z}	Lw ^{3Z}	PI Sx	Py	1000	500	400	2.0	7	-	20	PI, Lw	1.4	125	500	2000 ^{U14}	
														Fd	1.0					
															Others	0.8				
															PI, Lw	1.0	125	500	2000 ^{U14}	
1001827	UWRMF3	IDFdm2	05	PI Sx	Fd ^{1,3Z}			1000	500	400	2.0	7	-	20	PI, Lw	1.0	125	500	2000 ^{U14}	
															Fd	0.8				
															Sx	0.6				
1001828	UWRMF4	IDFdm2	07	Sx ¹	Fd ^{1,3Z}	Lw ^{1,3Z}	PI ¹	1000	500	400	2.0	4	-	20	PI, Lw	1.0	125	500	2000 ^{U14}	
			Note ^{U15}												Fd	0.8				
															Sx	0.6				
1001830	UWROF4	MSdk	01	Fd ^{3Z}	Lw ^{3Z}		BI	1200	700	600	2.0	7	-	20	PI, Lw	1.4	125	1200	2200	
															Others	0.8				
				02			non-forested		-	-	-		-	-	-	-				
1001831			MSdk	03	Fd	Lw	PI	Sx	1000	500	400	2.0	7	-	20	PI, Lw	1.0	125	1000	2200
															Others	0.6				
1001833			MSdk ^{U17}	03	Fd	Lw	PI	Sx	U8	76 ^{U10}	U20	2.0 ^{/4}	-	-	20	PI,Lw	1.4	125	76	400 ^{U14}
															Others	0.6				
1001832			MSdk	04	Fd	Lw	PI	Sx	1200	700	600	2.0	7	-	20	PI, Lw	1.4	125	1200	2200
															Others	0.8				
1001834			MSdk	05	Fd ^{3Z}	Lw ^{3Z}	PI Sx	BI	1200	700	600	2.0	7	-	20	PI, Lw	1.4	125	1200	2200
														Others	0.8					
1001835		MSdk	06	Sx	Fd ^{1,3Z}	Lw ^{1,3Z}	BI PI ¹	1200	700	600	2.0	4	-	20	PI, Lw	1.4	125	1200	2200	
														Others	0.8					
1001836	UWROR3	PPdh2	01	Py	Fd ^{27,3Z}		Lw ^{10,23,3Z}	PI ²³	U9	0 ^{U10}	U20	2.0 ^{/4}	-	-	20	All	0.5	125	0	75 ^{U14}
1001837	UWROR4	PPdh2	02a	Py	Fd ^{27,3Z}				U9	0 ^{U10}	U20	2.0 ^{/4}	-	-	20	All	0.5	125	0	75 ^{U14}
1001838	UWROR5	PPdh2	02b	Py	Fd ^{27,3Z}				U9	0 ^{U10}	U20	2.0 ^{/4}	-	-	20	All	0.5	125	0	75 ^{U14}
1001839	UWROF5	PPdh2	03	Fd ^{3Z}	Py ¹	Sx ²⁸	Lw	PI ²³	U8	76 ^{U10}	U20	2.0 ^{/4}	-	-	20	All	0.5	125	76	400 ^{U14}

1,2 etc - see "Footnotes"

*Avoid logging

** Includes NDT4/ UWR standards; Additional information or requirements may be contained in the text of the footnotes.

August 3, 2010

6 of 8

Rocky Mountain Forest District FSP Stocking Standards**

	Definitions	#	Footnote	#	Footnote
	Conifer Tree Species	17	restricted to western portion of biogeoclimatic unit in region	75	For the purposes of free growing and regeneration survey standards, minimum horizontal intertree distance (MITD) is 2.0 m or greater for trees to be considered
	"Ba" means amabilis fir;	18	restricted to eastern portion of biogeoclimatic unit in region		well-spaced. A reduced MITD of 1.7 metres may be used to facilitate selection of
	"Bg" means grand fir;	19	19-22 Not applicable to the Rocky Mountain Forest District.		superior planting microsites when sites have:
	"Bl" means subalpine fir;	23	restricted to trial use		<ul style="list-style-type: none"> • Dispersed occurrence of standing water
	"Bp" means noble fir;	24	suitable (as a major species) in wetter portion of biogeoclimatic unit		<ul style="list-style-type: none"> • Dispersed occurrence of bedrock outcrops
	"Cw" means western red cedar;				<ul style="list-style-type: none"> • Mechanical site preparation (including: mounding, disc trenching)
	"Fd" means Douglas-fir;	25	Not applicable to the Rocky Mountain Forest District.		<ul style="list-style-type: none"> • Root disease problems
	"Hm" means mountain hemlock;	26	Not applicable to the Rocky Mountain Forest District.		<ul style="list-style-type: none"> • Conditions where obstacle planting for snow creep is necessary.
	"Hw" means western hemlock;	27	partial canopy cover required for successful establishment		In any instance where the MITD is reduced below 2.0m, the specific reason will be
	"Lt" means tamarack;	28	limited by moisture deficit		identified in the site plan and a map showing stratum location and boundaries will
	"Lw" means western larch;	29	risk of heavy browsing by moose		be attached to the site plan. (These items will be appended to the site plan when
	"Pa" means whitebark pine;	30	risk of porcupine damage		the conditions justifying use of reduced MITD have been identified.) The area where
	"Pl" means lodgepole pine;	31	risk of white pine blister rust		conditions justify reduced MITD will be stratified separately. One hectare will be the
	"Pw" means white pine;	32	limited by growing-season frosts		minimum stratum size. Planting will be conducted to target levels.
	"Py" means ponderosa pine;	33	footnote retired and replaced with footnote 'a'		The reduced MITD applies to planted trees only.
	"Sb" means black spruce;	34	risk of snow damage	76	Conditions where Lw may be promoted from "acceptable" to
	"Se" means Engelmann spruce;	35	risk of weevil damage		"preferred" in the ESSFdm:
	"Ss" means Sitka spruce;	36	Not applicable to the Rocky Mountain Forest District.		Larch may be considered "preferred" at lower elevations in the ESSFdm where it
	"Sw" means white spruce;	37	risk of heart rots		is present and performing well in the pre-existing mature overstorey or
	"Sx" means hybrid spruce or interior spruce;	38	footnote retired		adjacent mature overstorey of similar site series, slope, aspect and elevation
	"Sxs" means hybrid Sitka spruce;	39	avoid exposed and windy sites		and is >25% of the overstorey.
	"Sxw" means hybrid white spruce;	40	risk of redheart		Larch may be considered "preferred" at lower elevations in the ESSFdm
	"Yc" means yellow cedar.	41	limited by poorly drained soils		where it is present and is performing well as planted or natural regeneration
		42	restricted to fresh soil moisture regimes		on similar sites in adjacent immature stands that are > 15 years old, and it
	Broadleaf Tree Species	43	Footnotes 43-46 Not applicable to the Rocky Mountain Forest District.		constitutes >25% of the stand based on the silviculture label.
	"Acb" means balsam poplar;	47	risk of balsam wooly adelgid		Larch may be considered "preferred" at lower elevations in the ESSFdm where a
	"Act" means black cottonwood;	48	risk of heavy browsing by deer		significant forest health issue for other preferred species has been identified and
	"At" means trembling aspen;	49	applies only to rust resistant, planted stock.		described in the Site Plan.
	"Ep" means common paper birch;	50	restricted to sites where the species occurs as a		At lower elevations in the ESSFdm where there is 10-25% Lw in the pre-harvest
			major species in a pre-harvest, natural stand		stand, Lw may count towards a maximum of 25% of the total well spaced
#	Broadleaf Management Constraints	51	restricted to areas with proven P1 performance		preferred stems.
a	productive, reliable, and feasible regeneration option	52	restricted to sheltered microsites with deep soil		Conditions where Se may be promoted from "acceptable" to
b	limited in productivity, reliability and/or feasibility	53	minor component		"preferred" in the ESSFdm.
		54	risk of unsuccessful release of advance regeneration		Spruce may be considered "preferred" in the ESSFdm on moister sites where it
	"Biogeoclimatic unit" or "BGC classification" means	55	acceptable in sx-sm portion of site series		is present and performing well in the pre-existing mature overstorey or adjacent
	the zone, subzone, variant and site series described				mature overstorey of similar site series, slope, aspect and elevation and
	in the most recent field guide published by the Ministry	#	Localized Footnotes		is >25% of the overstorey.
	of Forests for the identification and interpretation of	56	Footnotes 56 and 59 to 68 do not apply		Spruce may be considered "preferred" in the ESSFdm on moister sites where
	ecosystems, as applicable to a harvested area.		to the Rocky Mountain Forest District		it is present and is performing well as planted or natural regeneration on similar
		57	Pw rust-resistant stock may be preferred to a max 50% of preferred		sites in adjacent immature stands that are >15 years old, and it constitutes >25%
	"MIN" or "Min" means minimum.		and acceptable well-spaced stems.		of the stand based on the silviculture label.
	"MAX" or "Max" means maximum	58	Fd, Bg limited to a max 50% of preferred and acceptable well-spaced		Spruce may be considered "preferred" in the ESSFdm on moister sites where
			stems due to root rot.		a significant forest health issue for other preferred species has been identified
#	Footnote	69	Species is restricted to upper elevations when used in the southern		and described in the Site Plan.
1	elevated microsites are preferred		portion of the biogeoclimatic unit.		On moister sites where there is 10-25% Se in the pre-harvest stand, Se may
2	suitable on thick forest floors	70	Can be considered as "preferred species" on sites where low risk of		count towards a maximum of 25% of the total well spaced preferred stems.
3	restricted to coarse-textured soils		snow damage is expected.		<i>Acceptable performance is indicated by good form and vigour, with minimum</i>
4	restricted to medium-textured soils	71	Can be considered as "preferred species" on sites where Armillaria is		<i>evidence of damage and relatively disease free.</i>
5	footnote retired		a serious concern.		<i>Appropriate documentation for stand composition and vigour includes:</i>
6	restricted to nutrient-very-poor sites	72	Can be considered as "preferred species" on frost prone sites		<i>cruise compilations, silviculture surveys on older established stands, professional</i>
7	restricted to nutrient-medium sites		(footnote #1 then applies).		<i>site assessments and pre-harvest silviculture data.</i>
8	restricted to steep slopes	73	Can be considered as "preferred species" on sites where a low risk of		<i>Lower elevation is defined as below 1575 metres on cool aspects and below</i>
9	restricted to southerly aspects		damage from forest health factors (in particular; stem rusts, gall rust,		<i>1650 metres on warm aspects.</i>
10	restricted to northerly aspects		and Petrova albicapitana) is present.	77	May be considered as "preferred species" above 1800 metres.
11	restricted to crest slope positions	74	Layer 1 trees may be tallied regardless of spacing providing they meet	78	May be considered as preferred species for purposes of managing caribou
12	suitable on cold air drainage sites		free-growing damage criteria.		habitat on areas legally designated for caribou habitat
13	restricted to upper elevations of biogeoclimatic unit				
14	restricted to lower elevations of biogeoclimatic unit				
15	restricted to northern portion of biogeoclimatic unit in region				
16	restricted to southern portion of biogeoclimatic unit in region				

Rocky Mountain Forest District FSP Stocking Standards**

	UWR Footnotes			
N1	Rotational harvest entries using clearcut or light overstorey shelterwood. Manage for timber, ungulate winter range and approximately two decades of interim rangeland values per rotation.			
N2	Maintain connectivity of retention forest and OGMA's through managed forest and open forest ecosystems. Provide winter forest cover for ungulates.			
N3	Periodic entries of burning, thinning and partial cutting to maintain open forest conditions and rangeland values.			
N4	Provide connectivity between Open Range areas. Provide ungulate travel corridors between winter range and winter forest cover.			
N5	Periodic harvesting, prescribed burning and/or thinning to maintain open range condition, enhancing existing or potential bunchgrass sites.			
N6	Maintain connectivity of rangelands.			
N7	Inventory and periodic burns.			
U8	As stated on the UWR Order; the stocking range is 76-400 trees/hectare which must include 20-50 trees of the largest 1/3 of existing diameter range.			
U9	As stated on the UWR Order; the stocking range is 5-75 trees/hectare which must include 5-20 trees of the largest 1/3 of the existing diameter range.			
U10	KBLUP assumes at the landscape level Open Forest will contribute 50% of maximum timber benefits and 50% of maximum forage benefits and that Open Range contributes 10% timber benefits and 90% forage benefits. Targets of 250 stems/hectare for Open Forest and 20 stems/hectare for Open Range approximate the 50% and 10% timber contribution. It is recognized that to accomplish UWR forage objectives and subject to footnote U14, the range of stocking may vary for Open Forest from 76 to 400 stems/ha and that Open Range may vary from 0 to 75 stems/ha.			
N11	10% max.			
N12	40% max.			
N13	80% max.			
U14	FSP Max Density Standards and Section 8 of UWR Orders U-4-006, U-4-008 are used where applicable.			
U15	IDFdm2 07 is not in UWR order. (In UWR objectives it is expected to be managed as Riparian Area.)			
U16	PPdh2 04 is Open Forest in the UWR order but is not considered part of timber harvesting base, no standard is applied.			
U17	Standard applies only where Fd is the leading species.			
U18	Applies >1000 metres except in LUs 132, 135, and 138 where normal Managed Forest standards apply.			
U19	Applies <1000 metres except in LUs 132, 135, and 138 where normal Managed Forest standards apply.			
U20	These stocking standards do not over-ride the stand structure and forest cover requirements contained in the Ungulate Winter Range Orders for the Cranbrook and Invermere TSAs. Refer to these documents when designing and harvesting UWR/NDT4 openings.			