

Entity and Attribute Definitions Report

Run by: CASEOWNER
Run on: April 21, 2009 05:10 PM
Total Pages: 151
Total Entities: 102

Parameters

<i>Application:</i>	VRIMS
<i>Entities:</i>	%
<i>ER Diagram:</i>	%
<i>Include Entity Notes?</i>	Y
<i>Include Attribute Descriptions?</i>	Y
<i>Include Attribute Notes?</i>	Y
<i>Include Attribute Values?</i>	Y
<i>Include Table of Contents?</i>	N
<i>Include Index of Entities?</i>	Y

Entity Name: ADJUSTMENT ATTRIBUTE CODE			<i>Short Name:</i>	AAC
<i>Plural:</i>	ADJUSTMENT ATTRIBUTE CODE			
<i>Init. Volume:</i>	22	<i>Avg. Volume:</i>	25	<i>Max. Volume:</i> 30
			<i>Annual Growth Rate:</i>	5%

Description:

A code table list of data attributes that can be adjusted by staging and adjustment business area processes.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* ADJUSTMENT ATTRIBUTE CODE	CODETABLE CODE	N	VARCHAR2	10
Code representation of a factor that can be adjusted.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MAY BE grouped by one or more ADJUSTMENT ATTRIBUTE SET ADJ

MAY BE grouped by one or more ADJUSTMENT ATTRIBUTE SET STG

* = Relationships in primary unique identifier.

Unique Identifiers:

AAC PK	Primary	Y
ADJUSTMENT ATTRIBUTE CODE		

Entity Name: ADJUSTMENT ATTRIBUTE SET ADJUSTE				Short Name:	ASA
Plural:	ADJUSTMENT ATTRIBUTE SET ADJ				
Init. Volume:	3800000	Avg. Volume:	4000000	Max. Volume:	4200000
				Annual Growth Rate:	5%

Description:

An intersecting entity representing a set of attributes to which the adjustment factors have been applied, resulting in the adjusted business area values for this polygon.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* ADJUSTMENT ATTRIB SET ADJ ID	NUMERIC IDENTIFIER	N	NUMBER	10
Primary numeric identifier for the set of attributes being adjusted.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MUST BE adjusts as group one and only one ADJUSTMENT ATTRIBUTE CODE

MUST BE group for one and only one ADJUSTMENT FACTOR ADJUSTED

* = Relationships in primary unique identifier.

Unique Identifiers:

ASA UK	Primary	N
MUST BE adjusts as group one and only one ADJUSTMENT ATTRIBUTE CODE		
MUST BE group for one and only one ADJUSTMENT FACTOR ADJUSTED		
ASA PK	Primary	Y
ADJUSTMENT ATTRIB SET ADJ ID		

Entity Name: ADJUSTMENT ATTRIBUTE SET STAGING				Short Name:	AAS
Plural:	ADJUSTMENT ATTRIBUTE SET STG				
Init. Volume:	30000	Avg. Volume:	30000	Max. Volume:	120000
				Annual Growth Rate:	0%

Description:

An intersecting entity representing a set of attributes to which the adjustment factors have been applied, resulting in the staging business area values for this polygon.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* ADJUSTMENT ATTRIB SET STG ID	NUMERIC IDENTIFIER	N	NUMBER	10
Primary numeric identifier for the set of attributes being adjusted.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MUST BE adjusts as group one and only one ADJUSTMENT ATTRIBUTE CODE

MUST BE applied to one and only one ADJUSTMENT FACTOR STAGING

* = Relationships in primary unique identifier.

Unique Identifiers:

AAS UK	Primary	N
MUST BE adjusts as group one and only one ADJUSTMENT ATTRIBUTE CODE		
MUST BE applied to one and only one ADJUSTMENT FACTOR STAGING		
AAS PK	Primary	Y
ADJUSTMENT ATTRIB SET STG ID		

AFA PK	Primary	Y
ADJUSTMENT FACTOR ADJUSTED ID		

Entity Name: ADJUSTMENT FACTOR STAGING				Short Name:	AFS
Plural:	ADJUSTMENT FACTOR STAGING				
Init. Volume:	30000	Avg. Volume:	30000	Max. Volume:	120000
				Annual Growth Rate:	0%

Description:

Details adjustment factors or coefficients that are used to adjust a staging attribute. The factor values are used as variables in established calibration fomulas to map raw (generic) sensor data to a useful values in a human-understandable measurement system.

Eg. if the sensor captures a height as 100 (according to its current calibration), a coefficient (factor A for argument sake) of 1.134 may be applied to transform the height into metres, or 3.72 (factor B for argument sake) to transform the 100 into feet.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* ADJUSTMENT FACTOR STAGING ID	NUMERIC IDENTIFIER	N	NUMBER	10
Primary numeric identifier for the adjustment factor.				
FACTOR A	NUMERIC PRECISION	Y	NUMBER	10,4
The first factor (coefficient) used to adjust an attribute.				
FACTOR B	NUMERIC PRECISION	Y	NUMBER	10,4
The second factor (coefficient) used to adjust an attribute.				
FACTOR C	NUMERIC PRECISION	Y	NUMBER	10,4
The third factor (coefficient) used to adjust an attribute.				
FACTOR K	NUMERIC PRECISION	Y	NUMBER	10,4
The fourth factor (coefficient) used to adjust an attribute.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MUST BE adjusts one and only one TREE COVER LAYER STAGING
or MUST BE adjusts one and only one TREE SPECIES STAGING
or MUST BE adjusts one and only one VEGETATION COVER POLYGON STAGING
MAY BE group for one or more ADJUSTMENT ATTRIBUTE SET STG

* = Relationships in primary unique identifier.

Unique Identifiers:

AFS PK	Primary	Y
ADJUSTMENT FACTOR STAGING ID		

Entity Name: ADJUSTMENT INPUT ADJUSTED

Short Name:

AIA

Plural: ADJUSTMENT INPUT ADJUSTED

Init. Volume: 3800000

Avg. Volume: 4000000

Max. Volume: 4200000

Annual Growth Rate: 5%

Description:

This provides additional adjustment data to clients running against the VRIMS adjusted data. This entity acts as temporary storage where adjustment inputs can be entered that will ultimately override actual data values in the core data entities, for a single run of an adjustment. This data is provided to VDYP when it is run, which uses these values instead of the actual data.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* ADJUSTMENT INPUT ADJUSTED ID	NUMERIC IDENTIFIER	N	NUMBER	10
Primary unique numeric identifier for a VRI Adjusted Input.				
LOREY HEIGHT	HEIGHT - LOREY	Y	NUMBER	9,5
This is a statistically adjusted attribute that is input to VRIADJUST, a VDYP7 program that modifies the stand description that is required to project the polygon. This is the height in meters of the tree of average basal area.				
BASAL AREA 12.5CM	BASAL AREA	Y	NUMBER	10,6
This is a statistically adjusted attribute that is input to VRIADJUST, a VDYP7 program that modifies the stand description needed to project the polygon. This basal area is the total cross sectional area, at 1.3 metres height, in square meters per hectare				
WHOLE STEM VOLUME 7.5CM	VOLUME	Y	NUMBER	9,5
This is a statistically adjusted attribute that is input to VRIADJUST, a VDYP7 program that modifies the stand description that is required to project the polygon. This volume is the whole stem volume in cubic metres per hectare for all living trees above 7.5+cm dbh.				
WHOLE STEM VOLUME 12.5CM	VOLUME	Y	NUMBER	9,5
This is a statistically adjusted attribute that is input to VRIADJUST, a VDYP7 program that modifies the stand description that is required to project the polygon. This volume is the whole stem volume in cubic metres per hectare for all living trees above 12.5+cm dbh.				
CLOSE UTIL VOLUME 12.5CM	VOLUME	Y	NUMBER	9,5
This is a statistically adjusted attribute that is input to VRIADJUST, a VDYP7 program that modifies the stand description that is required to project the polygon. This volume is the whole stem volume net stumps and tops in cubic metres per hectare.				
CLOSE UTIL NET DECAY VOLUME	VOLUME	Y	NUMBER	9,5
This is a statistically adjusted attribute that is input to VRIADJUST, a VDYP7 program that modifies the stand description that is needed to project the polygon. This volume is the whole stem volume net stumps and tops, and decay, in cubic metres per hectare. Adjusted Close Utilization Volume Net Decay at 12.5+ dbh.				
CLOSE UTIL NET WASTE VOLUME	VOLUME	Y	NUMBER	9,5
This is a statistically adjusted attribute that is input to VRIADJUST, a VDYP7 program that modifies the stand description that is required to project the polygon. This volume is the whole stem volume net for utilization, decay and waste in cubic metres.				
INPUT MODE	INPUT - VRIADJUST MODE	Y	VARCHAR2	10
The input mode as used by VRIADJUST, a VDYP7 program that modifies the stand description that is needed to project the polygon.				
VRI ADJUST LAYER ID	NUMERIC IDENTIFIER	Y	NUMBER	10
Represents a layer that is to be adjusted by VDYP7's VRIADJUST application. When provided, the layer will override the actual layer value of the adjustment.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				

ADJUSTMENT INPUT ADJUSTED ID

Entity Name: ADJUSTMENT INPUT STAGING

Short Name:

AIS

Plural: ADJUSTMENT INPUT STAGING

Init. Volume: 30000

Avg. Volume: 30000

Max. Volume: 120000

Annual Growth Rate: 0%

Description:

This provides additional adjustment data to clients running against the VRIMS staging data. This entity acts as temporary storage where adjustment inputs can be entered that will ultimately override actual data values in the core data entities, for a single run of an adjustment. This data is provided to VDYP when it is run, which uses these values instead of the actual data.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* ADJUSTMENT INPUT STAGING ID	NUMERIC IDENTIFIER	N	NUMBER	10
Primary unique numeric identifier for a (staging area) VRI Adjusted Input.				
LOREY HEIGHT	HEIGHT - LOREY	Y	NUMBER	9,5
This is a statistically adjusted attribute that is input to VRIADJUST, a VDYP7 program that modifies the stand description that is required to project the polygon. This is the height in meters of the tree of average basal area.				
BASAL AREA 12.5CM	BASAL AREA	Y	NUMBER	10,6
This is a statistically adjusted attribute that is input to VRIADJUST, a VDYP7 program that modifies the stand description needed to project the polygon. This basal area is the total cross sectional area, at 1.3 metres height, in square meters per hectare				
WHOLE STEM VOLUME 7.5CM	VOLUME	Y	NUMBER	9,5
This is a statistically adjusted attribute that is input to VRIADJUST, a VDYP7 program that modifies the stand description that is required to project the polygon. This volume is the whole stem volume in cubic metres per hectare for all living trees above 7.5+cm dbh.				
WHOLE STEM VOLUME 12.5CM	VOLUME	Y	NUMBER	9,5
This is a statistically adjusted attribute that is input to VRIADJUST, a VDYP7 program that modifies the stand description that is required to project the polygon. This volume is the whole stem volume in cubic metres per hectare for all living trees above 12.5+cm dbh.				
CLOSE UTIL VOLUME 12.5CM	VOLUME	Y	NUMBER	9,5
This is a statistically adjusted attribute that is input to VRIADJUST, a VDYP7 program that modifies the stand description that is required to project the polygon. This volume is the whole stem volume net stumps and tops in cubic metres per hectare.				
CLOSE UTIL NET DECAY VOLUME	VOLUME	Y	NUMBER	9,5
This is a statistically adjusted attribute that is input to VRIADJUST, a VDYP7 program that modifies the stand description that is needed to project the polygon. This volume is the whole stem volume net stumps and tops, and decay, in cubic metres per hectare.				
CLOSE UTIL NET WASTE VOLUME	VOLUME	Y	NUMBER	9,5
This is a statistically adjusted attribute that is input to VRIADJUST, a VDYP7 program that modifies the stand description that is required to project the polygon. This volume is the whole stem volume net for utilization, decay and waste in cubic metres.				
INPUT MODE	INPUT - VRIADJUST MODE	Y	VARCHAR2	10
The input mode as used by VRIADJUST, a VDYP7 program that modifies the stand description that is needed to project the polygon.				
VRI ADJUST LAYER ID	NUMERIC IDENTIFIER	Y	NUMBER	10
Represents a layer that is to be adjusted by VDYP7's VRIADJUST application. When provided, the layer will override the actual layer value of the adjustment.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30

Entity Name:	ADJUSTMENT INPUT STAGING (cont'd)	<i>Short Name:</i>	AIS
---------------------	-----------------------------------	--------------------	-----

Updated by userid

* = *Attributes in primary unique identifier.*

Relationships:

Each Occurrence Of This Entity:

MUST BE is adjusted by one and only one VEGETATION COVER POLYGON STAGING

* = *Relationships in primary unique identifier.*

Unique Identifiers:

AIS PK	Primary	Y
--------	---------	---

ADJUSTMENT INPUT STAGING ID

APA PK Primary Y
ADJUSTMENT PROJECT ADJUSTED ID

APS PK Primary Y
ADJUSTMENT PROJECT STAGING ID

ADC PK Primary Y

ALPINE DESIGNATION CODE

Entity Name: BCLCS LEVEL1 CODE			Short Name:	BLC1
Plural:	BCLCS LEVEL1 CODE			
Init. Volume:	5	Avg. Volume:	5	Max. Volume: 5
			Annual Growth Rate:	10%

Description:

The code list for the first level of land cover classification. The codes are approved by the Resource Inventory Committee, RIC. Level 1 identifies a Vegetated or Non-vegetated state, with further dichotomous refinement to Level 5, which identifies the Vegetation Density Class related to Vegetated land, or specific Non-vegetated state cover such as beaches, mudflats etc.

Eg. N - Non-Vegetated
U - Unreported
V - Vegetated

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* BCLCS LEVEL1 CODE	CODETABLE CODE	N	VARCHAR2	10
The first level of the BC Land Cover Classification Scheme classifies the presence or absence of vegetation within the boundaries of the polygon. Presence or absence is recognized by the vertical projection of vegetation upon the land base within the polygon.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MAY BE first BCLCS level for one or more VEGETATION COVER POLYGON ADJ
MAY BE first BCLCS level for one or more VEGETATION COVER POLYGON EST
MAY BE first BCLCS level for one or more VEGETATION COVER POLYGON PRJ
MAY BE first BCLCS level for one or more VEGETATION COVER POLYGON STG
* = Relationships in primary unique identifier.

Unique Identifiers:

BLC1 PK	Primary	Y
BCLCS LEVEL1 CODE		

Entity Name: BCLCS LEVEL2 CODE			<i>Short Name:</i>	BLC2
<i>Plural:</i>	BCLCS LEVEL2 CODE			
<i>Init. Volume:</i>	5	<i>Avg. Volume:</i>	5	<i>Max. Volume:</i> 5
			<i>Annual Growth Rate:</i>	10%

Description:

The code list for the second level of land cover classification. Classifies the polygon as to the land cover type: treed or non-treed for vegetated polygons; land or water for non-vegetated polygons.

Eg. L - Land
N - Non-Treed
T - Treed
W - Water

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* BCLCS LEVEL2 CODE	CODETABLE CODE	N	VARCHAR2	10
The second level of the BC Land Cover Classification Scheme classifies the polygon as to the land cover type: treed or non-treed for vegetated polygons; land or water for non-vegetated polygons.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MAY BE second BCLCS level for one or more VEGETATION COVER POLYGON ADJ
MAY BE second BCLCS level for one or more VEGETATION COVER POLYGON EST
MAY BE second BCLCS level for one or more VEGETATION COVER POLYGON PRJ
MAY BE second BCLCS level for one or more VEGETATION COVER POLYGON STG
* = Relationships in primary unique identifier.

Unique Identifiers:

BLC2 PK	Primary	Y
BCLCS LEVEL2 CODE		

Entity Name: BCLCS LEVEL3 CODE			<i>Short Name:</i>	BLC3
<i>Plural:</i>	BCLCS LEVEL3 CODE			
<i>Init. Volume:</i>	5	<i>Avg. Volume:</i>	5	<i>Max. Volume:</i> 5
			<i>Annual Growth Rate:</i>	10%

Description:

The code list for the third level of land cover classification. The location of the polygon relative to elevation and drainage, and is described as either alpine, wetland, or upland. In rare cases, the polygon may be alpine wetland.

Eg. A - Alpine
U - Upland
W - Wetland

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* BCLCS LEVEL3 CODE	CODETABLE CODE	N	VARCHAR2	10
The third level of the BC Land Cover Classification Scheme classifies the polygon as to the the location of the polygon relative to elevation and drainage, and is described as either alpine, wetland, or upland. In rare cases, the polygon may be alpine wetland.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MAY BE third BCLCS level for one or more VEGETATION COVER POLYGON ADJ
MAY BE third BCLCS level for one or more VEGETATION COVER POLYGON EST
MAY BE third BCLCS level for one or more VEGETATION COVER POLYGON PRJ
MAY BE third BCLCS level for one or more VEGETATION COVER POLYGON STG
* = Relationships in primary unique identifier.

Unique Identifiers:

BLC3 PK	Primary	Y
BCLCS LEVEL3 CODE		

Entity Name: BCLCS LEVEL4 CODE			Short Name:	BLC4
Plural:	BCLCS LEVEL4 CODE			
Init. Volume:	15	Avg. Volume:	15	Max. Volume: 15
			Annual Growth Rate:	10%

Description:

The code list for the fourth level of land cover classification. Classifies the vegetation types and Non-Vegetated cover types (as described by the presence of distinct types upon the land base within the polygon).

- Eg. BL - Bryoid - Lichens
- BM - Bryoid - Moss
- BY - Bryoids
- EL - Exposed Land
- HE - Herb
- HF - Herb - Forbs
- HG - Herb - Graminoids
- RO - Rock/Rubble
- SI - Snow/Ice
- SL - Shrub - Low
- ST - Shrub - Tall
- TB - Treed - Broadleaf
- TC - Treed - Coniferous
- TM - Treed - Mixed

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* BCLCS LEVEL4 CODE	CODETABLE CODE	N	VARCHAR2	10
The fourth level of the BC Land Cover Classification Scheme classifies the vegetation types and Non-Vegetated cover types (as described by the presence of distinct types upon the land base within the polygon).				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

- MAY BE fourth BCLCS level for one or more VEGETATION COVER POLYGON ADJ
 - MAY BE fourth BCLCS level for one or more VEGETATION COVER POLYGON EST
 - MAY BE fourth BCLCS level for one or more VEGETATION COVER POLYGON PRJ
 - MAY BE fourth BCLCS level for one or more VEGETATION COVER POLYGON STG
- * = Relationships in primary unique identifier.

Unique Identifiers:

BLC4 PK	Primary	Y
BCLCS LEVEL4 CODE		

Entity Name:	BCLCS LEVEL5 CODE			Short Name:	BLC5
Plural:	BCLCS LEVEL5 CODE				
Init. Volume:	40	Avg. Volume:	40	Max. Volume:	40
				Annual Growth Rate:	10%

Description:

The code list for the fifth level of land cover classification. Classifies the vegetation density classes and Non-Vegetated categories.

- Eg. AP - Airport
- BE - Beach
- BI - Blockfield
- BR - Bedrock
- BU - Burned Area
- CB - Cutbank
- CL - Closed
- DE - Dense
- ES - Exposed Soils
- GL - Glacier
- GP - Gravel Pit
- LA - Lake
- LB - Lava Bed
- LL - Landing
- LS - Pond or Lake Sediments
- MI - Open Pit Mine
- MN - Moraine
- MU - Mudflat Sediment
- MZ - Rubbly Mine Spoils
- OC - Ocean
- OP - Open
- OT - Other
- PN - Snow Cover
- RE - Reservoir
- RI - River/Stream
- RM - Reservoir Margin
- RN - Railway Surface
- RS - River Sediments
- RZ - Road Surface
- SP - Sparse
- TA - Talus
- TZ - Tailings
- UR - Urban

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* BCLCS LEVEL5 CODE	CODETABLE CODE	N	VARCHAR2	10
The fifth level of the BC Land Cover Classification Scheme classifies the vegetation density classes and Non-Vegetated categories.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
* = Attributes in primary unique identifier.				

Relationships:

Entity Name:	BCLCS LEVEL5 CODE (cont'd)	<i>Short Name:</i>	BLC5
---------------------	----------------------------	--------------------	------

Each Occurrence Of This Entity:

MAY BE fifth BCLCS level for one or more VEGETATION COVER POLYGON ADJ
MAY BE fifth BCLCS level for one or more VEGETATION COVER POLYGON EST
MAY BE fifth BCLCS level for one or more VEGETATION COVER POLYGON PRJ
MAY BE fifth BCLCS level for one or more VEGETATION COVER POLYGON STG
* = Relationships in primary unique identifier.

Unique Identifiers:

BLC5 PK	Primary	Y
BCLCS LEVEL5 CODE		

Entity Name: BEC ZONE CODE			Short Name:	BZC
Plural:	BEC ZONE CODE			
Init. Volume:	15	Avg. Volume:	20	Max. Volume: 25
			Annual Growth Rate:	10%

Description:

A list of codes for the Biogeoclimatic Classification System. This is a method to classify and manage sites on an ecosystem-specific basis. There are 14 Together, the three levels Bio, Geo and Climatic are used to classify any site in BC into an ecosystem.

- Eg. AT - Alpine Tundra
- BG - Bunchgrass
- BWBS - Boreal White and Black Spruce
- CDF - Coastal Douglas Fir
- CWH - Coastal Western Hemlock
- ESSF - Engelmann Spruce - Subalpine Fir
- ICH - Interior Cedar - Hemlock
- IDF - Interior Douglas Fir
- MH - Mountain Hemlock
- MS - Montane Spruce
- PP - Ponderosa Pine
- SBPS - Sub-Boreal Pine - Spruce
- SBS - Sub-Boreal Spruce
- SWB - Spruce - Willow - Birch

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* BEC ZONE CODE	CODETABLE CODE	N	VARCHAR2	10
Biogeoclimatic Classification System is a method to classify and manage sites on an ecosystem-specific basis. There are 14 Together, the three levels Bio, Geo and Climatic are used to classify any site in BC into an ecosystem. In British Columbia, there are 14 Biogeoclimatic zones identified.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

- MAY BE BEC Zone for one or more VEGETATION COVER POLYGON ADJ
 - MAY BE bec zone for one or more VEGETATION COVER POLYGON EST
 - MAY BE BEC Zone for one or more VEGETATION COVER POLYGON PRJ
 - MAY BE BEC zone for one or more VEGETATION COVER POLYGON STG
- * = Relationships in primary unique identifier.

Unique Identifiers:

- BZC PK
- Primary* Y
- BEC ZONE CODE

Entity Name: COVER PATTERN CODE

Short Name:

CP

Plural: COVER PATTERN CODE

Init. Volume: 10

Avg. Volume: 10

Max. Volume: 20

Annual Growth Rate: 10%

Description:

A list of codes that describes the cover pattern code that describes the spatial distribution of the species within the polygon.

Eg. 0 - None

1 - Single To Very Few Occurrences Of Limited Extent, Circular To Irregular Shape

2 - Single To Very Few Occurrences Of Limited Extent, Linear Or Elongated Shape

3 - Several Sporadic Occurrences Of Limited Extent, Circular To Irregular Shape

4 - Several Sporadic Occurrences Of Limited Extent, Linear Or Elongated Shape

5 - Intimately Intermixed Units, Often With Gradational Transitions From One To The Other

6 - Discontinuous But Extensive Occurrences, Parallel To Sub-Parallel Elongated In Shape

7 - Limited Continuous Occurrence With Few Inclusions

8 - Continuous Occurrence With Several Inclusions.

9 - Continuous Occurrence With Very Few Inclusions

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u> <u>Format</u>	<u>Length</u>
* COVER PATTERN CODE	CODETABLE CODE	N VARCHAR2	10
A code that describes the spatial distribution of the species within the polygon. Examples include clumps of herbaceous species on rocky outcrops, scattered patches or individual trees or solid, continuous cover.			
DESCRIPTION	CODETABLE DESCRIPTION	N VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.			
EFFECTIVE DATE	DATE TIME	N DATE	
Effective date/time			
EXPIRY DATE	DATE TIME	N DATE	
Expiry date/time			
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N DATE	
Update date/time			

* = Attributes in primary unique identifier.

Relationships:Each Occurrence Of This Entity:

MAY BE non veg cover pattern for one or more NON VEGETATIVE COVER ADJ

MAY BE non veg cover pattern for one or more NON VEGETATIVE COVER EST

MAY BE non veg cover pattern for one or more NON VEGETATIVE COVER PRJ

MAY BE non veg cover pattern for one or more NON VEGETATIVE COVER STG

MAY BE tree cover pattern for one or more TREE COVER LAYER ADJUSTED

MAY BE tree cover pattern for one or more TREE COVER LAYER ESTIMATED

MAY BE tree cover pattern for one or more TREE COVER LAYER PROJECTED

MAY BE tree cover pattern for one or more TREE COVER LAYER STAGING

MAY BE herb cover pattern for one or more VEGETATION COVER POLYGON ADJ

MAY BE shrub pattern for one or more VEGETATION COVER POLYGON ADJ

MAY BE herb cover pattern for one or more VEGETATION COVER POLYGON EST

MAY BE shrub pattern for one or more VEGETATION COVER POLYGON EST

MAY BE herb cover pattern for one or more VEGETATION COVER POLYGON PRJ

MAY BE shrub pattern for one or more VEGETATION COVER POLYGON PRJ

MAY BE herb pattern for one or more VEGETATION COVER POLYGON STG

MAY BE shrub pattern for one or more VEGETATION COVER POLYGON STG

* = Relationships in primary unique identifier.

Entity Name:	COVER PATTERN CODE (cont'd)	<i>Short Name:</i>	CP
---------------------	-----------------------------	--------------------	----

Unique Identifiers:

HCP PK

PrimaryY

COVER PATTERN CODE

Entity Name:	DATA CAPTURE METHOD CODE	Short Name:	DCMC
Plural:	DATA CAPTURE METHOD CODE		
Init. Volume:	20	Avg. Volume:	30
		Max. Volume:	40
		Annual Growth Rate:	10%

Description:

A list of codes that identify the method of capture for the feature.

- Eg. 0 - Not Accounted For
1 - Landsat5
2 - Landsat7
3 - SPOT
4 - Photogrammetric
5 - Differential GPS
6 - Non-Differential GPS
7 - Digitizing
8 - Scanning
9 - Monorestitution
10 - Tight Chaining
11 - Results
12 - Other

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* DATA CAPTURE METHOD CODE	CODETABLE CODE	N	VARCHAR2	10
A code to identify the method of capture for the feature. d.g. DIGI - Digitized.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

- MAY BE describes data capture for one or more DISTURBANCE EVENT
MAY BE data capture method for one or more FOREST COVER OBJECT
MAY BE method of data capture for one or more FOREST COVER OBJECT STAGING
* = Relationships in primary unique identifier.

Unique Identifiers:

DCMC PK	Primary	Y
DATA CAPTURE METHOD CODE		

Entity Name: DATA SOURCE AGE CODE**Short Name:**

DSAC

Plural: DATA SOURCE AGE CODE**Init. Volume:** 25**Avg. Volume:** 30**Max. Volume:** 40**Annual Growth Rate:** 10%**Description:**

A list of codes for the source of data used for the interpretation of age and the derivation of the year of origin.

Eg. 0 - Photo-interpretation

1 - Aircall, High Level Observation

2 - Aircall, Low Level Observation

3 - Phase 1 photo sample (pre-1990)

4 - Inventory Ground Call

5 - Standard fixed radius sample (pre-1979)

6 - Phase 2 or Phase 3 sample (pre-1990)

7 - Silviculture Survey

8 - Ground Observation

9 - Research plots (e.g. Sx trials, ecological site description)

10 - Valuation cruise plot(s)

11 - A record from a silv.information system that summarizes the stand structure following an activity or treatment.

12 - Disturbance which is classified as NSR. No additional information other than type & year of disturbance.

13 - Managed stand sample

14 - Ground call, 2 or more points

15 - Null

16 - Vegetation sample

17 - Vegetation ground call

18 - Vegetation air call

19 - Natural growth sample

20 - Volume and depletion sample

22 - Photogrammetrically captured information

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u> <u>Format</u>	<u>Length</u>
* DATA SOURCE AGE CODE	CODETABLE CODE	N VARCHAR2	10
The source of data used for the interpretation of age and the derivation of the year of origin.			
DESCRIPTION	CODETABLE DESCRIPTION	N VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.			
EFFECTIVE DATE	DATE TIME	N DATE	
Effective date/time			
EXPIRY DATE	DATE TIME	N DATE	
Expiry date/time			
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N DATE	
Update date/time			
* = Attributes in primary unique identifier.			

Relationships:Each Occurrence Of This Entity:

MAY BE source age for one or more TREE SPECIES ADJUSTED

MAY BE age sourced for one or more TREE SPECIES ESTIMATED

MAY BE source age for one or more TREE SPECIES PROJECTED

MAY BE source age for one or more TREE SPECIES STAGING

* = Relationships in primary unique identifier.

Unique Identifiers:

DSAC PK

Primary Y

DATA SOURCE AGE CODE

Entity Name: DATA SOURCE BASAL AREA CODE			Short Name:	DBAC
Plural:	DATA SOURCE BASAL AREA CODE			
Init. Volume:	25	Avg. Volume:	30	Max. Volume: 40
			Annual Growth Rate:	10%

Description:

- A list of codes for the source of data used for the interpretation of the basal area.
- Eg. 0 - Photo Interpretation
1 - Aircall, High Level Observation
2 - Aircall, Low Level Observation
3 - Phase 1 photo sample(pre-1990)
4 - Inventory Ground Call
5 - Standard fixed radius sample(pre-1979)
6 - Phase 2 or Phase 3 sample (pre-1990)
7 - Silviculture Survey 8, Ground Observation
9 - Research plots(e.g. Sx trials, ecological site description)
10 - Valuation Cruise Plot(s)
11 - A record from a silv.information system that summarizes the stand structure following an activity or treatment.
12 - Disturbance which is classified as NSR. No additional information other than type & year of distrubance.
13 - Managed stand sample
14 - Ground call, 2 or more points
16 - Vegetation sample
17 - Vegetation ground call
18 - Vegetation air call
19 - Natural growth sample
20 - Volume and depletion sample

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* DATA SOURCE BASAL AREA CODE	CODETABLE CODE	N	VARCHAR2	10
The source of data used for the interpretation of the basal area.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

- MAY BE basal area for one or more TREE COVER LAYER ADJUSTED
MAY BE source of basal area for one or more TREE COVER LAYER ESTIMATED
MAY BE basal area data source for one or more TREE COVER LAYER PROJECTED
MAY BE basal area source for one or more TREE COVER LAYER STAGING
* = Relationships in primary unique identifier.

Unique Identifiers:

DBAC PK	Primary	Y
DATA SOURCE BASAL AREA CODE		

Entity Name: DATA SOURCE ECOSYS CLASS CODE			Short Name:	DSEC
Plural:	DATA SOURCE ECOSYS CLASS CODE			
Init. Volume:	25	Avg. Volume:	30	Max. Volume: 40
			Annual Growth Rate:	10%

Description:

A list of codes that describes the source of the data used in the interpretation of the ecological attributes (SURFACE EXPRESSION, MODIFYING PROCESS, SITE POSITION MESO, ALPINE DESIGNATION, and SOIL NUTRIENT REGIME) that describe the polygon.

- Eg. 0 - Photo-interpretation
1 - Aircall, High Level Observation
2 - Aircall, Low Level Observation
3 - Phase 1 photo sample (pre-1990)
4 - Inventory Ground Call
5 - Standard fixed radius sample (pre-1979)
6 - Phase 2 or Phase 3 sample (pre-1990)
7 - Silviculture Survey
8 - Ground Observation
9 - Research plots (e.g. Sx trials, ecological site description)
10 - Valuation cruise plot(s)
11 - A record from a silv.information system that summarizes the stand structure following an activity or treatment.
12 - Disturbance which is classified as NSR. No additional information other than type & year of distrubance.
14 - Ground call, 2 or more points
16 - Vegetation sample
17 - Vegetation ground call
18 - Vegetation air call

Attribtes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* DATA SOURCE ECOSYS CLASS CODE	CODETABLE CODE	N	VARCHAR2	10
The source of the data used in the interpretation of the ecological attributes (SURFACE EXPRESSION, MODIFYING PROCESS, SITE POSITION MESO, ALPINE DESIGNATION, and SOIL NUTRIENT REGIME) that describe the polygon.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

- MAY BE ecosystem data source for one or more VEGETATION COVER POLYGON ADJ
MAY BE ecosystem class source for one or more VEGETATION COVER POLYGON EST
MAY BE ecosystem class data source for one or more VEGETATION COVER POLYGON PRJ
MAY BE ecosytem class data source for one or more VEGETATION COVER POLYGON STG
* = Relationships in primary unique identifier.

Unique Identifiers:

DSEC PK	Primary	Y
DATA SOURCE ECOSYS CLASS CODE		

Entity Name: DATA SOURCE HEIGHT CODE	<i>Short Name:</i>	DSHC
---	--------------------	------

<i>Plural:</i> DATA SOURCE HEIGHT CODE
--

<i>Init. Volume:</i> 25	<i>Avg. Volume:</i> 30	<i>Max. Volume:</i> 40	<i>Annual Growth Rate:</i> 10%
-------------------------	------------------------	------------------------	--------------------------------

Description:

A list of codes for the source of data used for the interpretation of height.

Eg. 0 - Photo-interpretation

1 - Aircall, High Level Observation

2 - Aircall, Low Level Observation

3 - Phase 1 photo sample (pre-1990)

4 - Inventory Ground Call

5 - Standard fixed radius sample (pre-1979)

6 - Phase 2 or Phase 3 sample (pre-1990)

7 - Silviculture Survey

8 - Ground Observation

9 - Research plots (e.g. Sx trials, ecological site description)

10 - Valuation cruise plot(s)

11 - A record from a silv.information system that summarizes the stand structure following an activity or treatment.

12 - Disturbance which is classified as NSR. No additional information other than type & year of disturbance.

13 - Managed stand sample

14 - Ground call, 2 or more points

15 - Null

16 - Vegetation sample

17 - Vegetation ground call

18 - Vegetation air call

19 - Natural growth sample

20 - Volume and depletion sample

22 - Photogrammetrically captured information

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u> <u>Format</u>	<u>Length</u>
* DATA SOURCE HEIGHT CODE	CODETABLE CODE	N VARCHAR2	10
Code representation for the source of data used for the interpretation of height.			
DESCRIPTION	CODETABLE DESCRIPTION	N VARCHAR2	120
Description of the source of data used for the interpretation of height.			
EFFECTIVE DATE	DATE TIME	N DATE	
Effective date/time			
EXPIRY DATE	DATE TIME	N DATE	
Expiry date/time			
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N DATE	
Update date/time			

* = Attributes in primary unique identifier.

Relationships:Each Occurrence Of This Entity:

MAY BE source height for one or more TREE SPECIES ADJUSTED

MAY BE source of height for one or more TREE SPECIES ESTIMATED

MAY BE source height for one or more TREE SPECIES PROJECTED

MAY BE source height for one or more TREE SPECIES STAGING

* = Relationships in primary unique identifier.

Unique Identifiers:

DSHC PK	<i>Primary</i> Y
---------	------------------

DATA SOURCE HEIGHT CODE

Entity Name: DATA SOURCE INTERPRETED CODE

Short Name:

DSIC

Plural: DATA SOURCE INTERPRETED CODE

Init. Volume: 25

Avg. Volume: 30

Max. Volume: 40

Annual Growth Rate: 10%

Description:

A list of codes that describe the origin of the information that contributed to the determination of the VRI attributes.

Eg. 0 - Photo Interpretation

1 - Aircall, High Level Observation

2 - Aircall, Low Level Observation

3 - Phase 1 photo sample(pre-1990)

4 - Inventory Ground Call

5 - Standard fixed radius sample(pre-1979)

6 - Phase 2 or Phase 3 sample (pre-1990)

7 - Silviculture Survey

8 - Ground Observation

9 - Research plots(e.g. Sx trials, ecological site description)

10 - Valuation Cruise Plot(s)

11 - A record from a silv.information system that summarizes the stand structure following an activity or treatment.

12 - Disturbance which is classified as NSR. No additional information other than type & year of disturbance.

13 - Managed stand sample

14 - Ground call, 2 or more points

16 - Vegetation sample

17 - Vegetation ground call

18 - Vegetation air call

19 - Natural growth sample

20 - Volume and depletion sample

22 - Photogrammetrically captured information

71 - Free Growing Survey

72 - Conditional Free Growing

73 - Not Free Growing

74 - Pre-Stand Tending

75 - Naturally Regenerated

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* DATA SOURCE INTERPRETED CODE	CODETABLE CODE	N	VARCHAR2	10
A code describing the origin of the information that contributed to the determination of the VRI attributes.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				

* = Attributes in primary unique identifier.

Relationships:Each Occurrence Of This Entity:

MAY BE interpreted data source for one or more TREE COVER LAYER ADJUSTED

MAY BE interpreted data source for one or more TREE COVER LAYER ESTIMATED

MAY BE interpreted data source for one or more TREE COVER LAYER PROJECTED

MAY BE interpreted data source for one or more TREE COVER LAYER STAGING

* = Relationships in primary unique identifier.

Entity Name:	DATA SOURCE INTERPRETED CODE (cont'd)	<i>Short Name:</i>	DSIC
---------------------	---------------------------------------	--------------------	------

Unique Identifiers:

DSIC PK	Primary	Y
---------	---------	---

DATA SOURCE INTERPRETED CODE

Entity Name: DATA SRC VRI LIVE STEM HA CODE				Short Name:	DSSH
Plural:	DATA SRC VRI LIVE STEM HA CODE				
Init. Volume:	25	Avg. Volume:	30	Max. Volume:	40
				Annual Growth Rate:	10%

Description:

A list of codes for the source of the data that was used for the interpretation of the VRI live stems per hectare, or stand density.

- Eg. 0 - Photo Interpretation
1 - Aircall, High Level Observation
10 - Valuation Cruise Plot(s)
11 - A record from a silv.information system that summarizes the stand structure following an activity or treatment.
12 - Disturbance which is classified as NSR. No additional information other than type & year of distrubance.
13 - Managed stand sample
14 - Ground call, 2 or more points
16 - Vegetation sample
17 - Vegetation ground call
18 - Vegetation air call
19 - Natural growth sample
2 - Aircall, Low Level Observation
20 - Volume and depletion sample
3 - Phase 1 photo sample(pre-1990)
4 - Inventory Ground Call
5 - Standard fixed radius sample(pre-1979)
6 - Phase 2 or Phase 3 sample (pre-1990)
7 - Silviculture Survey 8, Ground Observation
9 - Research plots(e.g. Sx trials, ecological site description)

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* DATA SRC VRI LIVE STEM HA CODE	CODETABLE CODE	N	VARCHAR2	10
Code representation of the source of the data that was used for the interpretation of the VRI live stems per hectare, or stand density.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Description of the source of the data that was used for the interpretation of the VRI live stems per hectare, or stand density.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

- MAY BE stems per ha for one or more TREE COVER LAYER ADJUSTED
MAY BE source of stems per ha for one or more TREE COVER LAYER ESTIMATED
MAY BE stems per ha data source for one or more TREE COVER LAYER PROJECTED
MAY BE source of stems per ha for one or more TREE COVER LAYER STAGING
* = Relationships in primary unique identifier.

Unique Identifiers:

DSSH PK	Primary	Y
DATA SRC VRI LIVE STEM HA CODE		

Entity Name: DISTURBANCE EVENT				Short Name:	DE
Plural:	DISTURBANCE EVENT				
Init. Volume:	152000	Avg. Volume:	160000	Max. Volume:	170000
				Annual Growth Rate:	5%

Description:

Describes an event where a stand has been disturbed by some force. This entity provides a historical reference about a polygon that was involved in a disturbance, which may no longer be present in the system. The timeline of interest for a disturbance polygon will likely be significantly longer than for a regular polygon. As such, this entity provides means to store the disturbance geometry and critical disturbance attribution without requiring retention of the entire base polygon's information. While a Disturbance Event may not always be present for a polygon (or vice-versa), it is initially created in parallel to a regular polygon.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* DISTURBANCE EVENT ID	SDE NUMERIC IDENTIFIER	N	NUMBER	38
Primary unique numeric identifier for a disturbance event.				
GEOMETRY	GEOMETRY	Y	NUMBER	38
A spatial polygon feature used to store the map component of the Vegetation Cover area.This is a ArcSDE spatial column. NOTE: It can be linear, polygonal or point.				
INTERPRETER	USERID	N	VARCHAR2	30
The name of the person who provided the estimates for the data associated with each polygon.				
INTERPRETATION DATE	DATE TIME	N	DATE	
The date on which the polygon estimates were photo interpreted.				
PROJECT NAME	PROJECT NAME	N	VARCHAR2	100
The business assigned name of the project. The name typically reflects a Timber Supply Area, an initiating Agency, or a land area.				
REFERENCE YEAR	NUMERIC YEAR	Y	NUMBER	4,0
The year of the photo or source survey that was used to generate the VRI attributes.				
DISTURBANCE START YEAR	DATE TIME	Y	DATE	
Starting year of the disturbance event.				
DISTURBANCE END YEAR	DATE TIME	Y	DATE	
Ending year of the disturbance event.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

- MAY BE data capture method of one and only one DATA CAPTURE METHOD CODE
 - MAY BE disturbed by one and only one DISTURBANCE TYPE CODE
 - MAY BE identified by one and only one FOREST COVER OBJECT
 - MAY BE disturbed by one and only one VRIMS DISTURBANCE CODE
- * = Relationships in primary unique identifier.

Unique Identifiers:

DE PK	Primary	Y
DISTURBANCE EVENT ID		

DTC PK	Primary	Y
DISTURBANCE TYPE CODE		

Entity Name:	ESTIMATED SINDEXTM SOURCE CODE			Short Name:	ESRC
Plural:	ESTIMATED SINDEXTM SOURCE CODE				
Init. Volume:	100	Avg. Volume:	120	Max. Volume:	150
				Annual Growth Rate:	10%

Description:

A list of codes that describe the site index source that indicates the method used for obtaining an adjusted site index. The adjusted site index source identifies the method by which the site index is adjusted, indicates the reliability of the adjustment and classifies the source.

- Eg. A - Adjacent stand
- E - Ecological correlation
- H - Historic
- I - Growth intercept
- S - Silviculture section
- A - POPLAR
- AC - POPLAR
- ACB - BALSAM POPLAR
- ACT - BLACK COTTONWOOD
- AT - TREMBLING ASPEN
- AX - Poplar Hybrid
- B - True Fir
- BA - AMABILIS FIR
- BB - Balsam Fir
- BG - GRAND FIR
- BL - SUBALPINE FIR
- BN - Noble Fir
- C - CEDAR
- CW - WESTERN RED CEDAR
- D - ALDER
- DG - GREEN/SITKA ALDER (N)
- DM - MOUNTAIN ALDER (N)
- DR - RED ALDER
- E - BIRCH
- EA - ALASKA PAPER BIRCH
- EB - SCRUB BIRCH
- EP - PAPER BIRCH
- ES - SWAMP BIRCH
- EW - WATER BIRCH
- EX - BIRCH HYBRID
- EXP - ALASKA PAPER X PAPER
- EXW - WATER X PAPER
- F - Douglas-Fir
- FD - Douglas-Fir
- FDC - DOUGLAS-FIR (COAST)
- FDI - DOUGLAS-FIR (INTERIOR)
- G - DOGWOOD (N)
- GP - FLOWERING DOGWOOD (N)
- GR - RED-OSIER DOGWOOD
- H - HEMLOCK
- HM - MOUNTAIN HEMLOCK
- HW - WESTERN HEMLOCK
- HX - HEMLOCK HYBRID
- HXM - WESTERN X MOUNTAIN
- J - JUNIPER (N)
- JD - COMMON JUNIPER
- JH - CREEPING JUNIPER
- JR - ROCKY MOUNTAIN JUNIPER (N)
- K - CASCARA (N)
- KC - CASCARA (N)
- L - LARCH
- LA - ALPINE LARCH
- LD - DAHURIAN LARCH

Entity Name:	ESTIMATED SINDEXTABLE SOURCE CODE (cont'd)	Short Name:	ESRC
---------------------	--	-------------	------

LS - SIBERIAN LARCH
LT - TAMARACK
LW - WESTERN LARCH
M - MAPLE
MB - BIGLEAF MAPLE
MR - DOUGLAS MAPLE (N)
MV - VINE MAPLE (N)
P - PINE
PA - WHITEBARK PINE
PF - LIMBER PINE
PJ - JACK PINE
PL - LODGEPOLE PINE
PLC - LODGEPOLE PINE (COAST)
PLI - LODGEPOLE PINE (INTERIOR)
PR - Red Pine
PW - WESTERN WHITE PINE
PX - PINE HYBRID
PXJ - LODGEPOLE X JACK
PY - YELLOW PINE
Q - OAK
QG - GARRY OAK
RA - ARBUTUS (N)
S - SPRUCE
SA - NORWAY SPRUCE
SB - BLACK SPRUCE
SE - ENGELMANN SPRUCE
SS - SITKA SPRUCE
SW - WHITE SPRUCE
SX - SPRUCE HYBRID
SXB - WHITE X BLACK
SXE - ENGELMA
NN X SITKA
SXL - WHITE X SITKA (PICEA X LUTZII)
SXS - SITKA X UNKNOWN HYBRID
SXW - WHITE X ENGELMANN
SXX - WHITE X ENGELMANN X SITKA
T - YEW
TW - WESTERN YEW
UP - PACIFIC CRAB APPLE (MALUS FUSCA)
V - CHERRY (N)
VB - BITTER CHERRY (N)
VP - PIN CHERRY
VW - CHOKE CHERRY
W - WILLOW
WA - BARCLAY'S WILLOW
WB - BEBB'S WILLOW
WD - GREY-LEAVED WILLOW
WS - SCOULER'S WILLOW
WT - TEA-LEAVED WILLOW
Y - CYPRESS
YC - YELLOW CEDAR

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* ESTIMATED SINDEXTABLE SOURCE CODE	CODETABLE CODE	N	VARCHAR2	10
Site index source indicates the method used for obtaining an adjusted site index. The adjusted site index source identifies the method by which the site index is adjusted, indicates the reliability of the adjustment and classifies the source				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120

Entity Name:	ESTIMATED SINDEXTREE COVER LAYER SOURCE CODE (cont'd)	Short Name:	ESRC
---------------------	---	-------------	------

Provides the description for the code. This is the human readable form of the code.		
EXPIRY DATE	DATE TIME	N DATE
Expiry date/time		
EFFECTIVE DATE	DATE TIME	N DATE
Effective date/time		
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N DATE
Update date/time		
* = Attributes in primary unique identifier.		

Relationships:

Each Occurrence Of This Entity:

MAY BE site index source for one or more TREE COVER LAYER ADJUSTED
MAY BE site index source for one or more TREE COVER LAYER ESTIMATED
MAY BE site index source for one or more TREE COVER LAYER PROJECTED
MAY BE site index source for one or more TREE COVER LAYER STAGING
* = Relationships in primary unique identifier.

Unique Identifiers:

ESRC PK	Primary	Y
ESTIMATED SINDEXTREE COVER LAYER SOURCE CODE		

Entity Name: FOREST COVER OBJECT*Short Name:*

FCO

Plural: FOREST COVER OBJECT*Init. Volume:* 3800000*Avg. Volume:* 4000000*Max. Volume:* 4200000*Annual Growth Rate:* 5%**Description:**

This entity represents a Forest Cover Polygon that has been successfully integrated into the database, and maintains the unique business identification of that polygon. Each polygon represents an area of land identified spatially that is measured by a Vegetation Resource Inventory activity.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* FOREST COVER OBJECT ID	SDE NUMERIC IDENTIFIER	N	NUMBER	38
The unique business identification of a forest cover polygon. Each polygon represents an area of land identified spatially that is measured by a Vegetation Resource Inventory activity.[GRY Description]A required attribute of feature classes and object classes in a geodatabase. This attribute is added to a SDE layer that was not previously created as part of a geodatabase but is now being registered with a geodatabase.				
OPENING NUMBER	OPENING NUMBER	Y	VARCHAR2	4
The OPENING_NUMBER is from RESULTS. It may or may not be present.				
OPENING ID	RESULTS OPENING ID	Y	NUMBER	10,0
The OPENING_ID is the identifier from RESULTS.				
POLYGON NUMBER	POLYGON NUMBER	N	VARCHAR2	16
The POLYGON_NUMBER is a human readable identifier. Generated by a POLYGON_ALIAS_NAME function.				
GEOMETRY	GEOMETRY	Y	NUMBER	38
This is the polygon that represents a vegetation resource polygon. A spatial polygon feature used to store the map component of the Vegetation Cover area.This is a ArcSDE spatial column. NOTE: It can be linear, polygonal or point.				
POLYGON AREA	POLYGON AREA	Y	NUMBER	15,3
The area of a polygon; usually derived from geographic information system processing software in hectares.				
INTERPRETER	USERID	N	VARCHAR2	30
The user id of the individual who provided the estimates for the data associated with each polygon.				
INTERPRETATION DATE	DATE TIME	N	DATE	
The date on which the polygon estimates were photo interpreted.				
PROJECT NAME	PROJECT NAME	N	VARCHAR2	100
The business assigned name of the project. The name typically reflects a Timber Supply Area, an initiating Agency, or a land area.				
EXPIRY DATE	DATE TIME	Y	DATE	
The date/time from which the spatial object is retired.				
CREATED DATE	DATE TIME	N	DATE	
The date/time from the spatial object was created. This may be different from the data/time the entry containing the spatial object was created.				
SLIVER IND	INDICATOR	N	VARCHAR2	1
If a polygon is a sliver then the indication will be 'Y'. This flag will only be set if there is no computational means to either merge the sliver with an adjacent polygon, or integrate it by some other means. The slivers will have to be manually identified and manually dealt with.				
FREE TO GROW IND	INDICATOR	N	VARCHAR2	1
Indicates that the polygon has achieved Free To Grow status, which marks the milestone where a stand is capable of growing and should be allowed to do so, without intervention.				
DISTURBANCE START YEAR	DATE TIME	Y	DATE	
Starting year of the disturbance event.				
DISTURBANCE END YEAR	DATE TIME	Y	DATE	

Entity Name: FOREST COVER OBJECT (cont'd)			Short Name:	FCO
Ending year of the disturbance event.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

- MAY BE data captured by means of one and only one DATA CAPTURE METHOD CODE
 - MAY BE disturbance for one and only one DISTURBANCE EVENT
 - MAY BE of disturbance type one and only one DISTURBANCE TYPE CODE
 - MUST BE inventory standard described by one and only one INVENTORY STANDARD CODE
 - MUST BE source for one and only one VEGETATION COVER POLYGON ADJUSTED
 - MUST BE source for one and only one VEGETATION COVER POLYGON ESTIMATED
 - MUST BE source for one and only one VEGETATION COVER POLYGON PROJECTED
 - MAY BE identified for processing by one or more VRIMS BATCH PROCESS POLYGON
 - MAY BE disturbed by one and only one VRIMS DISTURBANCE CODE
 - MUST BE Represented by one or more VRIMS MAPSHEET LINK
 - MAY BE created by one and only one VRIMS PACKAGE TRANSACTION
 - MAY BE retired by one and only one VRIMS PACKAGE TRANSACTION
 - MAY BE extracted during one or more VRIMS POLYGON TRANSACTION
- * = Relationships in primary unique identifier.

Unique Identifiers:

FCO PK	Primary	Y
FOREST COVER OBJECT ID		

Entity Name: FOREST COVER OBJECT STAGING**Short Name:**

FCOS

Plural: FOREST COVER OBJECT STAGING**Init. Volume:** 30000**Avg. Volume:** 30000**Max. Volume:** 120000**Annual Growth Rate:** 0%**Description:**

This entity represents a polygon that has been loaded for preparation, but has not been processed for integration, and maintains the unique business identification of a forest cover polygon. Each polygon represents an area of land identified spatially that is measured by a Vegetation Resource Inventory activity. Staged polygons are purged immediately once a transaction has been approved and completed. However, they may need to be stored indefinitely, depending on the duration required to have the polygon approved for integration.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* FOREST COVER OBJECT STAGING ID	SDE NUMERIC IDENTIFIER	N	NUMBER	38
The unique business identification of a forest cover polygon. Each polygon represents an area of land identified spatially that is measured by a Vegetation Resource Inventory activity.[GRY Description]A required attribute of feature classes and object classes in a geodatabase. This attribute is added to a SDE layer that was not previously created as part of a geodatabase but is now being registered with a geodatabase.				
OPENING NUMBER	OPENING NUMBER	Y	VARCHAR2	4
The OPENING_NUMBER is from RESULTS, when available.				
OPENING ID	RESULTS OPENING ID	Y	NUMBER	10,0
The OPENING_ID is the identifier from RESULTS.				
POLYGON NUMBER	POLYGON NUMBER	Y	VARCHAR2	16
The POLYGON_NUMBER is a human readable identifier. Generated by a POLYGON_ALIAS_NAME function.				
GEOMETRY	GEOMETRY	Y	NUMBER	38
This is the polygon representation of a forest vegetation polygon. A spatial polygon feature used to store the map component of the Vegetation Cover area.This is a ArcSDE spatial column. NOTE: It can be linear, polygonal or point.				
POLYGON AREA	POLYGON AREA	Y	NUMBER	15,3
The area of a polygon; usually derived from geographic information system processing software in hectares.				
INTERPRETER	USERID	Y	VARCHAR2	30
The user id of the individual who provided the estimates for the data associated with each polygon.				
INTERPRETATION DATE	DATE TIME	Y	DATE	
The date on which the polygon estimates were photo interpreted.				
PROJECT NAME	PROJECT NAME	Y	VARCHAR2	100
The business assigned name of the project. The name typically reflects a Timber Supply Area, an initiating Agency, or a land area.				
EXPIRY DATE	DATE TIME	Y	DATE	
The date/time from which the spatial object is retired.				
CREATED DATE	DATE TIME	Y	DATE	
The date/time from the spatial object was created. This may be different from the data/time the entry containing the spatial object was created.				
SLIVER IND	INDICATOR	N	VARCHAR2	1
If a polygon is a sliver then the indication will be 'Y'. This flag will only be set if there is no computational means to either merge the sliver with an adjacent polygon, or integrate it by some other means. The slivers will have to be manually identified and manually dealt with.				
<i>This attribute is defaulted to 'N' by the application on load, as its value is not known until integration.</i>				
FREE TO GROW IND	INDICATOR	N	VARCHAR2	1
Indicates that the polygon has achieved Free To Grow status, which marks the milestone where a stand is capable of growing and should be allowed to do so, without intervention.				

Entity Name: FOREST COVER OBJECT STAGING (cont'd)			Short Name:	FCOS
DISTURBANCE START YEAR	DATE TIME	Y	DATE	
Starting year of the disturbance event.				
DISTURBANCE END YEAR	DATE TIME	Y	DATE	
Ending year of the disturbance event.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

- MAY BE data captured by means of one and only one DATA CAPTURE METHOD CODE
 - MAY BE disturbed by one and only one DISTURBANCE TYPE CODE
 - MAY BE inventory standard described by one and only one INVENTORY STANDARD CODE
 - MAY BE staged by one and only one VEGETATION COVER POLYGON STAGING
 - MAY BE disturbed by one and only one VRIMS DISTURBANCE CODE
 - MAY BE produces errors for one or more VRIMS ERROR LOG
 - MUST BE processed as part of one and only one VRIMS PACKAGE TRANSACTION
 - MAY BE processed by one and only one VRIMS POLYGON TRANSACTION
- * = Relationships in primary unique identifier.

Unique Identifiers:

FCOS PKPrimaryY

FOREST COVER OBJECT STAGING ID

Entity Name: FOREST COVER RANK CODE			Short Name:	FCRC
Plural:	FOREST COVER RANK CODE			
Init. Volume:	5	Avg. Volume:	5	Max. Volume: 10
			Annual Growth Rate:	10%

Description:

A list of codes that describes how the numeric designation of the relative importance of the layer component in the stand, as determined by the business area. For Vegetation Cover-originated data, this value is assigned via a business rule. The rule is based on the supplied order of the layer records, as recorded by the interpreter. For FIP originated data, this value is known as the RANK CD, and is explicitly supplied by the interpreter, based on Regional guidelines at the time of interpretation. Rank is used to determine the layer of tree volumes that will be calculated by VDYP. VDYP is the current yield prediction model used in production.

- Eg. 0 - Null
- 1 - Rank 1
- 2 - Rank 2
- 3 - Rank 3
- 4 - Rank 4

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* FOREST COVER RANK CODE	CODETABLE CODE	N	VARCHAR2	10
A numeric designation of the relative importance of the layer component in the stand, as determined by the business area. For Vegetation Cover-originated data, this value is assigned via a business rule. The rule is based on the supplied order of the layer records, as recorded by the interpreter. For FIP originated data, this value is known as the RANK CD, and is explicitly supplied by the interpreter, based on Regional guidelines at the time of interpretation. Rank is used to determine the layer of tree volumes that will be calculated by VDYP. VDYP is the current yield prediction model used in production.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

- MAY BE rank for one or more TREE COVER LAYER ADJUSTED
 - MAY BE forest cover rank for one or more TREE COVER LAYER ESTIMATED
 - MAY BE forest cover rank for one or more TREE COVER LAYER PROJECTED
 - MAY BE forest cover rank for one or more TREE COVER LAYER STAGING
- * = Relationships in primary unique identifier.

Unique Identifiers:

FCRC PK	Primary	Y
FOREST COVER RANK CODE		

Entity Name: HERB COVER TYPE CODE			Short Name:	HCT
Plural:	HERB COVER TYPE CODE			
Init. Volume:	5	Avg. Volume:	5	Max. Volume: 10
			Annual Growth Rate:	10%

Description:

A list of codes that describes a set of attributes for the portion of herb cover that is not obscured by the vertical projection of the crowns of either trees or shrubs. Herbs are defined as non-woody (vascular) plants, including graminoids (sedges, rushes, grasses), forbs (ferns, club mosses, and horsetails) and some low, woody species and intermediate life forms.

- Eg. HE - Herb - a herb polygon with no distinction between forbs and graminoids
HF - Herb-Forbs - a herb polygon with forbs greater than 50% of the herb cover.
HG - Herb-Graminoids - a herb polygon with graminoids greater than 50% of the herb cover

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* HERB COVER TYPE CODE	CODETABLE CODE	N	VARCHAR2	10
This set of attributes describes the portion of herb cover that is not obscured by the vertical projection of the crowns of either trees or shrubs. Herbs are defined as non-woody (vascular) plants, including graminoids (sedges, rushes, grasses), forbs (ferns, club mosses, and horsetails) and some low, woody species and intermediate life forms.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

- MAY BE herb type for one or more VEGETATION COVER POLYGON ADJ
MAY BE herb type for one or more VEGETATION COVER POLYGON EST
MAY BE herb cover type for one or more VEGETATION COVER POLYGON PRJ
MAY BE herb type for one or more VEGETATION COVER POLYGON STG
* = Relationships in primary unique identifier.

Unique Identifiers:

HCT PK	Primary	Y
HERB COVER TYPE CODE		

Entity Name: INVENTORY STANDARD CODE			<i>Short Name:</i>	ISC
<i>Plural:</i>	INVENTORY STANDARD CODE			
<i>Init. Volume:</i>	5	<i>Avg. Volume:</i>	5	<i>Max. Volume:</i> 10
			<i>Annual Growth Rate:</i>	10%

Description:

A list of valid codes that describes under which inventory standard the data was collected. The standards define the fields that are collected in each sampling, varying the quantity of data present between sample types.

Eg. F - FIP Data collected to FIP Standards
I - Veg Data Incomplete - Full set of VRI Attributes not collected
V - Veg Data collected to Veg Standards

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* INVENTORY STANDARD CODE	CODETABLE CODE	N	VARCHAR2	10
Code indicating under which inventory standard the data was collected. Values are: "V:" for Vegetation Resources Inventory (VRI), "F" for Forest Inventory Planning (FIP) and "I" for Incomplete (when a full set of VRI attributes is not collected).				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MAY BE inventory code for one or more FOREST COVER OBJECT
MAY BE inventory code for one or more FOREST COVER OBJECT STAGING
* = Relationships in primary unique identifier.

Unique Identifiers:

ISC PK	Primary	Y
INVENTORY STANDARD CODE		

Entity Name: LAND COVER CLASS CODE		<i>Short Name:</i>	LCCC
<i>Plural:</i>	LAND COVER CLASS CODE		
<i>Init. Volume:</i>	50	<i>Avg. Volume:</i>	60
		<i>Max. Volume:</i>	70
		<i>Annual Growth Rate:</i>	10%

Description:

A list of codes that describe the land cover Classification Land cover types within the polygon that contribute to the overall polygon description, but are too small to be delineated using current guidelines, may be described by land cover components. The sub-division of a polygon by a quantified Land Cover Component, allowing nonspatial resolution for modeling of wildlife habitat capability.

- Eg. AP - Airport
- BE - Beach
- BI - Blockfield
- BL - Bryoid Lichens
- BM - Bryoid Moss
- BR - Bedrock
- BU - Burned Area
- BY - Bryoid
- CB - Cutbank
- EL - Exposed Land
- ES - Exposed Soil
- GL - Glacier
- GP - Gravel Pit
- HE - Herb
- HF - Herb Forbs
- HG - Herb Graminoids
- LA - Lake
- LB - Lava Bed
- LL - Landing
- LS - Pond or Lake Sediments
- MI - Open Pit Mine
- MN - Moraine
- MU - Mudflat Sediment
- MZ - Rubbly Mine Spoils
- Null - No Value
- OC - Ocean
- OT - Other
- PN - Snow Cover
- RE - Reservoir
- RI - River/Stream
- RM - Reservoir Margin
- RN - Railway Surface
- RO - Rock/Rubble
- RS - River Sediments
- RZ - Road Surface
- SI - Snow/Ice
- SL - Shrub Low
- ST - Shrub Tall
- TA - Talus
- TB - Treed Broadleaf
- TC - Treed Coniferous
- TM - Treed Mixed
- TZ - Tailings
- UR - Urban

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* LAND COVER CLASS CODE	CODETABLE CODE	N	VARCHAR2	10
The codes for the land cover Classification Land cover types within the polygon that contribute to the overall polygon description, but are too small to be delineated using current guidelines, may be described by land cover components. The sub-division of a				

Entity Name:	LAND COVER CLASS CODE (cont'd)	Short Name:	LCCC
--------------	--------------------------------	-------------	------

 polygon by a quantified Land Cover Component, allowing nonspatial resolution for modeling of wildlife habitat capability.

DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
-------------	--------------------------	---	----------	-----

 Provides the description for the code. This is the human readable form of the code.

EFFECTIVE DATE	DATE TIME	N	DATE
Effective date/time			

EXPIRY DATE	DATE TIME	N	DATE
Expiry date/time			

UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE
Update date/time			

 * = Attributes in primary unique identifier.

Relationships:

Each Occurrence Of This Entity:

- MAY BE cover class for one or more LAND COVER COMPONENT ADJ
- MAY BE land cover class for one or more LAND COVER COMPONENT EST
- MAY BE land cover class for one or more LAND COVER COMPONENT PRJ
- MAY BE cover class for one or more LAND COVER COMPONENT STG

 * = Relationships in primary unique identifier.

Unique Identifiers:

LCCC PK	Primary	Y
LAND COVER CLASS CODE		

Entity Name: LAND COVER COMPONENT ADJUSTED				Short Name:	LCCA
Plural:	LAND COVER COMPONENT ADJ				
Init. Volume:	1700000	Avg. Volume:	1785000	Max. Volume:	1875000
				Annual Growth Rate:	5%

Description:

The table that maintains the number of a specific instances of a land cover component as attached to a polygon record. This can be from 1 to 4.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* LAND COVER COMPONENT ADJ ID	NUMERIC IDENTIFIER	N	NUMBER	10
Primary unique numerical identifier for an adjusted polygon's land cover component.				
LAND COVER ORDER	NUMERIC ORDER	Y	NUMBER	3
The order of a specific instance of a land cover component as attached to a polygon record. This can be from 1 to 4.				
COVERAGE PCT	PERCENTAGE 3,0	Y	NUMBER	3,0
The percentage coverage of a polygon occupied by each Land Cover Component. Generally, sizes under 10% will not be used.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

- MAY BE describes land cover class one and only one LAND COVER CLASS CODE
- MAY BE layer at level one and only one LAND COVER LEVEL CODE
- MAY BE describes soil moisture regime one and only one SOIL MOISTURE REGIME CODE
- MUST BE describe land cover types for one and only one VEGETATION COVER POLYGON ADJUSTED
- * = Relationships in primary unique identifier.

Unique Identifiers:

LCCA UK	Primary	N
MUST BE describe land cover types for one and only one VEGETATION COVER POLYGON ADJUSTED		
MAY BE layer at level one and only one LAND COVER LEVEL CODE		
LCCA PK	Primary	Y
LAND COVER COMPONENT ADJ ID		

Entity Name: LAND COVER COMPONENT ESTIMATED				Short Name:	LCCE
Plural:	LAND COVER COMPONENT EST				
Init. Volume:	1700000	Avg. Volume:	1785000	Max. Volume:	1875000
				Annual Growth Rate:	5%

Description:

The table that maintains the number of a specific instances of a land cover component as attached to a polygon record. This can be from 1 to 4.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* LAND COVER COMPONENT EST ID	NUMERIC IDENTIFIER	N	NUMBER	10
Primary unique numerical identifier for an estimated polygon's land cover component.				
LAND COVER ORDER	NUMERIC ORDER	Y	NUMBER	3
The order of a specific instance of a land cover component as attached to a polygon record. This can be from 1 to 4.				
COVERAGE PCT	PERCENTAGE 3,0	Y	NUMBER	3,0
The percentage coverage of a polygon occupied by each Land Cover Component. Generally, sizes under 10% will not be used.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MAY BE of land cover class one and only one LAND COVER CLASS CODE

MAY BE layer at level one and only one LAND COVER LEVEL CODE

MAY BE has soil moisture regime one and only one SOIL MOISTURE REGIME CODE

MUST BE land cover types for one and only one VEGETATION COVER POLYGON ESTIMATED

* = Relationships in primary unique identifier.

Unique Identifiers:

LCCE UK	Primary	N
MUST BE land cover types for one and only one VEGETATION COVER POLYGON ESTIMATED		
MAY BE layer at level one and only one LAND COVER LEVEL CODE		
LCCE PK	Primary	Y
LAND COVER COMPONENT EST ID		

Entity Name: LAND COVER COMPONENT PROJECTED				Short Name:	LCCP
Plural:	LAND COVER COMPONENT PRJ				
Init. Volume:	1700000	Avg. Volume:	1785000	Max. Volume:	1875000
				Annual Growth Rate:	5%

Description:

This maintains the number of a specific instances of a projected land cover component as attached to a polygon record. This can be from 1 to 4.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* LAND COVER COMPONENT PRJ ID	NUMERIC IDENTIFIER	N	NUMBER	10
Primary unique numerical identifier for a projected polygon's land cover component.				
LAND COVER ORDER	NUMERIC ORDER	Y	NUMBER	3
The order of a specific instance of a land cover component as attached to a polygon record. This can be from 1 to 4.				
COVERAGE PCT	PERCENTAGE 3,0	Y	NUMBER	3,0
The percentage coverage of a polygon occupied by each Land Cover Component. Generally, sizes under 10% will not be used.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MAY BE of land cover class one and only one LAND COVER CLASS CODE

MAY BE layer at level one and only one LAND COVER LEVEL CODE

MAY BE moisture regime described by one and only one SOIL MOISTURE REGIME CODE

MUST BE describes land cover types for one and only one VEGETATION COVER POLYGON PROJECTED

* = Relationships in primary unique identifier.

Unique Identifiers:

LCCP UK	Primary	N
MUST BE describes land cover types for one and only one VEGETATION COVER POLYGON PROJECTED		
MAY BE layer at level one and only one LAND COVER LEVEL CODE		
LCCP PK	Primary	Y
LAND COVER COMPONENT PRJ ID		

Entity Name: LAND COVER COMPONENT STAGING				Short Name:	LCCS
Plural:	LAND COVER COMPONENT STG				
Init. Volume:	22500	Avg. Volume:	22500	Max. Volume:	22500
				Annual Growth Rate:	0%

Description:

Thist maintains the number of a specific instances of a land cover component beign staged, as attached to a polygon record.
This can be from 1 to 4.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* LAND COVER COMPONENT STG ID	NUMERIC IDENTIFIER	N	NUMBER	10
Primary unique numerical identifier for a staging polygon's land cover component.				
LAND COVER ORDER	NUMERIC ORDER	Y	NUMBER	3
The order of a specific instance of a land cover component as attached to a polygon record. This can be from 1 to 4.				
COVERAGE PCT	PERCENTAGE 3,0	Y	NUMBER	3,0
The percentage coverage of a polygon occupied by each Land Cover Component. Generally, sizes under 10% will not be used.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MAY BE land cover class described by one and only one LAND COVER CLASS CODE

MAY BE layer at level one and only one LAND COVER LEVEL CODE

MAY BE soil moisture regime described by one and only one SOIL MOISTURE REGIME CODE

MUST BE describes land cover types for one and only one VEGETATION COVER POLYGON STAGING

* = Relationships in primary unique identifier.

Unique Identifiers:

LCCS UK	Primary	N
MUST BE describes land cover types for one and only one VEGETATION COVER POLYGON STAGING		
MAY BE layer at level one and only one LAND COVER LEVEL CODE		
LCCS PK	Primary	Y
LAND COVER COMPONENT STG ID		

Entity Name: LAND COVER LEVEL CODE			Short Name:	LCLC
Plural:	LAND COVER LEVEL CODE			
Init. Volume:	10	Avg. Volume:	10	Max. Volume: 15
			Annual Growth Rate:	10%

Description:

- A list of codes that are a representation of a level of land cover.
- Eg. 1 - First specific instance of a land cover component as attached to a polygon record
2 - Second specific instance of a land cover component as attached to a polygon record
3 - Third specific instance of a land cover component as attached to a polygon record
4 - All other specific instances of a land cover component as attached to a polygon record

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* LAND COVER LEVEL CODE	CODETABLE CODE	N	VARCHAR2	10
Code representation of the land cover level.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

- MAY BE layer level for one or more LAND COVER COMPONENT ADJ
MAY BE layer level for one or more LAND COVER COMPONENT EST
MAY BE layer level for one or more LAND COVER COMPONENT PRJ
MAY BE layer level for one or more LAND COVER COMPONENT STG
* = Relationships in primary unique identifier.

Unique Identifiers:

LCLC PK	Primary	Y
LAND COVER LEVEL CODE		

Entity Name: LAYER LEVEL CODE			Short Name:	LLC
Plural:	LAYER LEVEL CODE			
Init. Volume:	10	Avg. Volume:	10	Max. Volume: 15
			Annual Growth Rate:	10%

Description:

A list of codes that are a representation of a level of vegetative or non-vegetative material.

- Eg. 1 - Tallest Layer
- 2 - Second Tallest Layer
- 3 - Third Tallest Layer
- 4 - Fourth Tallest Layer
- 5 - Fifth Tallest Layer
- 6 - Sixth Tallest Layer
- 7 - Seventh Tallest Layer
- 8 - Eighth Tallest Layer
- 9 - Ninth Tallest Layer
- S - Silviculture Layer
- V - Veteran Layer

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* LAYER LEVEL CODE	CODETABLE CODE	N	VARCHAR2	10
Code representation of the layer level.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

- MAY BE layer level for one or more NON VEGETATIVE COVER ADJ
 - MAY BE layer level for one or more NON VEGETATIVE COVER EST
 - MAY BE layer level for one or more NON VEGETATIVE COVER PRJ
 - MAY BE layer level for one or more NON VEGETATIVE COVER STG
 - MAY BE layer for one or more TREE COVER LAYER ADJUSTED
 - MAY BE layer for one or more TREE COVER LAYER ESTIMATED
 - MAY BE layer level for one or more TREE COVER LAYER PROJECTED
 - MAY BE layer level for one or more TREE COVER LAYER STAGING
- * = Relationships in primary unique identifier.

Unique Identifiers:

LLC PK	Primary	Y
LAYER LEVEL CODE		

Entity Name: LAYER SUMMARIZATION CODE			<i>Short Name:</i>	LSC
<i>Plural:</i>	LAYER SUMMARIZATION CODE			
<i>Init. Volume:</i>	5	<i>Avg. Volume:</i>	5	<i>Max. Volume:</i> 10
			<i>Annual Growth Rate:</i>	10%

Description:

A list of codes that describes the number of layers to be summarized for volume, as required for VDYP calculation.

Eg. 1 - Single Layer
2 - Two Layer

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* LAYER SUMMARIZATION CODE	CODETABLE CODE	N	VARCHAR2	10
Indicates combination of layers and tree class to be summarized for volume.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MAY BE summarization for one or more VEGETATION COVER POLYGON ADJ
MAY BE layer summarization for one or more VEGETATION COVER POLYGON STG
* = Relationships in primary unique identifier.

Unique Identifiers:

LSC PK	Primary	Y
LAYER SUMMARIZATION CODE		

Entity Name: MODIFYING PROCESS CODE			<i>Short Name:</i>	MPC
<i>Plural:</i>	MODIFYING PROCESS CODE			
<i>Init. Volume:</i>	10	<i>Avg. Volume:</i>	10	<i>Max. Volume:</i> 15
			<i>Annual Growth Rate:</i>	10%

Description:

A list of codes that describes a natural mechanism of weathering, erosion and soil material deposition that result in the modification of surficial materials and landforms. Used for terrain classification, site classification, soil condition and identification of potential hazards such as avalanches, slope instability and flooding.

Eg. A - Avalanche
B - River Channeling
F - Mass Movements
N - None
U - Flooding
V - Gully Erosion

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* MODIFYING PROCESS CODE	CODETABLE CODE	N	VARCHAR2	10
A natural mechanism of weathering, erosion and soil material deposition that result in the modification of surficial materials and landforms. Used for terrain classification, site classification, soil condition and identification of potential hazards such as avalanches, slope instability and flooding.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MAY BE modifying process for one or more VEGETATION COVER POLYGON ADJ
MAY BE modifying process for one or more VEGETATION COVER POLYGON EST
MAY BE modifying process for one or more VEGETATION COVER POLYGON PRJ
MAY BE process for one or more VEGETATION COVER POLYGON STG
* = Relationships in primary unique identifier.

Unique Identifiers:

MPC PK	Primary	Y
MODIFYING PROCESS CODE		

NFDC PK Primary Y

NON FOREST DESCRIPTOR CODE

Entity Name: NON PRODUCTIVE CODE				Short Name:	NPC
Plural:	NON PRODUCTIVE CODE				
Init. Volume:	25	Avg. Volume:	30	Max. Volume:	30
				Annual Growth Rate:	10%

Description:

A list of codes that describe the land that is incapable of supporting commercial forests. This code list parallels the entries in Non-Productive Descriptor Code, but is specialized for use by VDYP translation processes only, which utilizes a different set of codes.

- Eg. 02 - Alpine
- 10 - Alpine Forest (with species etc.)
- 42 - Clearing
- 09 - Clay Bank
- 18 - Gravel Bar
- 06 - Gravel Pit
- 01 - Icefield
- 15 - Lake
- 62 - Meadow
- 26 - Mud Flat
- 64 - Non-Applicable (salt water)
- 11 - Non-Productive Brush
- 13 - Non-Productive Burn
- 12 - Non-Productive Forest (with species etc.)
- 63 - Open Range
- 60 - Hayfield
- 03 - Rock
- 25 - River
- 35 - Swamp
- 07 - Sand
- 16 - Tidal Flat
- 54 - Urban/Roads

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* NON PRODUCTIVE CODE	CODETABLE CODE	N	VARCHAR2	10
Code representation of the land type that is not able to support commercial logging.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

- MAY BE non-productive VDYP descriptor for one or more VEGETATION COVER POLYGON ADJ
- MAY BE non-productive VDYP descriptor for one or more VEGETATION COVER POLYGON EST
- MAY BE non-productive VDYP descriptor for one or more VEGETATION COVER POLYGON PRJ
- MAY BE VDYP descriptor for one or more VEGETATION COVER POLYGON STG
- * = Relationships in primary unique identifier.

Unique Identifiers:

NPC PK

Primary Y

Entity Name:	NON PRODUCTIVE CODE (cont'd)	Short Name:	NPC
---------------------	------------------------------	--------------------	-----

NON PRODUCTIVE CODE

Entity Name:	NON PRODUCTIVE DESCRIPTOR CODE			Short Name:	NPDC
Plural:	NON PRODUCTIVE DESCRIPTOR CODE				
Init. Volume:	25	Avg. Volume:	30	Max. Volume:	30
				Annual Growth Rate:	10%

Description:

A list of codes that describe the land that is incapable of supporting commercial forests. This relates directly to the FIP attribute, NON PRODUCTIVE DESCRIPTOR and is also utilized for the determination of the BC Land Cover Classification. This is a FIP classification based attribute only, and is retained for the purposes of business transition from FIP to Vegetation Inventory. The current growth projection model, 'VDYP', requires this attribute as a key input variable, and will continue to be utilized for Vegetative Cover until phased out. There is no expectation that this attribute would be updated or created under Vegetation Inventory classification practice.

Eg. A - Alpine
 AF - Alpine Forest(with species etc.)
 C - Clearing
 CL - Clay Bank
 G - Gravel Bar
 GR - Gravel Pit
 ICE - Icefield
 L - Lake
 M - Meadow
 MUD - Mud Flat
 NA - Non-Applicable (salt water)
 NP - Non-Productive
 NPBR - Non-Productive Brush
 NPBU - Non-Productive Burn
 NPF - Non-Productive Forest(with species etc.)
 OR - Open Range
 P - Hayfield
 R - Rock
 RIV - River
 S - Swamp
 SAND - Sand
 TIDE - Tidal Flat
 U - Roads

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* NON PRODUCTIVE DESCRIPTOR CODE	CODETABLE CODE	N	VARCHAR2	10
Land that is incapable of supporting commercial forests. This relates directly to the FIP attribute, NON PRODUCTIVE DESCRIPTOR and is also utilized for the determination of the BC Land Cover Classification. This is a FIP classification based attribute only, and is retained for the purposes of business transition from FIP to Vegetation Inventory. The current growth projection model, 'VDYP', requires this attribute as a key input variable, and will continue to be utilized for Vegetative Cover until phased out. There is no expectation that this attribute would be updated or created under Vegetation Inventory classification practice.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				

* = Attributes in primary unique identifier.

Relationships:

Entity Name:	NON PRODUCTIVE DESCRIPTOR CODE (cont'd)	Short Name:	NPDC
--------------	---	-------------	------

Each Occurrence Of This Entity:

MAY BE non-productive descriptor for one or more VEGETATION COVER POLYGON ADJ
MAY BE non-productive descriptor for one or more VEGETATION COVER POLYGON EST
MAY BE non productive descriptor for one or more VEGETATION COVER POLYGON PRJ
MAY BE descriptor for one or more VEGETATION COVER POLYGON STG

* = Relationships in primary unique identifier.

Unique Identifiers:

NPDC PK	Primary	Y
---------	---------	---

NON PRODUCTIVE DESCRIPTOR CODE

Entity Name: NON VEGETATIVE COVER ADJUSTED**Short Name:**

NVCA

Plural: NON VEGETATIVE COVER ADJ**Init. Volume:** 600000 **Avg. Volume:** 630000**Max. Volume:** 660000**Annual Growth Rate:** 5%**Description:**

The tables that maintains the number of a specific instance of a non-vegetative record as attached to a polygon record. The number of a specific instance of non-vegetative cover, associated with a particular polygon.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* NON VEGETATIVE COVER ADJ ID	NUMERIC IDENTIFIER	N	NUMBER	10
Primary unique numerical identifier for an adjusted polygon's non-vegetative cover.				
NON VEG ORDER	NUMERIC ORDER	Y	NUMBER	3
The order of a specific instance of a non-vegetative record as attached to a polygon record.				
NON VEG COVER PCT	PERCENTAGE 3,0	Y	NUMBER	3,0
Area of a polygon that the non-vegetated portion covers, expressed as a percentage.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				

* = Attributes in primary unique identifier.

Relationships:Each Occurrence Of This Entity:

MAY BE has non veg cover pattern one and only one COVER PATTERN CODE

MUST BE layer at level one and only one LAYER LEVEL CODE

MAY BE describes cover type one and only one NON VEGETATIVE COVER TYPE CODE

MUST BE describes non vegetative content for one and only one VEGETATION COVER POLYGON ADJUSTED

* = Relationships in primary unique identifier.

Unique Identifiers:NVCA UK *Primary* N*MUST BE describes non vegetative content for one and only one VEGETATION COVER POLYGON ADJUSTED**MUST BE layer at level one and only one LAYER LEVEL CODE*NVCA PK *Primary* Y

NON VEGETATIVE COVER ADJ ID

Entity Name: NON VEGETATIVE COVER ESTIMATED				Short Name:	NVCE
Plural:	NON VEGETATIVE COVER EST				
Init. Volume:	600000	Avg. Volume:	630000	Max. Volume:	660000
				Annual Growth Rate:	5%

Description:

The number of a specific instance of a non-vegetative cover (record) as attached to a particular polygon.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* NON VEGETATIVE COVER EST ID	NUMERIC IDENTIFIER	N	NUMBER	10
Primary unique numerical identifier for an estimated polygon's non-vegetative cover.				
NON VEG ORDER	NUMERIC ORDER	Y	NUMBER	3
The order of a specific instance of a non-vegetative record as attached to a polygon record.				
NON VEG COVER PCT	PERCENTAGE 3,0	Y	NUMBER	3,0
Area of a polygon that the non-vegetated portion covers, expressed as a percentage.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MAY BE has non veg cover pattern one and only one COVER PATTERN CODE

MUST BE layer at level one and only one LAYER LEVEL CODE

MAY BE cover type described by one and only one NON VEGETATIVE COVER TYPE CODE

MUST BE describes non vegetative content for one and only one VEGETATION COVER POLYGON ESTIMATED

* = Relationships in primary unique identifier.

Unique Identifiers:

NVCE UK	Primary	N
MUST BE describes non vegetative content for one and only one VEGETATION COVER POLYGON ESTIMATED		
MUST BE layer at level one and only one LAYER LEVEL CODE		
NVCE PK	Primary	Y
NON VEGETATIVE COVER EST ID		

Entity Name: NON VEGETATIVE COVER PROJECTED				Short Name:	NVCP
Plural:	NON VEGETATIVE COVER PRJ				
Init. Volume:	600000	Avg. Volume:	630000	Max. Volume:	660000
				Annual Growth Rate:	5%

Description:

The number of a specific instance of a projected non-vegetative cover (record) as attached to a polygon polygon.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* NON VEG COVER PRJ ID	NUMERIC IDENTIFIER	N	NUMBER	10
Primary unique numerical identifier for a projected polygon's non-vegetative cover.				
NON VEG ORDER	NUMERIC ORDER	Y	NUMBER	3
The order of a specific instance of a non-vegetative record as attached to a polygon record.				
NON VEG COVER PCT	PERCENTAGE 3,0	Y	NUMBER	3,0
Area of a polygon that the non-vegetated portion covers, expressed as a percentage.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

- MAY BE has non veg cover pattern one and only one COVER PATTERN CODE
- MUST BE layer at level one and only one LAYER LEVEL CODE
- MAY BE cover type described by one and only one NON VEGETATIVE COVER TYPE CODE
- MUST BE non vegetative content for one and only one VEGETATION COVER POLYGON PROJECTED
- * = Relationships in primary unique identifier.

Unique Identifiers:

NVCP UK	Primary	N
MUST BE layer at level one and only one LAYER LEVEL CODE		
MUST BE non vegetative content for one and only one VEGETATION COVER POLYGON PROJECTED		
NVCP PK	Primary	Y
NON VEG COVER PRJ ID		

Entity Name: NON VEGETATIVE COVER STAGING			Short Name:	NVCS
Plural:	NON VEGETATIVE COVER STG			
Init. Volume:	4800	Avg. Volume:	4800	Max. Volume: 4800
			Annual Growth Rate:	0%

Description:

The tables that maintains the number of a specific instance of a non-vegetative cover (record) that is being staged, as attached to a polygon.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* NON VEGETATIVE COVER STG ID	NUMERIC IDENTIFIER	N	NUMBER	10
Primary unique numerical identifier for a staging polygon's non-vegetative cover.				
NON VEG ORDER	NUMERIC ORDER	Y	NUMBER	3
The order of a specific instance of a non-vegetative record as attached to a polygon record.				
NON VEG COVER PCT	PERCENTAGE 3,0	Y	NUMBER	3,0
Area of a polygon that the non-vegetated portion covers, expressed as a percentage.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

- MAY BE has non veg cover pattern one and only one COVER PATTERN CODE
- MAY BE layer at level one and only one LAYER LEVEL CODE
- MAY BE of non-vegatative cover type one and only one NON VEGETATIVE COVER TYPE CODE
- MUST BE describes non-vegetative content for one and only one VEGETATION COVER POLYGON STAGING

* = Relationships in primary unique identifier.

Unique Identifiers:

NVCS UK	Primary	N
MUST BE describes non-vegetative content for one and only one VEGETATION COVER POLYGON STAGING		
MAY BE layer at level one and only one LAYER LEVEL CODE		
NVCS PK	Primary	Y
NON VEGETATIVE COVER STG ID		

Entity Name: NON VEGETATIVE COVER TYPE CODE		Short Name:	NVCTC
Plural:	NON VEG COVER TYPE CODE		
Init. Volume:	40	Avg. Volume:	50
		Max. Volume:	60
		Annual Growth Rate:	10%

Description:

A list of codes that describes the designated type for all of the observable non-vegetated land cover within a polygon.

- Eg. AP - Airport
- BE - Beach
- BI - Blockfield
- BR - Bedrock
- BU - Burned Area
- CB - Cutbank
- ES - Exposed Soil
- GL - Glacier
- GP - Gravel Pit
- LA - Lake
- LB - Lava Bed
- LL - Landing
- LS - Pond or Lake Sediments
- MI - Open Pit Mine
- MN - Moraine
- MU - Mudflat Sediment
- MZ - Rubbly Mine Spoils
- Null - No Value
- OC - Ocean
- OT - Other
- PN - Snow Cover
- RE - Reservoir
- RI - River/Stream
- RM - Reservoir Margin
- RN - Railway
- RS - River Sediments
- RZ - Road Surface
- TA - Talus
- TZ - Tailings
- UR - Urban

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* NON VEG COVER TYPE CODE	CODETABLE CODE	N	VARCHAR2	10
Designated type for all of the observable non-vegetated land cover within a polygon.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MAY BE cover type for one or more NON VEGETATIVE COVER ADJ

MAY BE cover type for one or more NON VEGETATIVE COVER EST

MAY BE cover type for one or more NON VEGETATIVE COVER PRJ

Entity Name:	NON VEGETATIVE COVER TYPE CODE (cont'd)	<i>Short Name:</i>	NVCTC
---------------------	---	--------------------	-------

MAY BE non-vegatative cover type for one or more NON VEGETATIVE COVER STG

* = Relationships in primary unique identifier.

Unique Identifiers:

NVCTC PK	Primary	Y
----------	---------	---

NON VEG COVER TYPE CODE

Entity Name: PROJECTED YIELD

Short Name:

PY

Plural: PROJECTED YIELD

Init. Volume: 91200000

Avg. Volume: 95760000

Max. Volume: 100550000

Annual Growth Rate: 5%

Description:

This tracks the year to which time dependent stand information such as age and height is projected.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* PROJECTED YIELD ID	NUMERIC IDENTIFIER	N	NUMBER	10
Primary unique numeric identifier for a Projected Yield.				
PROJECTED YEAR	NUMERIC YEAR	N	NUMBER	4,0
The projection year to which time dependent stand information, such as age and height, is projected.				
DBH LIMIT	DBH LIMIT	Y	NUMBER	3,1
Indicates the minimum diameter breast height (DBH) for measuring trees (i.e. stems) in the field sample.				
BASAL AREA	BASAL AREA	N	NUMBER	10,6
Basal area is the total cross sectional area (at breast height), as projected for all living trees of the specified species at a particular age in the layer. Basal area is expressed as square metres per hectare.				
DIAMETER	NUMERIC PRECISION 8,3	N	NUMBER	8,3
Diameter of the layer at the age specified, for the species specified, in metres.				
LOREY HEIGHT	NUMERIC PRECISION 8,3	N	NUMBER	8,3
Lorey height of the layer at the age specified, for the species specified, in metres.				
TREES PER HECTARE	NUMERIC PRECISION 8,3	N	NUMBER	8,3
The number of trees per hectare of the layer at the age specified, for the species specified.				
VOLUME CLOSE UTILIZATION	NUMERIC PRECISION 8,3	N	NUMBER	8,3
Close Utilization Volume at the age specified for the given layer, species. Volume is measured in cubic metres per hectare.				
VOLUME LESS DECAY	NUMERIC PRECISION 8,3	N	NUMBER	8,3
Volume less Decay at the age specified for the given layer, species. Volume is measured in cubic metres per hectare.				
VOLUME LESS DECAY WASTE	NUMERIC PRECISION 8,3	N	NUMBER	8,3
Volume less Decay and Waste at the age specified for the given layer, species. Volume is measured in cubic metres per hectare.				
VOLUME LESS DECAY WASTE BREAK	NUMERIC PRECISION 8,3	N	NUMBER	8,3
Volume less Decay, Waste and Breakage at the age specified for the given layer, species. Volume is measured in cubic metres per hectare.				
VOLUME WHOLE STEM	NUMERIC PRECISION 8,3	N	NUMBER	8,3
Whole Stem Volume at the age specified for the given layer, species. Volume is measured in cubic metres per hectare.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				

* = Attributes in primary unique identifier.

Relationships:

Entity Name:	PROJECTED YIELD (cont'd)	<i>Short Name:</i>	PY
---------------------	--------------------------	--------------------	----

Each Occurrence Of This Entity:

MUST BE describes projected yield for one and only one TREE SPECIES PROJECTED
* = Relationships in primary unique identifier.

Unique Identifiers:

PY PK	Primary	Y
PROJECTED YIELD ID		

PLC PK	Primary	Y
PROJECTION LAYER CODE		

Entity Name: SAMPLES USED ADJUSTED				Short Name:	SUA
Plural:	SAMPLES USED ADJUSTED				
Init. Volume:	3800000	Avg. Volume:	4000000	Max. Volume:	4200000
				Annual Growth Rate:	5%

Description:

Identifies samples used in adjustment project, for the given adjusted polygon and strata. Entries into this entity will not be purged on entry of a new Project.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* SAMPLES USED ADJUSTED ID	NUMERIC IDENTIFIER	N	NUMBER	10
Primary unique numeric identifier for a VRI Sample.				
NAME	SAMPLE NAME	N	VARCHAR2	13
The VRI Sample identifier for a polygon. The identifier is a multi-component key, made up of the project id, sample id and sample type.				
WEIGHT	SAMPLE WEIGHT	Y	NUMBER	7,1
One weight value per VRISample, expressed as a number (no. of hectares in strata/no. of samples in strata).				
USED IN ADJUSTMENT IND	INDICATOR	N	VARCHAR2	1
Indicates if the sample was used in the adjustment.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MUST BE part of strata one and only one STRATA ADJUSTED

MUST BE adjusted by one and only one VEGETATION COVER POLYGON ADJUSTED

* = Relationships in primary unique identifier.

Unique Identifiers:

SUA PK	Primary	Y
SAMPLES USED ADJUSTED ID		

Entity Name: SAMPLES USED STAGING				Short Name:	SUS
Plural:	SAMPLES USED STAGING				
Init. Volume:	60000	Avg. Volume:	63000	Max. Volume:	66000
				Annual Growth Rate:	0%

Description:

Identifies samples used in adjustment project, for the given staging polygon and strata. Entries into this entity will not be purged on entry of a new Project.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* SAMPLES USED STAGING ID	NUMERIC IDENTIFIER	N	NUMBER	10
Primary unique numeric identifier for a VRI Sample.				
NAME	SAMPLE NAME	N	VARCHAR2	13
The VRI Sample identifier for a polygon. The identifier is a multi-component key, made up of the project id, sample id and sample type.				
WEIGHT	SAMPLE WEIGHT	Y	NUMBER	7,1
One weight value per VRISample, expressed as a number (no. of hectares in strata/no. of samples in strata).				
USED IN ADJUSTMENT IND	INDICATOR	N	VARCHAR2	1
Indicates if the sample was used in the adjustment.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MUST BE part of strata one and only one STRATA STAGING
MUST BE adjusts one and only one VEGETATION COVER POLYGON STAGING
* = Relationships in primary unique identifier.

Unique Identifiers:

SUS PK	Primary	Y
SAMPLES USED STAGING ID		

Entity Name:	SITE POSITION MESO CODE			<i>Short Name:</i>	SPMC
<i>Plural:</i>	SITE POSITION MESO CODE				
<i>Init. Volume:</i>	10	<i>Avg. Volume:</i>	15	<i>Max. Volume:</i>	20
				<i>Annual Growth Rate:</i>	10%

Description:

A list of codes that denote the relative position of the sampling site within a catchment area with the intent to be consistent within the scale of topography affecting surface water flow. The vertical difference is usually between 3 and 300m, and the surface area generally exceeds 0.5 has in size. Also known as slope position, and meso site position. Definition Source: "Describing Ecosystems in the Field", MOE Manual 11, Province of B.C. 1990, p. 31.

- Eg. C - Crest
- D - Depression
- F - Flat (Level)
- L - Lower Slope
- M - Middle Slope
- T - Toe
- U - Upper Slope

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* SITE POSITION MESO CODE	CODETABLE CODE	N	VARCHAR2	10
A code denoting the relative position of the sampling site within a catchment area with the intent to be consistent within the scale of topography affecting surface water flow. The vertical difference is usually between 3 and 300m, and the surface area generally exceeds 0.5 has in size. Also known as slope position, and meso site position. Definition Source: "Describing Ecosystems in the Field", MOE Manual 11, Province of B.C. 1990, p. 31.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

- MAY BE site position meso for one or more VEGETATION COVER POLYGON ADJ
- MAY BE site position meso for one or more VEGETATION COVER POLYGON EST
- MAY BE site position meso for one or more VEGETATION COVER POLYGON PRJ
- MAY BE position meso for one or more VEGETATION COVER POLYGON STG
- * = Relationships in primary unique identifier.

Unique Identifiers:

SPMC PK	Primary	Y
SITE POSITION MESO CODE		

Entity Name: SOIL MOISTURE REGIME CODE*Short Name:*

SMRC

Plural: SOIL MOISTURE REGIME CODE*Init. Volume:* 10*Avg. Volume:* 15*Max. Volume:* 20*Annual Growth Rate:* 10%**Description:**

A list of class-based codes approximating the average amount of soil water available annually for evapotranspiration by vascular plants, averaged over many years. Soil Moisture Regime is an interpretive attribute for estimation of site potential and site series classification. In VDYP, the value is between 0 and 8 or blank.

Eg. 0 - Very Xeric

1 - Xeric

2 - Subxeric

3 - Submesic

4 - Mesic

5 - Subhygric

6 - Hygric

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u> <u>Format</u>	<u>Length</u>
* SOIL MOISTURE REGIME CODE	CODETABLE CODE	N VARCHAR2	10
A class-based code approximating the average amount of soil water available annually for evapotranspiration by vascular plants, averaged over many years. Soil moisture Regime is an interpretive attribute for estimation of site potential and site series classification. The value is between 0 and 8 or blank.			
DESCRIPTION	CODETABLE DESCRIPTION	N VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.			
EFFECTIVE DATE	DATE TIME	N DATE	
Effective date/time			
EXPIRY DATE	DATE TIME	N DATE	
Expiry date/time			
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N DATE	
Update date/time			
* = Attributes in primary unique identifier.			

Relationships:Each Occurrence Of This Entity:

MAY BE moisture regime for one or more LAND COVER COMPONENT ADJ

MAY BE soil moisture regime for one or more LAND COVER COMPONENT EST

MAY BE moisture regime for one or more LAND COVER COMPONENT PRJ

MAY BE moisture regime for one or more LAND COVER COMPONENT STG

* = Relationships in primary unique identifier.

Unique Identifiers:

SMRC PK

Primary Y

SOIL MOISTURE REGIME CODE

Entity Name: SOIL NUTRIENT REGIME CODE			<i>Short Name:</i>	SNRC
<i>Plural:</i>	SOIL NUTRIENT REGIME CODE			
<i>Init. Volume:</i>	10	<i>Avg. Volume:</i>	15	<i>Max. Volume:</i> 20
			<i>Annual Growth Rate:</i>	10%

Description:

A list of codes that describe the Soil Nutrient Regime (SNR) referring to a code to denote the relative amount of essential soil nutrients, particularly nitrogen, available to vascular plants over a period of several years. Soil nutrient regime is an interpretative attribute that together with soil moisture regime, is used to assist in site series identification.

- Eg. A - Very Poor
B - Poor
C - Medium
D - Rich
E - Very Rich
F - Ultra Rich

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* SOIL NUTRIENT REGIME CODE	CODETABLE CODE	N	VARCHAR2	10
Soil Nutrient Regime (SNR) refers to a code to denote the relative amount of essential soil nutrients, particularly nitrogen, available to vascular plants over a period of several years. Soil nutrient regime is an interpretative attribute that together with soil moisture regime, is used to assist in site series identification.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

- MAY BE soil nutrient regime for one or more VEGETATION COVER POLYGON ADJ
MAY BE soil nutrient regime for one or more VEGETATION COVER POLYGON EST
MAY BE soil nutrient regime for one or more VEGETATION COVER POLYGON PRJ
MAY BE soil nutrient regime for one or more VEGETATION COVER POLYGON STG
* = Relationships in primary unique identifier.

Unique Identifiers:

SNRC PK	Primary	Y
SOIL NUTRIENT REGIME CODE		

Entity Name: STRATA ADJUSTED				Short Name:	SA
Plural:	STRATA ADJUSTED				
Init. Volume:	1000	Avg. Volume:	1050	Max. Volume:	1100
				Annual Growth Rate:	5%

Description:

This describes a strata within a project that is being adjusted. Entries into this entity will not be purged on entry of a new Project.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* STRATA ADJUSTED ID	NUMERIC IDENTIFIER	N	NUMBER	10
Unique Identifier for a strata, within a project.				
NAME	STRATA NAME	Y	VARCHAR2	100
Name of a strata, describing how the strata Id was identified. Eg. SAD_N_V_31 (spruce, balsam or deciduous leading, non-THLB, vegetated, greater than 30 years old).				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

- MUST BE strata for one and only one ADJUSTMENT PROJECT ADJUSTED
 - MAY BE sample for one or more SAMPLES USED ADJUSTED
 - MAY BE part of strata one or more STRATA POLYGON ADJUSTED
- * = Relationships in primary unique identifier.

Unique Identifiers:

SA PK	Primary	Y
STRATA ADJUSTED ID		

Entity Name: STRATA POLYGON ADJUSTED				Short Name:	SPA
Plural:	STRATA POLYGON ADJUSTED				
Init. Volume:	3800000	Avg. Volume:	4000000	Max. Volume:	4200000
				Annual Growth Rate:	5%

Description:

This is an intersecting entity, resolving the many-to-many association between the adjusted strata and adjusted cover polygon. Entries into this entity will not be purged on entry of a new Project.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* STRATA POLYGON ADJUSTED ID	NUMERIC IDENTIFIER	N	NUMBER	10
Primary unique numeric identifier for a strata/adjusted cover polygon association.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MUST BE polygon for one and only one STRATA ADJUSTED

MUST BE polygon for one and only one VEGETATION COVER POLYGON ADJUSTED

* = Relationships in primary unique identifier.

Unique Identifiers:

SPA PK	Primary	Y
STRATA POLYGON ADJUSTED ID		

Entity Name: STRATA POLYGON STAGING				Short Name:	SPS
Plural:	STRATA POLYGON STAGING				
Init. Volume:	30000	Avg. Volume:	30000	Max. Volume:	30000
				Annual Growth Rate:	0%

Description:

This is an intersecting entity, resolving the many-to-many association between the staging strata and staging cover polygon. Entries into this entity will not be purged on entry of a new Project.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* STRATA POLYGON STAGING ID	NUMERIC IDENTIFIER	N	NUMBER	10
Primary unique numeric identifir for a strata/adjusted cover polygon association.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MUST BE polygon for one and only one STRATA STAGING

MUST BE part of strata one and only one VEGETATION COVER POLYGON STAGING

* = Relationships in primary unique identifier.

Unique Identifiers:

SPS PK	Primary	Y
STRATA POLYGON STAGING ID		

Entity Name: STRATA STAGING				<i>Short Name:</i>	SS
<i>Plural:</i>	STRATA STAGING				
<i>Init. Volume:</i>	1000	<i>Avg. Volume:</i>	1000	<i>Max. Volume:</i>	1000
				<i>Annual Growth Rate:</i>	0%

Description:

This describes a strata within a project that is being staged. Entries into this entity will not be purged on entry of a new Project.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* STRATA STAGING ID	NUMERIC IDENTIFIER	N	NUMBER	10
Unique Identifier for a strata, within a project.				
NAME	STRATA NAME	Y	VARCHAR2	100
Name of a strata, describing how the strata Id was identified. Eg. SAD_N_V_31 (spruce, balsam or deciduous leading, non-THLB, vegetated, greater than 30 years old).				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MUST BE strata for one and only one ADJUSTMENT PROJECT STAGING

MAY BE sample for one or more SAMPLES USED STAGING

MAY BE part of strata one or more STRATA POLYGON STAGING

* = Relationships in primary unique identifier.

Unique Identifiers:

SS PK	Primary	Y
STRATA STAGING ID		

Entity Name: SURFACE EXPRESSION CODE			Short Name:	SEC
Plural:	SURFACE EXPRESSION CODE			
Init. Volume:	10	Avg. Volume:	10	Max. Volume: 20
			Annual Growth Rate:	10%

Description:

A list of codes that describe the surface expression that refers to the form and patterns of form of the surficial material within the polygon. Given the fact that a canopy of trees often blankets the ground surface, a simple classification attribute was selected. Surface expression is relatively easy to photo interpret on the medium scale photography and together with the attributes "modifying processes" and "site position meso" will provide clues to soil parent material and useful site classification data.

- Eg. C - Cone
- D - Depression
- F - Fan
- H - Hummock(s)
- M - Rolling
- N - None
- P - Plain
- R - Ridge(s)
- T - Terrace(s)
- U - Undulating

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* SURFACE EXPRESSION CODE	CODETABLE CODE	N	VARCHAR2	10
Surface expression refers to the form and patterns of form of the surficial material within the polygon. Given the fact that a canopy of trees often blankets the ground surface, a simple classification attribute was selected. Surface expression is relatively easy to photo interpret on the medium scale photography and together with the attributes "modifying processes" and "site position meso" will provide clues to soil parent material and useful site classification data.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

- MAY BE surface expression for one or more VEGETATION COVER POLYGON ADJ
 - MAY BE surface expression for one or more VEGETATION COVER POLYGON EST
 - MAY BE surface expression for one or more VEGETATION COVER POLYGON PRJ
 - MAY BE expression for one or more VEGETATION COVER POLYGON STG
- * = Relationships in primary unique identifier.

Unique Identifiers:

SEC PK	Primary	Y
SURFACE EXPRESSION CODE		

Entity Name: TREE COVER LAYER ADJUSTED**Short Name:**

TCLA

Plural: TREE COVER LAYER ADJUSTED**Init. Volume:** 3600000**Avg. Volume:** 3780000**Max. Volume:** 4000000**Annual Growth Rate:** 5%**Description:**

The table that maintains the unique business identification of a layer, or horizontal stratum, in a stand. Each layer is normally characterized as a distinct canopy containing a common forest cover structure with timber of similar ages (at least 40 years between layers) and heights (at least 10 meters between layers). Layers are assigned from the tallest layer downward.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* TREE COVER LAYER ADJUSTED ID	NUMERIC IDENTIFIER	N	NUMBER	10
Primary unique numerical identifier for an adjusted polygon's tree cover layer.				
LAYER ORDER	NUMERIC ORDER	Y	NUMBER	3
The order of a layer, or horizontal stratum, in a stand. Each layer is normally characterized as a distinct canopy containing a common forest cover structure with timber of similar ages (at least 40 years between layers) and heights (at least 10 meters between layers). Layers are assigned from the tallest layer downward.				
CROWN CLOSURE PCT	PERCENTAGE 3,0	Y	NUMBER	3,0
The photo-estimated percentage of ground area that is covered by the vertically projected crowns of the tree cover and layer within the polygon. It is expressed as a percentage of the entire polygon area.				
BASAL AREA	BASAL AREA	Y	NUMBER	10,6
Basal area is the total cross sectional area (at breast height), of all living trees visible to the photo interpreter. It is measured from the dominant, codominant and high intermediate crown positions, for each tree layer in the polygon. Basal area is expressed as square metres per hectare. It is used for the determination of species composition and timber volume.				
Note: Dominant trees have well developed crowns that extend above the general level of the trees around them. Codominant trees have crowns forming the general level of trees around them. High intermediate trees have smaller crowns slightly below, but extending into the general level of trees around them.				
VRI LIVE STEMS PER HA	STEMS PER HA	Y	NUMBER	8,3
The average number of living trees visible to the photo interpreter in the dominant, co-dominant and high intermediate crown positions in each tree layer in the polygon. It is expressed as stems per hectare. This attribute is also called stand density.				
ESTIMATED SITE INDEX	SITE INDEX	Y	NUMBER	5,3
Contains a numeric value that equates to a site's value, compared to the species.				
MINIMUM ADJUSTMENT DBH	HEIGHT - BREAST DIAMETER	Y	NUMBER	3,1
The cross sectional tree area at breast height. This attribute may be either observed, as per Vegetation Inventory data collection specifications, or calculated from growth projection models, e.g. VDYP.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				

* = Attributes in primary unique identifier.

Relationships:Each Occurrence Of This Entity:

Entity Name:	TREE COVER LAYER ADJUSTED (cont'd)	Short Name:	TCLA
---------------------	------------------------------------	--------------------	------

MAY BE adjusted by factor one or more ADJUSTMENT FACTOR ADJUSTED

MAY BE has tree cover pattern one and only one COVER PATTERN CODE

MAY BE describes data source basal area one and only one DATA SOURCE BASAL AREA CODE

MAY BE describes interpreted data source one and only one DATA SOURCE INTERPRETED CODE

MAY BE describes stems per ha one and only one DATA SRC VRI LIVE STEM HA CODE

MAY BE describes site index source code one and only one ESTIMATED SINDEXTREE SOURCE CODE

MAY BE describes forest cover rank one and only one FOREST COVER RANK CODE

MAY BE described by one and only one LAYER LEVEL CODE

MAY BE describes non forest descriptor one and only one NON FOREST DESCRIPTOR CODE

MAY BE has projection layer one and only one PROJECTION LAYER CODE

MAY BE is composed of one or more TREE SPECIES ADJUSTED

MUST BE describes tree maturity for one and only one VEGETATION COVER POLYGON ADJUSTED

MAY BE describes vertical complexity one and only one VERTICAL COMPLEXITY CODE

MAY BE has est site index species one and only one VRIMS TREE SPECIES CODE

** = Relationships in primary unique identifier.*

Unique Identifiers:

TCLA UK	Primary	N
MAY BE described by one and only one LAYER LEVEL CODE		
MUST BE describes tree maturity for one and only one VEGETATION COVER POLYGON ADJUSTED		
TCLA PK	Primary	Y
TREE COVER LAYER ADJUSTED ID		

Entity Name: TREE COVER LAYER ESTIMATED**Short Name:**

TCLE

Plural: TREE COVER LAYER ESTIMATED**Init. Volume:** 3600000**Avg. Volume:** 3780000**Max. Volume:** 4000000**Annual Growth Rate:** 5%**Description:**

The table that maintains the unique business identification of a layer, or horizontal stratum, in a stand. Each layer is normally characterized as a distinct canopy containing a common forest cover structure with timber of similar ages (at least 40 years between layers) and heights (at least 10 meters between layers). Layers are assigned from the tallest layer downward.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* TREE COVER LAYER ESTIMATED ID	NUMERIC IDENTIFIER	N	NUMBER	10
Primary unique numerical identifier for an estimated polygon's tree cover layer.				
LAYER ORDER	NUMERIC ORDER	Y	NUMBER	3
The unique business identification of a layer, or horizontal stratum, in a stand. Each layer is normally characterized as a distinct canopy containing a common forest cover structure with timber of similar ages (at least 40 years between layers) and heights (at least 10 meters between layers). Layers are assigned from the tallest layer downward.				
CROWN CLOSURE PCT	PERCENTAGE 3,0	Y	NUMBER	3,0
The photo-estimated percentage of ground area that is covered by the vertically projected crowns of the tree cover and layer within the polygon. It is expressed as a percentage of the entire polygon area.				
BASAL AREA	BASAL AREA	Y	NUMBER	10,6
Basal area is the total cross sectional area (at breast height), of all living trees visible to the photo interpreter. It is measured from the dominant, codominant and high intermediate crown positions, for each tree layer in the polygon. Basal area is expressed as square metres per hectare. It is used for the determination of species composition and timber volume.				
Note: Dominant trees have well developed crowns that extend above the general level of the trees around them. Codominant trees have crowns forming the general level of trees around them. High intermediate trees have smaller crowns slightly below, but extending into the general level of trees around them.				
VRI LIVE STEMS PER HA	STEMS PER HA	Y	NUMBER	8,3
The average number of living trees visible to the photo interpreter in the dominant, co-dominant and high intermediate crown positions in each tree layer in the polygon. It is expressed as stems per hectare. This attribute is also called stand density.				
ESTIMATED SITE INDEX	SITE INDEX	Y	NUMBER	5,3
Contains a numeric value that equates to a site's value, as compared to the species.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				

* = Attributes in primary unique identifier.

Relationships:Each Occurrence Of This Entity:

MAY BE has tree cover pattern one and only one COVER PATTERN CODE

MAY BE basal area sourced from one and only one DATA SOURCE BASAL AREA CODE

MAY BE has interpreted data source one and only one DATA SOURCE INTERPRETED CODE

MAY BE stems per ha sourced from one and only one DATA SRC VRI LIVE STEM HA CODE

MAY BE has site index source one and only one ESTIMATED SINDEXT SOURCE CODE

Entity Name:	TREE COVER LAYER ESTIMATED (cont'd)	Short Name:	TCLE
---------------------	-------------------------------------	--------------------	------

MAY BE has forest cover rank one and only one FOREST COVER RANK CODE

MAY BE of layer one and only one LAYER LEVEL CODE

MAY BE has non-forest descriptor one and only one NON FOREST DESCRIPTOR CODE

MAY BE is composed of one or more TREE SPECIES ESTIMATED

MUST BE describes tree maturity for one and only one VEGETATION COVER POLYGON ESTIMATED

MAY BE has vertical complexity one and only one VERTICAL COMPLEXITY CODE

MAY BE has est site index species one and only one VRIMS TREE SPECIES CODE

* = Relationships in primary unique identifier.

Unique Identifiers:

TCLE UK	Primary	N
MUST BE describes tree maturity for one and only one VEGETATION COVER POLYGON ESTIMATED		
MAY BE of layer one and only one LAYER LEVEL CODE		
TCLE PK	Primary	Y
TREE COVER LAYER ESTIMATED ID		

Entity Name: TREE COVER LAYER PROJECTED**Short Name:**

TCLP

Plural: TREE COVER LAYER PROJECTED**Init. Volume:** 3600000**Avg. Volume:** 3780000**Max. Volume:** 4000000**Annual Growth Rate:** 5%**Description:**

This maintains the unique business identification of a projected layer, or horizontal stratum, in a stand. Each layer is normally characterized as a distinct canopy containing a common forest cover structure with timber of similar ages (at least 40 years between layers) and heights (at least 10 meters between layers). Layers are assigned from the tallest layer downward.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* TREE COVER LAYER PROJECTED ID	NUMERIC IDENTIFIER	N	NUMBER	10
Primary unique numerical identifier for a projected polygon's tree cover layer.				
LAYER ORDER	NUMERIC ORDER	N	NUMBER	3
The order of a layer, or horizontal stratum, in a stand. Each layer is normally characterized as a distinct canopy containing a common forest cover structure with timber of similar ages (at least 40 years between layers) and heights (at least 10 meters between layers). Layers are assigned from the tallest layer downward.				
CROWN CLOSURE PCT	PERCENTAGE 3,0	Y	NUMBER	3,0
The photo-estimated percentage of ground area that is covered by the vertically projected crowns of the tree cover and layer within the polygon. It is expressed as a percentage of the entire polygon area.				
BASAL AREA	BASAL AREA	Y	NUMBER	10,6
Basal area is the total cross sectional area (at breast height), of all living trees visible to the photo interpreter. It is measured from the dominant, codominant and high intermediate crown positions, for each tree layer in the polygon. Basal area is expressed as square metres per hectare. It is used for the determination of species composition and timber volume.				
Note: Dominant trees have well developed crowns that extend above the general level of the trees around them. Codominant trees have crowns forming the general level of trees around them. High intermediate trees have smaller crowns slightly below, but extending into the general level of trees around them.				
VRI LIVE STEMS PER HA	STEMS PER HA	Y	NUMBER	8,3
The average number of living trees visible to the photo interpreter in the dominant, co-dominant and high intermediate crown positions in each tree layer in the polygon. It is expressed as stems per hectare. This attribute is also called stand density.				
ESTIMATED SITE INDEX	SITE INDEX	Y	NUMBER	5,3
Contains a numeric value that equates to a site's value, as compared to the species.				
MINIMUM ADJUSTMENT DBH	HEIGHT - BREAST DIAMETER	Y	NUMBER	3,1
The cross sectional tree area at breast height. This attribute may be either observed, as per Vegetation Inventory data collection specifications, or calculated from growth projection models, e.g. VDYP.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				

* = Attributes in primary unique identifier.

Relationships:Each Occurrence Of This Entity:

Entity Name:	TREE COVER LAYER PROJECTED (cont'd)	<i>Short Name:</i>	TCLP
---------------------	-------------------------------------	--------------------	------

MAY BE has tree cover pattern one and only one COVER PATTERN CODE

MAY BE basal area sourced from one and only one DATA SOURCE BASAL AREA CODE

MAY BE interpreted data sourced from one and only one DATA SOURCE INTERPRETED CODE

MAY BE stems per ha sourced from one and only one DATA SRC VRI LIVE STEM HA CODE

MAY BE has site index source one and only one ESTIMATED SINDEXTREE SOURCE CODE

MAY BE forest cover rank described by one and only one FOREST COVER RANK CODE

MAY BE layer at level one and only one LAYER LEVEL CODE

MAY BE of non-forest descriptor one and only one NON FOREST DESCRIPTOR CODE

MAY BE is composed of one or more TREE SPECIES PROJECTED

MUST BE describes tree maturity for one and only one VEGETATION COVER POLYGON PROJECTED

MAY BE has vertical complexity of one and only one VERTICAL COMPLEXITY CODE

MAY BE has est site index species one and only one VRIMS TREE SPECIES CODE

* = Relationships in primary unique identifier.

Unique Identifiers:

TCLP UK	Primary	N
MUST BE describes tree maturity for one and only one VEGETATION COVER POLYGON PROJECTED		
MAY BE layer at level one and only one LAYER LEVEL CODE		
TCLP PK	Primary	Y
TREE COVER LAYER PROJECTED ID		

Entity Name: TREE COVER LAYER STAGING

Short Name:

TCLS

Plural: TREE COVER LAYER STAGING

Init. Volume: 90000

Avg. Volume: 90000

Max. Volume: 120000

Annual Growth Rate: 0%

Description:

This maintains the unique business identification of a layer or horizontal stratum, that is being staged within a stand. Each layer is normally characterized as a distinct canopy containing a common forest cover structure with timber of similar ages (at least 40 years between layers) and heights (at least 10 meters between layers). Layers are assigned from the tallest layer downward.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* TREE COVER LAYER STAGING ID	NUMERIC IDENTIFIER	N	NUMBER	10
Primary unique numerical identifier for a staging polygon's tree cover layer.				
LAYER ORDER	NUMERIC ORDER	Y	NUMBER	3
The order of a layer, or horizontal stratum, in a stand. Each layer is normally characterized as a distinct canopy containing a common forest cover structure with timber of similar ages (at least 40 years between layers) and heights (at least 10 meters between layers). Layers are assigned from the tallest layer downward.				
CROWN CLOSURE PCT	PERCENTAGE 3,0	Y	NUMBER	3,0
The photo-estimated percentage of ground area that is covered by the vertically projected crowns of the tree cover and layer within the polygon. It is expressed as a percentage of the entire polygon area.				
BASAL AREA	BASAL AREA	Y	NUMBER	10,6
Basal area is the total cross sectional area (at breast height), of all living trees visible to the photo interpreter. It is measured from the dominant, codominant and high intermediate crown positions, for each tree layer in the polygon. Basal area is expressed as square metres per hectare. It is used for the determination of species composition and timber volume.				
Note: Dominant trees have well developed crowns that extend above the general level of the trees around them. Codominant trees have crowns forming the general level of trees around them. High intermediate trees have smaller crowns slightly below, but extending into the general level of trees around them.				
VRI LIVE STEMS PER HA	STEMS PER HA	Y	NUMBER	8,3
The average number of living trees visible to the photo interpreter in the dominant, co-dominant and high intermediate crown positions in each tree layer in the polygon. It is expressed as stems per hectare. This attribute is also called stand density.				
ESTIMATED SITE INDEX	SITE INDEX	Y	NUMBER	5,3
Contains a numeric value that equates to a site's value, as compared to the species.				
MINIMUM ADJUSTMENT DBH	HEIGHT - BREAST DIAMETER	Y	NUMBER	3,1
The cross sectional tree area at breast height. This attribute may be either observed, as per Vegetation Inventory data collection specifications, or calculated from growth projection models, e.g. VDYP.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				

* = Attributes in primary unique identifier.

Relationships:Each Occurrence Of This Entity:

Entity Name:	TREE COVER LAYER STAGING (cont'd)	Short Name:	TCLS
---------------------	-----------------------------------	--------------------	------

MAY BE adjusted by factor one or more ADJUSTMENT FACTOR STAGING

MAY BE has tree cover pattern one and only one COVER PATTERN CODE

MAY BE basal area sourced by one and only one DATA SOURCE BASAL AREA CODE

MAY BE of interpreted data source one and only one DATA SOURCE INTERPRETED CODE

MAY BE stems per ha sourced by one and only one DATA SRC VRI LIVE STEM HA CODE

MAY BE of site index source code one and only one ESTIMATED SINDEXTREE SOURCE CODE

MAY BE of forest cover rank one and only one FOREST COVER RANK CODE

MAY BE layer at level one and only one LAYER LEVEL CODE

MAY BE has non forest descriptor one and only one NON FOREST DESCRIPTOR CODE

MAY BE has projection layer one and only one PROJECTION LAYER CODE

MAY BE is composed of one or more TREE SPECIES STAGING

MUST BE describes tree maturity for one and only one VEGETATION COVER POLYGON STAGING

MAY BE has vertical complexity one and only one VERTICAL COMPLEXITY CODE

MAY BE has est site index species one and only one VRIMS TREE SPECIES CODE

** = Relationships in primary unique identifier.*

Unique Identifiers:

TCLS UK	Primary	N
<i>MUST BE describes tree maturity for one and only one VEGETATION COVER POLYGON STAGING</i>		
<i>MAY BE layer at level one and only one LAYER LEVEL CODE</i>		
TCLS PK	Primary	Y
<i>TREE COVER LAYER STAGING ID</i>		

Entity Name: TREE SPECIES ADJUSTED				Short Name:	TSA
Plural:	TREE SPECIES ADJUSTED				
Init. Volume:	8000000	Avg. Volume:	8400000	Max. Volume:	8820000
				Annual Growth Rate:	5%

Description:

The table that maintains the business area supplied sequence of tree species. Normally, tree species are ordered by the Estimated Composition Percentage, however, this attribute represents the implied distinction where the percentage is the same. For example, where Estimated Composition Percentage is equal for two tree species, their supplied sequence implies an order of business preference.

Attribtes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* TREE SPECIES ADJUSTED ID	NUMERIC IDENTIFIER	N	NUMBER	10
Primary unique numerical identifier for an adjusted polygon's tree species.				
SPECIES ORDER	SPECIES ID	N	NUMBER	1
The order of the tree species importance, in terms of the dominance that a species has within the stand. Normally, tree species are ordered by the Estimated Composition Percentage, however, this attribute represents the implied distinction where the percentage is the same. For example, where Estimated Composition Percentage is equal for two tree species, their supplied sequence implies an order of business preference. This attribute was previously represented as the SPECIES_ID in the LRDW, but has been extracted from the primary key to abstract the business meaning of the attribute's value away from the database's physical dependance on it. This allows the primary key of the table to be changed (possibly required by a data fix or new processing method) without changing the business meaning of the SPECIES ORDER value.				
SPECIES PCT	PERCENTAGE 5,2	N	NUMBER	5,2
Percentages of the layer that each tree species occupies. For older stands, tree species percentage is based on relative basal area; for younger stands, tree species percentage is based on the number of stems per hectare. Tree species percentage is estimated to the nearest percent for all living trees above a specified diameter.				
AGE	NUMERIC AGE	Y	NUMBER	4,1
Age is an average age, weighted by basal area, of the dominant, codominant and high intermediate trees for the leading and second species of each tree layer identified. Stand age can be based on an estimate from aerial photographs.				
Note: Dominant trees have well developed crowns that extend above the general level of the trees around them. Codominant trees have crowns forming the general level of trees around them. High intermediate trees have smaller crowns slightly below but extending into the general level of trees around them. This value is not generally present for codominant species in the stand.				
HEIGHT	HEIGHT - TREE SPECIES	Y	NUMBER	5,3
The average height, weighted by basal area, of the dominant, co-dominant, and high intermediate trees for the leading and second species of each tree layer identified.				
Note: Dominant trees have well developed crowns that extend above the general level of the trees around them. Codominant trees have crowns forming the general level of trees around them. High intermediate trees have smaller crowns slightly below but extending into the general level of trees around them. This value is not generally present for codominant species in the stand.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				

Entity Name:	TREE SPECIES ADJUSTED (cont'd)	Short Name:	TSA
---------------------	--------------------------------	--------------------	-----

* = Attributes in primary unique identifier.

Relationships:

Each Occurrence Of This Entity:

- MAY BE adjusted by factor one or more ADJUSTMENT FACTOR ADJUSTED
- MAY BE describes source age one and only one DATA SOURCE AGE CODE
- MAY BE describes source height one and only one DATA SOURCE HEIGHT CODE
- MUST BE describes a tree species within one and only one TREE COVER LAYER ADJUSTED
- MAY BE has leading commercial/brush species one and only one VRIMS TREE SPECIES CODE

* = Relationships in primary unique identifier.

Unique Identifiers:

- | | | |
|--|---------|---|
| TSA UK | Primary | N |
| SPECIES ORDER | | |
| MUST BE describes a tree species within one and only one TREE COVER LAYER ADJUSTED | | |
| TSA PK | Primary | Y |
| TREE SPECIES ADJUSTED ID | | |

Entity Name: TREE SPECIES ESTIMATED**Short Name:**

TSE

Plural: TREE SPECIES ESTIMATED**Init. Volume:** 8000000**Avg. Volume:** 8400000**Max. Volume:** 8820000**Annual Growth Rate:** 5%**Description:**

The table that maintains the business area supplied sequence of tree species. Normally, tree species are ordered by the Estimated Composition Percentage, however, this attribute represents the implied distinction where the percentage is the same. For example, where Estimated Composition Percentage is equal for two tree species, their supplied sequence implies an order of business preference.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* TREE SPECIES ESTIMATED ID	NUMERIC IDENTIFIER	N	NUMBER	10
Primary unique numerical identifier for an estimated polygon's tree species.				
SPECIES ORDER	SPECIES ID	N	NUMBER	1
The order of the tree species importance, in terms of the dominance that a species has within the stand. Normally, tree species are ordered by the Estimated Composition Percentage, however, this attribute represents the implied distinction where the percentage is the same. For example, where Estimated Composition Percentage is equal for two tree species, their supplied sequence implies an order of business preference. This attribute was previously represented as the SPECIES_ID in the LRDW, but has been extracted from the primary key to abstract the business meaning of the attribute's value away from the database's physical dependance on it. This allows the primary key of the table to be changed (possibly required by a data fix or new processing method) without changing the business meaning of the SPECIES ORDER value.				
SPECIES PCT	PERCENTAGE 5,2	N	NUMBER	5,2
Percentages of the layer that each tree species occupies. For older stands, tree species percentage is based on relative basal area; for younger stands, tree species percentage is based on the number of stems per hectare. Tree species percentage is estimated to the nearest percent for all living trees above a specified diameter.				
AGE	NUMERIC AGE	Y	NUMBER	4,1
Age is an average age, weighted by basal area, of the dominant, codominant and high intermediate trees for the leading and second species of each tree layer identified. Stand age can be based on an estimate from aerial photographs.				
Note: Dominant trees have well developed crowns that extend above the general level of the trees around them. Codominant trees have crowns forming the general level of trees around them. High intermediate trees have smaller crowns slightly below but extending into the general level of trees around them. This value is not generally present for codominant species in the stand.				
HEIGHT	HEIGHT - TREE SPECIES	Y	NUMBER	5,3
The average height, weighted by basal area, of the dominant, co-dominant, and high intermediate trees for the leading and second species of each tree layer identified.				
Note: Dominant trees have well developed crowns that extend above the general level of the trees around them. Codominant trees have crowns forming the general level of trees around them. High intermediate trees have smaller crowns slightly below but extending into the general level of trees around them. This value is not generally present for codominant species in the stand.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				

Entity Name:	TREE SPECIES ESTIMATED (cont'd)	<i>Short Name:</i>	TSE
---------------------	---------------------------------	--------------------	-----

* = Attributes in primary unique identifier.

Relationships:

Each Occurrence Of This Entity:

- MAY BE age sourced by one and only one DATA SOURCE AGE CODE
- MAY BE height sourced by one and only one DATA SOURCE HEIGHT CODE
- MUST BE describes a tree species within one and only one TREE COVER LAYER ESTIMATED
- MAY BE has leading commercial/brush species one and only one VRIMS TREE SPECIES CODE

* = Relationships in primary unique identifier.

Unique Identifiers:

TSE UK	Primary	N
SPECIES ORDER		
MUST BE describes a tree species within one and only one TREE COVER LAYER ESTIMATED		
TSE PK	Primary	Y
TREE SPECIES ESTIMATED ID		

Entity Name: TREE SPECIES PROJECTED				Short Name:	TSP
Plural:	TREE SPECIES PROJECTED				
Init. Volume:	8000000	Avg. Volume:	8400000	Max. Volume:	8820000
				Annual Growth Rate:	5%

Description:

This maintains the business area supplied sequence of a projected tree species. Normally, tree species are ordered by the Estimated Composition Percentage, however, this attribute represents the implied distinction where the percentage is the same. For example, where Estimated Composition Percentage is equal for two tree species, their supplied sequence implies an order of business preference.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* TREE SPECIES PROJECTED ID	NUMERIC IDENTIFIER	N	NUMBER	10
Primary unique numerical identifier for a projected polygon's tree species.				
SPECIES ORDER	SPECIES ID	N	NUMBER	1
The order of the tree species importance, in terms of the dominance that a species has within the stand. Normally, tree species are ordered by the Estimated Composition Percentage, however, this attribute represents the implied distinction where the percentage is the same. For example, where Estimated Composition Percentage is equal for two tree species, their supplied sequence implies an order of business preference. This attribute was previously represented as the SPECIES_ID in the LRDW, but has been extracted from the primary key to abstract the business meaning of the attribute's value away from the database's physical dependance on it. This allows the primary key of the table to be changed (possibly required by a data fix or new processing method) without changing the business meaning of the SPECIES ORDER value.				
SPECIES PCT	PERCENTAGE 5,2	N	NUMBER	5,2
Percentages of the layer that each tree species occupies. For older stands, tree species percentage is based on relative basal area; for younger stands, tree species percentage is based on the number of stems per hectare. Tree species percentage is estimated to the nearest percent for all living trees above a specified diameter.				
AGE	NUMERIC AGE	Y	NUMBER	4,1
Age is an average age, weighted by basal area, of the dominant, codominant and high intermediate trees for the leading and second species of each tree layer identified. Stand age can be based on an estimate from aerial photographs.				
Note: Dominant trees have well developed crowns that extend above the general level of the trees around them. Codominant trees have crowns forming the general level of trees around them. High intermediate trees have smaller crowns slightly below but extending into the general level of trees around them. This value is not generally present for codominant species in the stand.				
HEIGHT	HEIGHT - TREE SPECIES	Y	NUMBER	5,3
The average height, weighted by basal area, of the dominant, co-dominant, and high intermediate trees for the leading and second species of each tree layer identified.				
Note: Dominant trees have well developed crowns that extend above the general level of the trees around them. Codominant trees have crowns forming the general level of trees around them. High intermediate trees have smaller crowns slightly below but extending into the general level of trees around them. This value is not generally present for codominant species in the stand.				
DERIVED SITE INDEX	DERIVED SITE INDEX	Y	NUMBER	3,1
Derived site index is an model predicted site index for tree layers with a leading species age greater than 30 years. Site index is the mean height of the dominant and codominant trees will attain at a base index age (50 years) used for the purposes of estimating forest site growth capability. The site index is based on a normalized set of coefficients calibrated to reflect the range of heights for a given tree species.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30

Entity Name:	TREE SPECIES PROJECTED (cont'd)	Short Name:	TSP
---------------------	---------------------------------	-------------	-----

Entry by userid			
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE
Update date/time			
UPDATE USERID	AUDIT USERID	N	VARCHAR2 30
Updated by userid			

* = Attributes in primary unique identifier.

Relationships:

Each Occurrence Of This Entity:

- MAY BE of source age one and only one DATA SOURCE AGE CODE
- MAY BE of source height one and only one DATA SOURCE HEIGHT CODE
- MAY BE is composed of one or more PROJECTED YIELD
- MUST BE describes a tree species within one and only one TREE COVER LAYER PROJECTED
- MAY BE has leading commercial/brush species one and only one VRIMS TREE SPECIES CODE

* = Relationships in primary unique identifier.

Unique Identifiers:

TSP UK	Primary	N
SPECIES ORDER		
MUST BE describes a tree species within one and only one TREE COVER LAYER PROJECTED		
TSP PK	Primary	Y
TREE SPECIES PROJECTED ID		

Entity Name: TREE SPECIES STAGING				Short Name:	TSS
Plural:	TREE SPECIES STAGING				
Init. Volume:	180000	Avg. Volume:	180000	Max. Volume:	180000
				Annual Growth Rate:	0%

Description:

The table that maintains the business area supplied sequence of tree species. Normally, tree species are ordered by the Estimated Composition Percentage, however, this attribute represents the implied distinction where the percentage is the same. For example, where Estimated Composition Percentage is equal for two tree species, their supplied sequence implies an order of business preference.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* TREE SPECIES STAGING ID	NUMERIC IDENTIFIER	N	NUMBER	10
Primary unique numerical identifier for a staging polygon's tree species.				
SPECIES ORDER	SPECIES ID	Y	NUMBER	1
The order of the tree species importance, in terms of the dominance that a species has within the stand. Normally, tree species are ordered by the Estimated Composition Percentage, however, this attribute represents the implied distinction where the percentage is the same. For example, where Estimated Composition Percentage is equal for two tree species, their supplied sequence implies an order of business preference. This attribute was previously represented as the SPECIES_ID in the LRDW, but has been extracted from the primary key to abstract the business meaning of the attribute's value away from the database's physical dependance on it. This allows the primary key of the table to be changed (possibly required by a data fix or new processing method) without changing the business meaning of the SPECIES ORDER value. Due to the possibly invalid nature of Staging area data, the SPECIES ORDER is optional in this context only.				
SPECIES PCT	PERCENTAGE 5,2	Y	NUMBER	5,2
Percentages of the layer that each tree species occupies. For older stands, tree species percentage is based on relative basal area; for younger stands, tree species percentage is based on the number of stems per hectare. Tree species percentage is estimated to the nearest percent for all living trees above a specified diameter.				
AGE	NUMERIC AGE	Y	NUMBER	4,1
Age is an average age, weighted by basal area, of the dominant, codominant and high intermediate trees for the leading and second species of each tree layer identified. Stand age can be based on an estimate from aerial photographs.				
Note: Dominant trees have well developed crowns that extend above the general level of the trees around them. Codominant trees have crowns forming the general level of trees around them. High intermediate trees have smaller crowns slightly below but extending into the general level of trees around them. This value is not generally present for codominant species in the stand.				
HEIGHT	HEIGHT - TREE SPECIES	Y	NUMBER	5,3
The average height, weighted by basal area, of the dominant, co-dominant, and high intermediate trees for the leading and second species of each tree layer identified.				
Note: Dominant trees have well developed crowns that extend above the general level of the trees around them. Codominant trees have crowns forming the general level of trees around them. High intermediate trees have smaller crowns slightly below but extending into the general level of trees around them. This value is not generally present for codominant species in the stand.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30

Entity Name:	TREE SPECIES STAGING (cont'd)	<i>Short Name:</i>	TSS
---------------------	-------------------------------	--------------------	-----

Updated by userid

* = *Attributes in primary unique identifier.*

Relationships:

Each Occurrence Of This Entity:

- MAY BE adjusted by factor one or more ADJUSTMENT FACTOR STAGING
 - MAY BE of source age one and only one DATA SOURCE AGE CODE
 - MAY BE of source height one and only one DATA SOURCE HEIGHT CODE
 - MUST BE describes a tree species within one and only one TREE COVER LAYER STAGING
 - MAY BE has leading commercial/brush species one and only one VRIMS TREE SPECIES CODE
- * = *Relationships in primary unique identifier.*

Unique Identifiers:

TSS UK	<i>Primary</i>	<i>N</i>
<i>SPECIES ORDER</i>		
<i>MUST BE describes a tree species within one and only one TREE COVER LAYER STAGING</i>		
TSS PK	<i>Primary</i>	<i>Y</i>
<i>TREE SPECIES STAGING ID</i>		

Entity Name: VEG COMP LAYER**Short Name:** VEG_VCL**Plural:** VEG COMP LAYER**Init. Volume:** 3800000**Avg. Volume:** 4000000**Max. Volume:** 4200000**Annual Growth Rate:** 5%**Description:**

This is a denormalized summary table combining fields from the following tables: TREE_COVER_LAYER, TREE_SPECIES, TREE_SPECIES_VOLUME, CORP_ORG_UNIT. This table contains a static cut of the VRI data projected to current year and will be updated annually. It is intended for strategic level resource analysis using the current GIS tools. ArcGIS users will link this table to VEG_COMP_POLYGON.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* FEATURE_ID		N	VARCHAR2	32
Provincially unique identifier for an instance of a spatial feature.				
* LAYER_ID		N	VARCHAR2	1
The unique business identification of a layer, or horizontal stratum, in a stand. Each layer is normally characterized as a distinct canopy containing a common forest cover structure with timber of similar ages (at least 40 years between layers) and heights (at least 10 meters between layers). Layers are assigned from the tallest layer downward.				
FOR_COVER_RANK_CD		Y	VARCHAR2	1
A numeric designation of the relative importance of the layer component in the stand as determined by the business. The level of importance decreases as the numeric designation increases. For Vegetation Cover originated data, this value is assigned via business rule based on the supplied order of the layer records as recorded by the interpreter. For FIP originated data, this value is known as the RANK CD, and is explicitly supplied by the interpreter. The RANK CD, or ranking, is based on Regional guidelines at the time of interpretation. This value is retained for FIP transition purposes, as tree volumes are only calculated by VDYP, the current software/mathematical model in production. The RANK CD will be superseded in time when Vegetation Inventory projection tools are developed.				
NON_FOREST_DESCRIPTOR		Y	VARCHAR2	5
Non commercial forest vegetation on a polygon that is capable of supporting commercial forests. Maps directly to the FIP attribute, NON FOREST DESCRIPTOR and is also utilized for the determination of the BC Land Cover Classification. This is a FIP classification based attribute only, and is retained for the purposes of business transition from FIP to Vegetation Inventory.				
INTERPRETED_DATA_SRC_CD		Y	NUMBER	2,0
The source of the data that contributed to the determination of the classification description. All values taken from Table 3-1, PIP This list of values is similar, but not identical to the FIP DATA SOURCE which will be used to validate the FIP file prior to loading. Non-conforming FIP DATA SOURCE values will be converted to the VEGETATION DATA SOURCE values on load to the Vegetative Cover database.				
QUAD_DIAM_125		Y	NUMBER	4,1
The quadratic mean stand diameter (breast height), at the projection date, based on the 22.5 cm utilization level. Calculated for Rank 1 stands only, type id (TYPID) 1 through 3.				
QUAD_DIAM_175		Y	NUMBER	4,1
The quadratic mean stand diameter (breast height), at the projection date, based on the 17.5 cm utilization level. Calculated for Rank 1 stands only, Type id (TYPID) for 1 through 3.				
QUAD_DIAM_225		Y	NUMBER	4,1
The quadratic mean stand diameter (breast height), at the projection date, based on the 22.5 cm utilization level. Calculated for Rank 1 stands only, type id (TYPID) 1 through 3.				
EST_SITE_INDEX_SPECIES_CD		Y	VARCHAR2	3
The species to which the estimated site index applies.				
EST_SITE_INDEX		Y	NUMBER	2,0
Estimated site index is an interpreter estimated site index for tree layers with a leading species age less than 31 years. Site index is the mean height of the dominant and codominant trees will attain at a base index age (50 years) used for the purposes of				

Entity Name: VEG COMP LAYER (cont'd)	<i>Short Name:</i>	VEG_VCL
estimating forest site growth capability. The site index is based on a normalized set of coefficients calibrated to reflect the range of heights for a given tree species.		
DERIVED_SITE_INDEX_CD	Y VARCHAR2	1
Derived site index is an model predicted site index for tree layers with a leading species age greater than 30 years. Site index is the mean height of the dominant and codominant trees will attain at a base index age (50 years) used for the purposes of estimating forest site growth capability. The site index is based on a normalized set of coefficients calibrated to reflect the range of heights for a given tree species.		
REF_YEAR_TYPE_ID	Y NUMBER	2,0
The classification derived from the layer's vegetation cover at the time of data collection (i.e. reference year). The classification reflects the value, importance or status of the vegetation cover with respect to forestry values. Classifications are distinct and range from 1 to 9.		
PROJ_TYPE_ID	Y NUMBER	2,0
The classification of the layer's vegetation cover at the year of projection. The classification reflects the absence or value/importance/status of the vegetation cover with respect to forestry values.		
INVENTORY_TYPE_GROUP_SRC_CD	Y VARCHAR2	1
The data source of the value of the Inventory Type Group (a grouping of the leading species and their relative composition percent). This has been renamed from the FIP attribute, INVENTORY TYPE GROUP ORIGIN. An additional value of 'TBL' has been added on conversion to the Vegetative Cover Database to explicitly represent the occurrence of a blank.		
INVENTORY_TYPE_GROUP_NUM	Y NUMBER	2,0
The designation of species composition by one of 42 type groups, each being a unique combination of pure or mixed species.		
VOLUME_ADJ_FACTOR	Y NUMBER	4,2
A factor or constant value applied to the volume calculation. Historically, decay, waste and breakage have been applied to the tree volumes (as reductions) though under the Vegetation Inventory design, direct adjustments to tree volume are applied		
HIST_CLASS_S_CD	Y VARCHAR2	1
A code for the site class (e.g. stand productivity) at the time of classification. This is a derived field based on the height and age of the leading species. Retained for historical purposes only.		
HIST_CLASS_SS_CD	Y VARCHAR2	1
A code indicating that the old site class of the stand, based on stand age and height, does not reflect the productive capacity of the land due to masking by external agents or to a high degree of variability between heights and ages. This special site classification is based on an assessment of physical and biological factors. Used for historical purposes only.		
CROWN_CLOSURE	Y NUMBER	3,0
The percentage of ground area covered by the vertically projected crowns of the tree cover for each tree layer within the polygon.		
STOCKING_CLASS_CD	Y VARCHAR2	1
A code describing the stocking class of the layer at the reference year. Stocking class is based on leading commercial species, stand age and/or the size (diameter) and number of stems per hectare. It is a FIP base attribute that is semantically overloaded with meaning. It is being retained in the Vegetative Cover database to facilitate the interim operation of the tree volume derivation routine, VDYP. Stocking Class variously means: immature, mature trees, density and diameter distribution combinations for certain tree species, and harvested with a remaining canopy. It is expected that this attribute will be eliminated once VDYP 6 dependencies are removed..		
STOCKING_CLASS_SRC_CD	Y VARCHAR2	1
A code indicating whether the layer's Stocking Class was input (e.g. measured or estimated) or derived.		
REFERENCE_DATE	Y DATE	

Entity Name: VEG COMP LAYER (cont'd)	<i>Short Name:</i>	VEG_VCL
The date of the source data on which the interpretation is based. Known as the 'Reference Year' in the VIF file.		
PROJECTED_STOCKING_CLASS_CD	Y VARCHAR2	1
A code describing the stocking class of the layer at the year of projection. Stocking class is determined based on the leading commercial species and/or the size (diameter) and number of stems per hectare.		
SITE_INDEX	Y NUMBER	4,1
Site index is an estimate of site productivity for tree growth (height in metres at breast height age of 50 years). The mean height of the dominant and codominant trees will attain at a base index age used for the purposes of estimating forest site growth capability. The site index is based on a normalized set of coefficients calibrated to reflect the range of heights for a given tree species.		
YEAR_OF_ESTAB	Y DATE	
The year the tree began to grow; applied to a layer (FIP) or a tree species (Vegetative Cover). Known as the Year of Stand Establishment in the FIP file.		
DBH_LIMIT	Y NUMBER	2,0
A code indicating the minimum diameter breast height (DBH) for measuring trees (i.e. stems) in the field sample. For example, a code of 3 indicates that stems were measured if they had a DBH greater than or equal to 7.5cm.		
CULMINATION_MAI_125	Y NUMBER	4,1
The maximum annual increment in stand volume at the 12.5 cm utilization level. Culmination MAI is determined net decay only and only for type id (TYPID) 1, 2, 3, 4, 5 and 9. It is the Increment of tree volume to a given age in years divided by that age for that utilization level		
CULMINATION_MAI_175	Y NUMBER	4,1
The maximum annual increment in stand volume at the 17.5 cm utilization level. Culmination MAI is determined net decay only and only for type id (TYPID) 1, 2, 3, 4, 5 and 9. It is the total increment of tree volume to a given age in years divided by that age for that utilization level		
CULMINATION_MAI_225	Y NUMBER	4,1
The maximum annual increment in stand volume at the 22.5 cm utilization level. Culmination MAI is determined net decay only and only for type id (TYPID) 1, 2, 3, 4, 5 and 9. It is the total increment of tree volume to a given age in years divided by that age for that utilization level		
CONF_INDEX_BASAL_AREA_CD	Y NUMBER	2,0
Confidence indices are a subjective value that reflect confidence of the photo interpreter in the estimation of basal area for each layer.		
DATA_SOURCE_BASAL_AREA_CD	Y NUMBER	2,0
The source of data used for the interpretation of basal area.		
VRI_LIVE_STEMS_PER_HA	Y NUMBER	6,0
The average number of living trees visible to the photo interpreter in the dominant, codominant and high intermediate crown positions in each tree layer in the polygon. It is expressed as stems per hectare.		
DATA_SRC_VRI_LIVE_STEM_HA_CD	Y NUMBER	2,0
The source of data used for the interpretation of stand density.		
VRI_DEAD_STEMS_PER_HA	Y NUMBER	4,0
The number of VRI dead tree stems on an unitary per hectare basis.		
TREE_COVER_PATTERN	Y NUMBER	2,0
The spatial distribution of the tree cover within each tree layer in the polygon. Definition Source: p 6-1, PIP Data Value Source; Figure 6-1		
VERTICAL_COMPLEXITY	Y NUMBER	2,0
The subjective classification that describes the form of each tree layer as indicated by the relative uniformity of the forest canopy as it appears on mid-scale aerial photographs.		

Entity Name: VEG COMP LAYER (cont'd)		Short Name:	VEG_VCL
Vertical complexity is influenced by stand age, species (succession as it relates to shade tolerance) and degree and age of past disturbances. The tree height range is calculated as the total difference in height between the tallest and shortest visible dominant, codominant, and high intermediate trees. To most adequately represent the tree layer of interest, occasional occurrences of either very tall or very short trees should be ignored so that the vertical complexity indicated is for the majority of stems in the dominant, codominant, and high intermediate portion of each tree layer.			
LOSS_TYPE_CD	Y VARCHAR2		3
This field is intended to hold a code indicating the method use to determine the methodology used to determine the volume reductions due to decay. The field is currently not populated in the Oracle data base			
SPECIES_CD_1	Y VARCHAR2		4
The code indicating the type of tree species predominate or leading in the tree layer. A "leading" species is identified as being the highest percent basal area or, if a very young stand, the relative number of stems per hectare. Species are described in terms of Genus, Species and variety.			
SPECIES_PCT_1	Y NUMBER		3,0
Percentages of the layer that the leading species occupies. For older stands, tree species percentage is based on percent basal area or, if a very young stand, the relative number of stems per hectare. Tree species percentage is estimated to the nearest percent for all living trees above a specified diameter.			
SPECIES_CD_2	Y VARCHAR2		4
The code indicating the type of tree species second most dominate in the tree layer. A "second" species is identified in descending order of species percent from the "leading" species. Species are described in terms of Genus, Species and variety.			
SPECIES_PCT_2	Y NUMBER		3,0
Percentages of the layer that the second most dominate species occupies. For older stands, tree species percentage is based on percent basal area or, if a very young stand, the relative number of stems per hectare. Tree species percentage is estimated to the nearest percent for all living trees above a specified diameter.			
SPECIES_CD_3	Y VARCHAR2		4
The code indicating the type of tree species third most dominate in the tree layer. A "third" species is identified in descending order of species percent from the "leading" species. Species are described in terms of Genus, Species and variety.			
SPECIES_PCT_3	Y NUMBER		3,0
Percentages of the layer that the third most dominate species occupies. For older stands, tree species percentage is based on percent basal area or, if a very young stand, the relative number of stems per hectare. Tree species percentage is estimated to the nearest percent for all living trees above a specified diameter.			
SPECIES_CD_4	Y VARCHAR2		4
The code indicating the type of tree species fourth most dominate in the tree layer. The "fourth" species is identified in descending order of species percent from the "leading" species. Species are described in terms of Genus, Species and variety.			
SPECIES_PCT_4	Y NUMBER		3,0
Percentages of the layer that the fourth most dominate species occupies. For older stands, tree species percentage is based on percent basal area or, if a very young stand, the relative number of stems per hectare. Tree species percentage is estimated to the nearest percent for all living trees above a specified diameter.			
SPECIES_CD_5	Y VARCHAR2		4
The code indicating the type of tree species fifth most dominate in the tree layer. The "fifth" species is identified in descending order of species percent from the "leading" species. Species are described in terms of Genus, Species and variety.			
SPECIES_PCT_5	Y NUMBER		3,0
Percentages of the layer that the fifth most dominate species occupies. For older stands, tree species percentage is based on percent basal area or, if a very young stand, the relative			

Entity Name: VEG COMP LAYER (cont'd)		Short Name:	VEG_VCL
number of stems per hectare. Tree species percentage is estimated to the nearest percent for all living trees above a specified diameter.			
SPECIES_CD_6	Y VARCHAR2	4	
The code indicating the type of tree species sixth most dominate in the tree layer. The "sixth" species is identified in descending order of species percent from the "leading" species. Species are described in terms of Genus, Species and variety.			
SPECIES_PCT_6	Y NUMBER	3,0	
Percentages of the layer that the sixth most dominate species occupies. For older stands, tree species percentage is based on percent basal area or, if a very young stand, the relative number of stems per hectare. Tree species percentage is estimated to the nearest percent for all living trees above a specified diameter.			
AGE_1	Y NUMBER	3,0	
The age of a stand at the time of classification, for Species 1. Stand age is based on a ring count from a bored core plus a correction for the age of the tree below the core sample height. Stand age can also be based on an estimate from aerial photographs.			
PROJ_AGE_1	Y NUMBER	3,0	
The age projected to the adjustment area ground sample date, for Species 1.			
AGE_2	Y NUMBER	3,0	
The age of a stand at the time of classification, for Species 2. Stand age is based on a ring count from a bored core plus a correction for the age of the tree below the core sample height. Stand age can also be based on an estimate from aerial photographs.			
PROJ_AGE_2	Y NUMBER	3,0	
The age projected to the adjustment area ground sample date, for Species 2.			
DATA_SOURCE_AGE_CD	Y NUMBER	3,0	
The source of data used for the interpretation of year of origin (age), for Species 1.			
UPDATE_AGE_DATE	Y DATE		
The date the DATE OF ORIGIN (tree age to many users) was revised after it was originally interpreted as part of the Vegetation Inventory classification. For Species 1.			
HEIGHT_1	Y NUMBER	4,1	
The average height, weighted by basal area, of the dominant, codominant, and high intermediate trees for the leading and second species of each tree layer identified. For Species 1.			
PROJ_HEIGHT_1	Y NUMBER	4,1	
The height projected to the adjustment area ground sample date, for Species 1.			
HEIGHT_2	Y NUMBER	4,1	
The average height, weighted by basal area, of the dominant, codominant, and high intermediate trees for the leading and second species of each tree layer identified. For Species 2.			
PROJ_HEIGHT_2	Y NUMBER	4,1	
The height projected to the adjustment area ground sample date, for Species 2.			
DATA_SOURCE_HEIGHT_CD	Y NUMBER	2,0	
The source of data used for the interpretation of height, for Species 1.			
UPDATE_HEIGHT_DATE	Y DATE		
The year, after year of photography, that an update or revision has occurred to the height of the leading tree species in the layer of the polygon. These fields will only be used after the initial inventory has been completed. For Species 1.			
VOL_PER_HA_SPP1_125	Y NUMBER	7,1	
This is the Net volume per hectare of the leading species determined by percent basal area of the tree layer at the 12.5 cm utilization level. Net volume per hectare is determined as gross volume less decay, waste, and breakage. Depending on the magnitude of the species' decay, waste and breakage, the net volume for the leading species may be lower than volume for other species in the stand. Net volumes are calculated for Rank 1 layers only, Typid 1 through 3.			

Entity Name: VEG COMP LAYER (cont'd)	<i>Short Name:</i>	VEG_VCL
VOL_PER_HA_SPP1_175 Y NUMBER This is the Net volume per hectare of the leading species determined by percent basal area of the tree layer at the 17.5 cm utilization level. Net volume per hectare is determined as gross volume less decay, waste, and breakage. Depending on the magnitude of the species' decay, waste and breakage, the net volume for the leading species may be lower than volume for other species in the stand. Net volumes are calculated for Rank 1 layers only, Typid 1 through 3.	7,1	
VOL_PER_HA_SPP1_225 Y NUMBER This is the Net volume per hectare of the leading species determined by percent basal area of the tree layer at the 22.5 cm utilization level. Net volume per hectare is determined as gross volume less decay, waste, and breakage. Depending on the magnitude of the species' decay, waste and breakage, the net volume for the leading species may be lower than volume for other species in the stand. Net volumes are calculated for Rank 1 layers only, Typid 1 through 3.	7,1	
VOL_PER_HA_SPP2_125 Y NUMBER This is the Net volume per hectare of the second species determined by percent basal area of the tree layer at the 12.5 cm utilization level. Net volume per hectare is determined as gross volume less decay, waste, and breakage. Depending on the magnitude of the species' decay, waste and breakage, the net volume for the leading species may be lower than volume for other species in the stand. Net volumes are calculated for Rank 1 layers only, Typid 1 through 3.	7,1	
VOL_PER_HA_SPP2_175 Y NUMBER This is the Net volume per hectare of the second species determined by percent basal area of the tree layer at the 17.5 cm utilization level. Net volume per hectare is determined as gross volume less decay, waste, and breakage. Depending on the magnitude of the species' decay, waste and breakage, the net volume for the leading species may be lower than volume for other species in the stand. Net volumes are calculated for Rank 1 layers only, Typid 1 through 3.	7,1	
VOL_PER_HA_SPP2_225 Y NUMBER This is the Net volume per hectare of the second species determined by percent basal area of the tree layer at the 22.5 cm utilization level. Net volume per hectare is determined as gross volume less decay, waste, and breakage. Depending on the magnitude of the species' decay, waste and breakage, the net volume for the leading species may be lower than volume for other species in the stand. Net volumes are calculated for Rank 1 layers only, Typid 1 through 3.	7,1	
VOL_PER_HA_SPP3_125 Y NUMBER This is the Net volume per hectare of the third species determined by percent basal area of the tree layer at the 12.5 cm utilization level. Net volume per hectare is determined as gross volume less decay, waste, and breakage. Depending on the magnitude of the species' decay, waste and breakage, the net volume for the leading species may be lower than volume for other species in the stand. Net volumes are calculated for Rank 1 layers only, Typid 1 through 3.	7,1	
VOL_PER_HA_SPP3_175 Y NUMBER This is the Net volume per hectare of the third species determined by percent basal area of the tree layer at the 17.5 cm utilization level. Net volume per hectare is determined as gross volume less decay, waste, and breakage. Depending on the magnitude of the species' decay, waste and breakage, the net volume for the leading species may be lower than volume for other species in the stand. Net volumes are calculated for Rank 1 layers only, Typid 1 through 3.	7,1	
VOL_PER_HA_SPP3_225 Y NUMBER This is the Net volume per hectare of the third species determined by percent basal area of the tree layer at the 22.5 cm utilization level. Net volume per hectare is determined as gross volume less decay, waste, and breakage. Depending on the magnitude of the species' decay, waste and breakage, the net volume for the leading species may be lower than volume for other species in the stand. Net volumes are calculated for Rank 1 layers only, Typid 1 through 3.	7,1	
VOL_PER_HA_SPP4_125 Y NUMBER	7,1	

Entity Name: VEG COMP LAYER (cont'd)	<i>Short Name:</i>	VEG_VCL
<p>This is the Net volume per hectare of the fourth species determined by percent basal area of the tree layer at the 12.5 cm utilization level. Net volume per hectare is determined as gross volume less decay, waste, and breakage. Depending on the magnitude of the species' decay, waste and breakage, the net volume for the leading species may be lower than volume for other species in the stand. Net volumes are calculated for Rank 1 layers only, Typid 1 through 3.</p>		
VOL_PER_HA_SPP4_175	Y NUMBER	7,1
<p>This is the Net volume per hectare of the fourth species determined by percent basal area of the tree layer at the 17.5 cm utilization level. Net volume per hectare is determined as gross volume less decay, waste, and breakage. Depending on the magnitude of the species' decay, waste and breakage, the net volume for the leading species may be lower than volume for other species in the stand. Net volumes are calculated for Rank 1 layers only, Typid 1 through 3.</p>		
VOL_PER_HA_SPP4_225	Y NUMBER	7,1
<p>This is the Net volume per hectare of the fourth species determined by percent basal area of the tree layer at the 22.5 cm utilization level. Net volume per hectare is determined as gross volume less decay, waste, and breakage. Depending on the magnitude of the species' decay, waste and breakage, the net volume for the leading species may be lower than volume for other species in the stand. Net volumes are calculated for Rank 1 layers only, Typid 1 through 3.</p>		
VOL_PER_HA_SPP5_125	Y NUMBER	7,1
<p>This is the Net volume per hectare of the fifth species determined by percent basal area of the tree layer at the 12.5 cm utilization level. Net volume per hectare is determined as gross volume less decay, waste, and breakage. Depending on the magnitude of the species' decay, waste and breakage, the net volume for the leading species may be lower than volume for other species in the stand. Net volumes are calculated for Rank 1 layers only, Typid 1 through 3.</p>		
VOL_PER_HA_SPP5_175	Y NUMBER	7,1
<p>This is the Net volume per hectare of the fifth species determined by percent basal area of the tree layer at the 17.5 cm utilization level. Net volume per hectare is determined as gross volume less decay, waste, and breakage. Depending on the magnitude of the species' decay, waste and breakage, the net volume for the leading species may be lower than volume for other species in the stand. Net volumes are calculated for Rank 1 layers only, Typid 1 through 3.</p>		
VOL_PER_HA_SPP5_225	Y NUMBER	7,1
<p>This is the Net volume per hectare of the fifth species determined by percent basal area of the tree layer at the 22.5 cm utilization level. Net volume per hectare is determined as gross volume less decay, waste, and breakage. Depending on the magnitude of the species' decay, waste and breakage, the net volume for the leading species may be lower than volume for other species in the stand. Net volumes are calculated for Rank 1 layers only, Typid 1 through 3.</p>		
VOL_PER_HA_SPP6_125	Y NUMBER	7,1
<p>This is the Net volume per hectare of the sixth species determined by percent basal area of the tree layer at the 12.5 cm utilization level. Net volume per hectare is determined as gross volume less decay, waste, and breakage. Depending on the magnitude of the species' decay, waste and breakage, the net volume for the leading species may be lower than volume for other species in the stand. Net volumes are calculated for Rank 1 layers only, Typid 1 through 3.</p>		
VOL_PER_HA_SPP6_175	Y NUMBER	7,1
<p>This is the Net volume per hectare of the sixth species determined by percent basal area of the tree layer at the 17.5 cm utilization level. Net volume per hectare is determined as gross volume less decay, waste, and breakage. Depending on the magnitude of the species' decay, waste and breakage, the net volume for the leading species may be lower than volume for other species in the stand. Net volumes are calculated for Rank 1 layers only, Typid 1 through 3.</p>		
VOL_PER_HA_SPP6_225	Y NUMBER	7,1
<p>This is the Net volume per hectare of the sixth species determined by percent basal area of</p>		

Entity Name:	VEG COMP LAYER (cont'd)	<i>Short Name:</i>	VEG_VCL
---------------------	-------------------------	--------------------	---------

the tree layer at the 22.5 cm utilization level. Net volume per hectare is determined as gross volume less decay, waste, and breakage. Depending on the magnitude of the species' decay, waste and breakage, the net volume for the leading species may be lower than volume for other species in the stand. Net volumes are calculated for Rank 1 layers only, Typid 1 through 3.

ORG_UNIT_NO	N	NUMBER	10,0
-------------	---	--------	------

Number from Org Unit code table representing the organization that collected the data.

ORG_UNIT_CODE	N	VARCHAR2	18
---------------	---	----------	----

Identifies any office within the ministry. First character identifies Exec, HQ branch, Region, or District. Next two chars identify the office name; next two the section (HQ Branch) or program (Region or District); last char identifies the subsection.

** = Attributes in primary unique identifier.*

Relationships:

Each Occurrence Of This Entity:

MUST BE has feature one and only one VEG COMP POLY

** = Relationships in primary unique identifier.*

Unique Identifiers:

VEG_VCL_PK	Primary	Y
------------	---------	---

FEATURE_ID
LAYER_ID

Entity Name: VEG COMP POLY**Short Name:** VEG_VCP**Plural:** VEG COMP POLY**Init. Volume:** 3800000 **Avg. Volume:** 4000000 **Max. Volume:** 4200000 **Annual Growth Rate:** 5%**Description:**

This is a denormalized summary table combining fields from the following tables:

VEG_VEGETATION_COVER_POLYGON, VEG_DATA_SET_VERSION, VEG_LABEL, VEGETATIVE_COVER, RESOURCE_INVENTORY_HISTORY, RSLT_OPENING, NON_VEGETATIVE_COVER, LAND_COVER_COMPONENT, CORP_ORG_UNIT. This table contains a static cut of the VRI data projected to current year and will be updated annually. It is intended for strategic level resource analysis using the current GIS tools.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* FEATURE_ID		N	VARCHAR2	32
Provincially unique identifier for an instance of a spatial feature.				
OBJECT_VERSION_SKEY		N	NUMBER	28,0
A unique identifier for the object instance				
MAP_ID		N	VARCHAR2	7
Identifies the Forest Cover Map corresponding to the FIP file. It is the British Columbia Geographic System's (BCGS) Key Reference Number of the Forest Cover Map. The mapsheet most commonly used is the 6' X 12' BCGS mapsheet.				
POLYGON_ID		N	NUMBER	6,0
The polygon number is a reference number (non unique) assigned to each Vegetated or Non-Vegetated polygon after it is delineated. The polygon number provides a link between the graphic and descriptive files. The business assigned unique identifier for a polygon. Typically this has been uniquely assigned within a BCGS 6 X 12 Mapsheet.				
OPENING_IND		Y	VARCHAR2	1
Indicates whether or not the polygon represents a silviculture opening.				
OPENING_SOURCE		Y	VARCHAR2	5
Defines whether the opening came from ISIS or MLSIS. This field is not populated in the current data model.				
OPENING_NUMBER		Y	VARCHAR2	4
A unique number assigned to each opening in the forest caused by a disturbance (e.g. fire, logging, etc.) for which there will be management activities.				
FEATURE_CLASS_SKEY		N	NUMBER	38,0
Unique identifier for a feature class.				
INVENTORY_STANDARD_CD		Y	VARCHAR2	1
Code indicating under which inventory standard the data was collected. Values are: "V:" for Vegetation Resources Inventory (VRI), "F" for Forest Inventory Planning (FIP) and "I" for Incomplete (when a full set of VRI attributes is not collected).				
POLYGON_AREA		Y	NUMBER	10,3
The area of a polygon; usually derived from geographic information system processing software. The total area, in hectares, of the forest cover polygon. The total area should be equal to the sum of the areas for all resultants in that polygon.				
NON_PRODUCTIVE_DESCRIPTOR_CD		Y	VARCHAR2	5
A unique code that references the classes or type of non-productive areas or land that is incapable of supporting commercial forests. This is a FIP classification based attribute only, and is retained for the purposes of business transition from FIP to Vegetation Inventory. There is no expectation that this attribute would be updated or created under Vegetation Inventory classification practise.				
NON_PRODUCTIVE_CD		Y	NUMBER	2,0
A unique numeric code that references the classes or type of non-productive areas. This is a FIP classification based attribute only, and is retained for the purposes of business transition from FIP to Vegetation Inventory. There is no expectation that this attribute would be updated or created under Vegetation Inventory classification practise.				

Entity Name: VEG COMP POLY (cont'd)		Short Name:	VEG_VCP
INPUT_DATE	Y DATE		
The date the forest cover information was entered into the Provincial Data Base.			
COAST_INTERIOR_CD	Y VARCHAR2	1	
A code indicating that the stand is located in the Coast or Interior Region of the Province. The Coast Region is defined as the mainland west of the Cascade and Coast Mountains, including the off-shore islands. Forest Inventory Zones (FIZ) A to C are included in the Coast region. The Interior Region is defined as the mainland east of the Cascade and Coast Mountains. Forest Inventory Zones (FIZ) D to L are included in the Interior Region.			
COAST_INTERIOR_DATA_SRC_CD	Y VARCHAR2	3	
The source of the assigned Coast Interior Cd for the polygon. This is not populated in the current Oracle Data model.			
SURFACE_EXPRESSION	Y VARCHAR2	1	
The form of surficial material apparent on the medium scale photography. A simplified attribution is used owing to the likelihood that the trees will mask suficial features. Decription Source: p. 3-5, Photo Interpretation Procedures, Phase 1, May 14, 1996. Data Value Source: Table 3-2, from Description Source			
MODIFYING_PROCESS	Y VARCHAR2	1	
A natural mechanism of weathering, erosion and soil material deposition that result in the modification of surficial materials and landforms. Used for terrain classification, site classification, soil condition and identification of potential hazards such as avalanches, slope instability and flooding. Data Definition Source: p.3-7, Photo Interpretation Procedures, Phase 1, May 14, 1996 Data Value Source: Table 3-3, from Data Definition Source.			
SITE_POSITION_MESO	Y VARCHAR2	1	
A code denoting the relative position of the sampling site within a catchment area with the intent to be consistent within the scale of topography affecting surface water flow. The vertical difference is usually between 3 and 300m, and the surface area generally exceeds 0.5 has in size. Also known as slope position or meso site position. Definition Source: "Describing Ecosystems in the Field", MOE Manual 11, Province of B.C. 1990, p. 31.			
ALPINE_DESIGNATION	Y VARCHAR2	1	
The location of the land unit with respect to location and elevation. An interpretation is applied as to whether the tree unit is above or below the tree line, that is, the upper elevation limit of continuous tree, or potential tree if cut-over, cover. If the land unit is above the the elevation line, a code of 'A' is applied, otherwise 'N', the default. Description Source: p. 3-11, Photo Interpretation Procedures, Phase 1, May 14, 1996. Data Value Source: Table 3-5, from Description Source			
SOIL_NUTRIENT_REGIME	Y VARCHAR2	1	
A code to denote, on a relative scale, the available nutrient supply for plant growth. The soil's nutrient regime (trophotope) integrates many environmental and biotic parameters which, in combination, determine the actual amounts of available nutrients. Definition Source: Reference: "Describing Ecosystems in the Field", MOE Manual 11, Province of B.C. 1990, p37-40 Soil Nutrient Regime (SNR) refers to the amount of essential soil nutrients, particularly nitrogen, available to vascular plants over a period of several years. SNR classes include A (very poor), B (poor), C (medium), D (rich), E (very rich) and F (ultra rich, saline).			
ECOSYS_CLASS_DATA_SRC_CD	Y NUMBER	2,0	
The source of the data used in the interpretation of the ecological attributes (Surface expression, modifying process, site position meso, alpine designation, and soil nutrient regime) that describe the polygon.			
BCLCS_LEVEL_1	Y VARCHAR2	2	
The code for the land cover classification. The codes are approved by the Resource Inventory Committee, RIC. Level 1 identifies a Vegetated or Non-vegetated state, with further dichotomous refinement to Level 5, which identifies the Vegetation Density Class related to Vegetated land, or specific Non-vegetated state cover such as beaches, mudflats etc.			
BCLCS_LEVEL_2	Y VARCHAR2	2	

Entity Name: VEG COMP POLY (cont'd)		Short Name:	VEG_VCP
The second level of the BC land cover classification scheme classifies the polygon as to the land cover type: treed or non-treed for vegetated polygons; land or water for non-vegetated polygons.			
BCLCS_LEVEL_3	Y VARCHAR2	2	
The location of the polygon relative to elevation and drainage, and is described as either alpine, wetland, or upland. In rare cases, the polygon may be alpine wetland.			
BCLCS_LEVEL_4	Y VARCHAR2	2	
Classifies the vegetation types and Non-Vegetated cover types (as described by the presence of distinct types upon the land base within the polygon).			
BCLCS_LEVEL_5	Y VARCHAR2	2	
Classifies the vegetation density classes and Non-Vegetated categories.			
PRI_UTIL_LEVEL_CD	Y NUMBER	2,0	
The utilization level defines the stump height and top diameter, inside bark, between which the volume of individual trees are determined. The primary level of utilization refers to the 'highest' or 'closest' use of the individual trees in determining stand volumes for Timber Supply Analyses. For example, volumes per hectare in the Interior Region, include trees with a stump inside bark diameter of 12.5 cm or greater (utilization code '04'). Attributes that are used to determine volumes by different utilization levels include: stump height, stump inside bark diameter, top inside bark diameter, main stem taper.			
SEC_UTIL_LEVEL_CD	Y NUMBER	2,0	
The utilization level defines the stump height and top diameter, inside bark, between which the volume of individual trees are determined. The secondary level of utilization refers to the medium' use of the individual trees in determining stand volumes for Timber Supply Analyses. For example, volumes per hectare in the Interior Region, include trees with a stump inside bark diameter of 17.5 cm or greater (utilization code '08'). Attributes that are used to determine volumes by different utilization levels include: stump height, stump inside bark diameter, top inside bark diameter, main stem taper.			
INTERPRETER	Y VARCHAR2	30	
The name of the person who provided the estimates for the data associated with each polygon.			
INTERPRETATION_DATE	Y DATE		
The date on which the data was photo interpreted.			
PROJECT	Y VARCHAR2	30	
The business assigned name of the project. The name typically reflects a Timber Supply Area, an initiating Agency, or a land area.			
DATE_OF_PHOTOGRAPHY	Y DATE		
The reference date of the photo from which data was interpreted .			
SPECIAL_CRUISE_NUMBER	Y NUMBER	4,0	
The numeric code of the Public Sustained Yield Unit(s) (PSYU) that fall within the forest cover polygon. PSYUs are areas of land, usually a natural topographic unit determined by drainage areas. Includes PSYUs, Tree Farm Licences (TFL), Tree Farms (TF), Major Parks and Ecological Reserves, Woodlot licences, and miscellaneous areas.			
SPECIAL_CRUISE_NUMBER_CD	Y VARCHAR2	1	
The numbers of the Public Sustained Yield Unit (PSYU) Block(s) that fall within the forest cover polygon. PSYU Blocks are subdivisions of a PSYU, and indicate the presence of a sub-unit survey (i.e. 1:10,000 scale inventory).			
INVENTORY_REGION	Y NUMBER	2,0	
The Inventory Region(s) that fall within the forest cover polygon. Inventory Regions are an administrative and planning level boundary used to subdivide the Province into 88 units. Inventory Region is also part of the reference key for identifying the geographic location of all Inventory Branch samples. Inventory Region, along with Inventory Compartment and Compartment Letter, form the key to identifying the Inventory samples.			
COMPARTMENT	Y NUMBER	3,0	
The Inventory Compartment(s) that fall within the forest cover polygon. Inventory			

Entity Name: VEG COMP POLY (cont'd)	<i>Short Name:</i>	VEG_VCP
<p>Compartments are a geographic subdivision of an Inventory Region, usually defining a watershed or part thereof. Inventory Compartment is also part of the reference key for identifying the geographic location of all Inventory Branch samples. Inventory Compartment, along with Compartment Letter and Inventory Region form the key to identifying Inventory samples.</p>		
COMPARTMENT_LETTER	Y VARCHAR2	1
<p>The Compartment Letter(s) that fall within the forest cover polygon. Compartment Letter is a geographic subdivision of an Inventory Compartment. Compartment Letter only applies to some Inventory Compartments (e.g. only in Inventory Regions 1, 3, 5, 6, 7, 9, 10, 11, 56). Compartment Letter is also part of the reference key for identifying the geographic location of all Inventory Branch samples. Compartment Letter, along with Inventory Compartment and Inventory Region form the key to identifying Inventory samples.</p>		
FIZ_CD	Y VARCHAR2	1
<p>The Forest Inventory Zone(s) (FIZ) that fall within the forest cover polygon. FIZ zones were developed to provide a broadly based ecological classification of the forestland in British Columbia. FIZ zones closely follow the early Biogeoclimatic zones developed by Dr. Krajina. The province of British Columbia is split into 12 FIZ zones.</p>		
MD_DATA_SOURCE_CODE	Y VARCHAR2	10
<p>The data source for this feature (e.g. GPS).</p>		
MD_CAPTURE_METHOD_CD	Y VARCHAR2	10
<p>A code to identify the method of capture for the feature. d.g. DIGI - Digitized.</p>		
MD_DATA_ACCURACY_CD	Y VARCHAR2	3
<p>The degree of accuracy at which this feature was captured.</p>		
MD_OBSERVATION_DATE	Y DATE	
<p>The date of photography or survey. It is used to indicate that a photo that was used to capture the data could be 5 years old.</p>		
MD_RETIREMENT_DATE	Y DATE	
<p>The date the feature is deleted from the spatial file.</p>		
MD_COMMENT	Y VARCHAR2	255
<p>A comment regarding the feature.</p>		
ATTRIBUTION_BASE_DATE	Y DATE	
<p>The date that the information about this polygon is considered to be based on. This is not currently populated in the LRDW.</p>		
PROJECTED_DATE	Y DATE	
<p>The date to which time dependent stand information is projected. Attributes that are projected to a future date include: - Age, - Age Class, - Height, - Height Class, - Type Identity, - Stocking Class, etc.</p>		
ADJUSTMENT_AREA_ID	Y NUMBER	9,0
<p>A unique ID representing an adjustment area.</p>		
SHRUB_HEIGHT	Y NUMBER	4,1
<p>The average height of the shrubs contained in the polygon as interpreted from medium scale photography. Note that this attribute only applies to the Shrub component. Definition Source: p. 7-2, PIP</p>		
SHRUB_CROWN_CLOSURE	Y NUMBER	3,0
<p>Shrub crown closure is the percentage of ground area covered by the vertically projected crowns of the shrub cover visible to the photo interpreter. Shrub crown closure is expressed as a percentage of the entire polygon.</p>		
SHRUB_COVER_PATTERN	Y NUMBER	2,0
<p>Shrub cover pattern is a code that describes the spatial distribution of the shrubs within the polygon. Shrub cover pattern is used to describe the shrub layer spatial distribution. Examples include clumps of shrubs on rocky patches or individual shrubs or solid, continuous cover</p>		
HERB_COVER_TYPE	Y VARCHAR2	2

Entity Name: VEG COMP POLY (cont'd)	<i>Short Name:</i>	VEG_VCP
<p>This set of attributes describes the portion of herb cover that is no obscured by the vertical projection of the crowns of either trees or shrubs. Herbs are defined as non-woody (vascular) plants, including graminoids (sedges, rushes, grasses), forbs (ferns, club mosses, and horsetails) and some low, woody species and intermediate life forms.</p>		
HERB_COVER_PATTERN	Y NUMBER	2,0
<p>Herb cover pattern is a code that describes the spatial distribution of the herbaceous species within the polygon. Herb cover pattern is used to describe the herb layer spatial distribution. Examples include clumps of herbaceous species on rock outcrops, scattered patches or individual herbs or solid, continuous herbaceous cover.</p>		
HERB_COVER_PCT	Y NUMBER	3,0
<p>Herb cover percent is the percentage of ground area covered by herbaceous cover visible to the photo interpreter. Herb cover percent is analogous to tree and shrub crown closures and is expressed as a percentage of the entire polygon.</p>		
BRYOID_COVER_PCT	Y NUMBER	3,0
<p>The percent cover of Bryoids: includes bryophytes (mosses, liverworts, hornworts) and non-crustose lichens.</p>		
NON_VEG_COVER_PATTERN_1	Y NUMBER	2,0
<p>Non-vegetated cover pattern_1 describes the spatial distribution of the most prevalent non-vegetated cover type based on percent area covered within the polygon. Definition Source: pp.7-4 (fig. 7-2), 8-5 (fig. 8-2), same as pp. 10-7, fig. 10-2, PIP</p>		
NON_VEG_COVER_PCT_1	Y NUMBER	3,0
<p>The area the predominate non-vegetated portion covers expressed as a percentage of the entire polygons area. Definition Source: p. 10-5, PIP</p>		
NON_VEG_COVER_TYPE_1	Y VARCHAR2	2
<p>Non-vegetated cover type_1 is the designation for the predominate observable non-vegetated land cover within the polygon.</p>		
NON_VEG_COVER_PATTERN_2	Y NUMBER	2,0
<p>Non-vegetated cover pattern_2 describes the spatial distribution of the second most prevalent non-vegetated cover type based on percent area covered within the polygon. Definition Source: pp. 7-4 (fig. 7-2), 8-5 (fig. 8-2), same as pp. 10-7, fig. 10-2, PIP</p>		
NON_VEG_COVER_PCT_2	Y NUMBER	3,0
<p>The area the second most prevalent non-vegetated portion covers expressed as a percentage of the entire polygons area. Definition Source: p. 10-5, PIP</p>		
NON_VEG_COVER_TYPE_2	Y VARCHAR2	2
<p>Non-vegetated cover type_2 is the designation for the second most prevalent observable non-vegetated land cover within the polygon.</p>		
NON_VEG_COVER_PATTERN_3	Y NUMBER	2,0
<p>Non-vegetated cover type_3 is the designation for the third most prevalent observable non-vegetated land cover within the polygon.</p>		
NON_VEG_COVER_PCT_3	Y NUMBER	3,0
<p>The area the third most prevalent non-vegetated portion covers expressed as a percentage of the entire polygons area. Definition Source: p. 10-5, PIP</p>		
NON_VEG_COVER_TYPE_3	Y VARCHAR2	2
<p>Non-vegetated cover type_3 is the designation for the third most prevalent observable non-vegetated land cover within the polygon.</p>		
LAND_COVER_CLASS_CD_1	Y VARCHAR2	2
<p>The Land Cover Classification Code_1 describes the predominate land cover type by percent area occupied within the polygon that contribute to the overall polygon description, but may be too small to be spatially identified. The sub-division of a polygon by a quantified Land Cover Component, allowing non-spatial resolution for modeling of wildlife habitat capability.</p>		
EST_COVERAGE_PCT_1	Y NUMBER	3,0
<p>The amount the polygon occupied by the predominate Land Cover Component. The sub-</p>		

Entity Name:	VEG COMP POLY (cont'd)	Short Name:	VEG_VCP
	division of a polygon by a quantified Land Cover Component allows a higher degree spatial resolution for modelling wildlife habitat capability. Generally, sizes under 10% would not be estimated. Definition Source: p. 4-6, PIP		
SOIL_MOISTURE_REGIME_1	Y NUMBER	2,0	
	The average amount of soil water annually available for evapotranspiration by vascular plants averaged over many years within the predominate cover type. Soil Moisture Regime is an interpretative attribute for estimation of site potential and site series classification. Definition Source: p. 4-7, PIP		
LAND_COVER_CLASS_CD_2	Y VARCHAR2	2	
	The Land Cover Classification Code_2 describes the second most dominate land cover type by percent area occupied within the polygon that contribute to the overall polygon description, but may be too small to be spatially identified. The sub-division of a polygon by a quantified Land Cover Component, allowing non-spatial resolution for modelling of wildlife habitat capability.		
EST_COVERAGE_PCT_2	Y NUMBER	3,0	
	The amount the polygon occupied by the second most dominate Land Cover Component. The sub-division of a polygon by a quantified Land Cover Component allows a higher degree spatial resolution for modelling wildlife habitat capability. Generally, sizes under 10% would not be estimated. Definition Source: p. 4-6, PIP		
SOIL_MOISTURE_REGIME_2	Y NUMBER	2,0	
	The average amount of soil water annually available for evapotranspiration by vascular plants averaged over many years within the second most dominate cover type. Soil Moisture Regime is an interpretative attribute for estimation of site potential and site series classification. Definition Source: p. 4-7, PIP		
LAND_COVER_CLASS_CD_3	Y VARCHAR2	2	
	The Land Cover Classification Code_3 describes the third most dominate land cover type by percent area occupied within the polygon that contribute to the overall polygon description, but may be too small to be spatially identified. The sub-division of a polygon by a quantified Land Cover Component, allowing non-spatial resolution for modelling of wildlife habitat capability.		
EST_COVERAGE_PCT_3	Y NUMBER	3,0	
	The amount the polygon occupied by the third most dominate Land Cover Component. The sub-division of a polygon by a quantified Land Cover Component allows a higher degree spatial resolution for modelling wildlife habitat capability. Generally, sizes under 10% would not be estimated. Definition Source: p. 4-6, PIP		
SOIL_MOISTURE_REGIME_3	Y NUMBER	2,0	
	The average amount of soil water annually available for evapotranspiration by vascular plants averaged over many years within the second most dominate cover type. Soil Moisture Regime is an interpretative attribute for estimation of site potential and site series classification. Definition Source: p. 4-7, PIP		
AVAIL_LABEL_HEIGHT	Y NUMBER	38,10	
	The available height for a label, in meters for a 1:15,000 map presentation. This is derived during the label generation process to calculate if the VRI label will fit within a polygon shape or be written the map side.		
AVAIL_LABEL_WIDTH	Y NUMBER	38,10	
	The available width for a label, in meters for a 1:15,000 map presentation. This is derived during the label generation process to calculate if the VRI label will fit within a polygon shape or be written the map side.		
FULL_LABEL	N VARCHAR2	500	
	The full Vegetation Map label. It contains the polygon id, Opening number, species composition, projected age, projected height, site index and crown closure, and indicator of shrub, herb, bryoid, or non vegetative components, and the historic disturbance and forest management activities. It is at most 8 lines. Back slashes represent carriage returns.		
LABEL_CENTRE_X	Y NUMBER	38,10	
	The x co-ordinate of the suggested centre of the label.		

Entity Name:	VEG COMP POLY (cont'd)	Short Name:	VEG_VCP
LABEL_CENTRE_Y	Y NUMBER	38,10	
The y co-ordinate of the suggested centre of the label.			
LABEL_HEIGHT	Y NUMBER	38,0	
The height of the full label for a 1:15,000 map presentation in meters. It is calculated as 30 times the number of lines in the full label.			
LABEL_WIDTH	Y NUMBER	38,0	
The width of the full label for a 1:15,000 map presentation in meters. It is calculated as 18 times the number of characters in the longest line.			
LINE_1_OPENING_NUMBER	Y VARCHAR2	4	
The MOF District Silviculture opening number to which the polygon applies to.			
LINE_1_OPENING_SYMBOL_CD	Y VARCHAR2	1	
The opening symbol code is represented as one of the following characters: 'x', ' ', or '~'. If the opening number is null, line 1 is not populated, so there is no opening symbol. If the adjoining NTS map number is in the form "num num num char num / char", it is an NTS number, the corresponding opening symbol is a hexagon with an 'N' in it, and is represented here by '~'. If the adjoining NTS map number is in the form "num num num char num num num", it is a BCGS number, the corresponding opening symbol is a hexagon with an 'X' in it, and is represented here by ' '. Otherwise the opening symbol is an empty hexagon, and is represented here by 'x'.			
LINE_2_POLYGON_ID	Y VARCHAR2	10	
The polygon ID for which this is the label. This is followed by /L (a multi-layered stand) or /S (a separate silviculture description is available in the data base).			
LINE_3_TREE_SPECIES	Y VARCHAR2	50	
A list of major species (minor species), ordered by percentage. The species symbols are F (Douglas fir), C (western red cedar), H (hemlock), B (balsam), S (spruce), Sb (black spruce), Yc (yellow cedar), Pw (western white pine), Pa (whitebark pine), Pf (limber pine), Pl (lodgepole pine), Pj (jack pine), Py (yellow pine), L (larch), Ac (cottonwood), D (red alder), Mb (broadleaf maple), E (birch), Al (aspen).			
LINE_4_CLASSES_INDEXES	Y VARCHAR2	12	
Line 4 is made up of 4 numerical characters followed by a hyphen, the site index, a slash, and the estimated site index. The four numerical characters represent projected age class, projected height class, projected stocking class, and crown closure class in that order.			
LINE_5_VEGETATION_COVER	Y VARCHAR2	11	
A listing of the non-vegetated descriptors or the non tree vegetative cover types ordered from most to least common. Possible values in the list are sh (shrub), he (herb), by (bryoid), or the non-vegetative cover codes.			
LINE_6_SITE_PREP_HISTORY	Y VARCHAR2	80	
The site preparation history represented by a list of abbreviations for the techniques used, followed by the years each technique was used. Possible values for the abbreviations are B (broadcast burn) C (chemical), G (grass seeded), H (hand preparation), RB (range management burn), S (spot burn), M (mechanical), MS (mechanical and spot burn), and W (windrow).			
LINE_7_ACTIVITY_HIST_SYMBOL	Y VARCHAR2	1	
A symbol representing what techniques where used in the labelled area. The symbol is a circle with 0 to 4 radius lines. Each line represents a technique applied to the labelled area.If RESOURCE_INVENTORY_HISTORY.SILV_BASE = ST(stand tending) then and draw as circle with a radius line pointing leftIf RESOURCE_INVENTORY_HISTORY.SILV_BASE = SI(regeneration/site preparation) then % draw as circle with a radius line pointing (up/down)If RESOURCE_INVENTORY_HISTORY.SILV_BASE = DI(disturbance) then and draw as circle with a radius line pointing rightIf RESOURCE_INVENTORY_HISTORY.SILV_BASE = PL(regeneration/site preparation) then % draw as circle with a radius line pointing (up/down)If RESOURCE_INVENTORY_HISTORY.SILV_BASE = ST and SI then < draw as combination of the above circles and radius linesIf			

Entity Name: VEG COMP POLY (cont'd)		Short Name:	VEG_VCP
<p>RESOURCE_INVENTORY_HISTORY.SILV_BASE = ST and DI then ` draw as combination of the above circles and radius linesIf RESOURCE_INVENTORY_HISTORY.SILV_BASE = ST and PL then : draw as combination of the above circles and radius linesIf RESOURCE_INVENTORY_HISTORY.SILV_BASE = SI and DI then * draw as combination of the above circles and radius linesIf RESOURCE_INVENTORY_HISTORY.SILV_BASE = SI and PL then X draw as combination of the above circles and radius linesIf RESOURCE_INVENTORY_HISTORY.SILV_BASE = DI and PL then ; draw as combination of the above circles and radius linesIf RESOURCE_INVENTORY_HISTORY.SILV_BASE = ST and PL and DI then ? draw as combination of the above circles and radius linesIf RESOURCE_INVENTORY_HISTORY.SILV_BASE = ST and SI and DI then @ draw as combination of the above circles and radius linesIf RESOURCE_INVENTORY_HISTORY.SILV_BASE = PL and ST and SI then [draw as combination of the above circles and radius linesIf RESOURCE_INVENTORY_HISTORY.SILV_BASE = SI and DI and PL then \ draw as combination of the above circles and radius linesIf RESOURCE_INVENTORY_HISTORY.SILV_BASE = ST and SI and DI and PL then ^ draw as combination of the above circles.</p>			
LINE_7A_STAND_TENDING_HISTORY	Y VARCHAR2		39
<p>The stand tending history represented by a list of abbreviations for the techniques used followed by the years each technique was used. Possible values for the abbreviations are F (fertilization), H (hand and squirt), J (juvenile spacing), M (mistletoe control), P (pruning), R (conifer realize), S (sanitation spacing), T (commercial thinning), W (brushing and weeding).</p>			
LINE_7B_DISTURBANCE_HISTORY	Y VARCHAR2		40
<p>The disturbance history described as a list of abbreviations for the techniques along with the years each technique was employed. Possible values are B (wildfire), BE (escaped burn), BG (ground burn), BR (range burn), BW (wildlife burn), D (disease), F (flooding), I (insect), K (fume kill), L (logging), L% (logged with percentage), R (site rehabilitation), S (slide), and W (wind throw).</p>			
LINE_8_PLANTING_HISTORY	Y VARCHAR2		80
<p>The planting (or regeneration) history described as a list of years during which artificial planting was performed.</p>			
PRINTABLE	N VARCHAR2		1
<p>"Y" means print the label. "N" means do not print the label.</p>			
SMALL_LABEL	N VARCHAR2		100
<p>The two-line (or Format 3) version of the label. This label contains, at most, 2 lines build from the line 1 and 2 attributes. A back slash represents a carriage return.</p>			
VIF_VER_HIST_ID_1	Y NUMBER		38,0
<p>A unique, generated identifier for a RI history record. History has been SKEYed as it may relate to either a Vegetation polygon OR to a Tree Layer within a Vegetation polygon. Given the either or nature of the record an skey is appropriate as the buiness key will have nulls from the Tree Layer primary key when the record is for the entire polygon.</p>			
VIF_VER_HIST_ID_2	Y NUMBER		38,0
<p>A unique, generated identifier for a RI history record. History has been SKEYed as it may relate to either a Vegetation polygon OR to a Tree Layer within a Vegetation polygon. Given the either or nature of the record an skey is appropriate as the buiness key will have nulls from the Tree Layer primary key when the record is for the entire polygon.</p>			
VIF_VER_HIST_ID_3	Y NUMBER		38,0
<p>A unique, generated identifier for a RI history record. History has been SKEYed as it may relate to either a Vegetation polygon OR to a Tree Layer within a Vegetation polygon. Given the either or nature of the record an skey is appropriate as the buiness key will have nulls from the Tree Layer primary key when the record is for the entire polygon.</p>			
OPENING_ID	Y NUMBER		10,0

Entity Name:	VEG COMP POLY (cont'd)	<i>Short Name:</i>	VEG_VCP
---------------------	------------------------	--------------------	---------

System generated value uniquely identifying the opening.		
ORG_UNIT_NO	N NUMBER	10,0
Number from Org Unit code table representing the organization that collected the data.		
ORG_UNIT_CODE	N VARCHAR2	18
Identifies any office within the ministry. First character identifies Exec, HQ branch, Region, or District. Next two chars identify the office name; next two the section (HQ Branch) or program (Region or District); last char identifies the subsection.		
GEOMETRY	Y NUMBER	38,0
A spatial polygon feature used to store the map component of the Vegetation Cover area.		
* = Attributes in primary unique identifier.		

Relationships:

Each Occurrence Of This Entity:

MAY BE feature for one or more VEG COMP LAYER

* = Relationships in primary unique identifier.

Unique Identifiers:

VEG_VCP_VEG_VCP2_UK	Primary	N
OBJECT_VERSION_SKEY		
POLYGON_ID		
VEG_VCP_PK	Primary	Y
FEATURE_ID		

Entity Name:	VEGETATION COVER POLYGON ADJUST			Short Name:	VCPA
Plural:	VEGETATION COVER POLYGON ADJ				
Init. Volume:	3800000	Avg. Volume:	4000000	Max. Volume:	4200000
				Annual Growth Rate:	5%

Description:

Describes a Forest Cover Object that has been successfully integrated from the staging area, by means of the update process. This provides the core attribution associated with the stand, as it was adjusted from the original data. Adjustments may be made in isolation from the original data, or may be a result of changes to the estimated data, which would actually represent a new sample of a stand or plot. As such, adjusted polygons (and attribution) may be present when there are no corresponding estimated polygons. This represents a middle stage in the life cycle of a Forest Cover Object, as they are integrated from the staging area into the estimated and/or adjusted areas.

The structure of the entity has been intentionally made to parallel other entities of similar names in the other components of the system. This was done in order to ease transition of data between the components, as the polygon transitions through its life cycle.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
INPUT DATE	DATE TIME	Y	DATE	
The date the vegetation cover information was entered into the Provincial Data Base.				
VRI DEAD STEMS PER HA	STEM COUNT	Y	NUMBER	4,0
The number of standing dead trees visible to the photo interpreter in the dominant, codominant and high intermediate crown positions in each tree layer. Snag frequency is expressed as stems per hectare for each tree layer. The snag frequency provides a direct estimate of snags per hectare that can be used for wildlife and fire management.				
Note: Dominant trees have well-developed crowns that extend above the general level of the trees around them. Codominant trees have crowns forming the general level of trees around them. High intermediate trees have smaller crowns slightly below but extending into the general level of trees around them.				
SHRUB HEIGHT	HEIGHT - SHRUB	Y	NUMBER	4,1
The average height of the shrubs contained in the polygon as interpreted from medium scale photography.				
SHRUB CROWN CLOSURE	PERCENTAGE 3,0	Y	NUMBER	3,0
Shrub crown closure is the percentage of ground area covered by the vertically projected crowns of the shrub cover visible to the photo interpreter. Shrub crown closure is expressed as a percentage of the entire polygon.				
HERB COVER PCT	PERCENTAGE 3,0	Y	NUMBER	3,0
Herb cover percent is the percentage of ground area covered by herbaceous cover visible to the photo interpreter. Herb cover percent is analogous to tree and shrub crown closures and is expressed as a percentage of the entire polygon.				
BRYOID COVER PCT	PERCENTAGE 3,0	Y	NUMBER	3,0
The percent cover of Bryoids: includes bryophytes (mosses, liverworts, hornworts) and non-crustose lichens.				
STOCKABILITY	STOCKABILITY	Y	NUMBER	4,1
An estimate of the percentage of polygon area that will eventually be stocked by trees. For example, a stockability value of 80% indicates that 20% of the area will never support tree growth.				
YIELD FACTOR	YIELD FACTOR	Y	NUMBER	5,3
An input to FIPSTART or VRISTART, two VDYP7 programs that generates the stand description that is required to project the polygon.				
REFERENCE YEAR	NUMERIC YEAR	Y	NUMBER	4,0
The year of the photo or source survey that was used to generate the VRI attributes.				
ADJUSTED IND	INDICATOR	N	VARCHAR2	1
Indicates the Polygon has been adjusted.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	

Entity Name:	VEGETATION COVER POLYGON ADJUST (cont'd)	Short Name:	VCPA
---------------------	--	--------------------	------

Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				

* = Attributes in primary unique identifier.

Relationships:

Each Occurrence Of This Entity:

- MAY BE adjusts one or more ADJUSTMENT FACTOR ADJUSTED
- MAY BE is adjusted by one or more ADJUSTMENT INPUT ADJUSTED
- MAY BE has alpine designation one and only one ALPINE DESIGNATION CODE
- MAY BE has first BCLCS level one and only one BCLCS LEVEL1 CODE
- MAY BE has second BCLCS level one and only one BCLCS LEVEL2 CODE
- MAY BE has third BCLCS level one and only one BCLCS LEVEL3 CODE
- MAY BE has fourth BCLCS level one and only one BCLCS LEVEL4 CODE
- MAY BE has fifth BCLCS level one and only one BCLCS LEVEL5 CODE
- MAY BE in BEC Zone one and only one BEC ZONE CODE
- MAY BE has herb cover pattern one and only one COVER PATTERN CODE
- MAY BE has shrub pattern one and only one COVER PATTERN CODE
- MAY BE ecosystem class sourced from one and only one DATA SOURCE ECOSYS CLASS CODE
- * MUST BE provides adjustment of one and only one FOREST COVER OBJECT
- MAY BE has herb cover type one and only one HERB COVER TYPE CODE
- MAY BE describes soil makeup through one or more LAND COVER COMPONENT ADJ
- MAY BE summarization described by one and only one LAYER SUMMARIZATION CODE
- MAY BE has modifying process one and only one MODIFYING PROCESS CODE
- MAY BE has non-productive VDYP descriptor one and only one NON PRODUCTIVE CODE
- MAY BE has non-productive descriptor one and only one NON PRODUCTIVE DESCRIPTOR CODE
- MAY BE shows non-veg coverage through one or more NON VEGETATIVE COVER ADJ
- MAY BE adjusts one or more SAMPLES USED ADJUSTED
- MAY BE has site position meso one and only one SITE POSITION MESO CODE
- MAY BE has soil nutrient regime one and only one SOIL NUTRIENT REGIME CODE
- MAY BE part of strata one or more STRATA POLYGON ADJUSTED
- MAY BE has surface expression one and only one SURFACE EXPRESSION CODE
- MAY BE divided vertically into one or more TREE COVER LAYER ADJUSTED
- MAY BE has meta-information one and only one VEGETATION METADATA ADJUSTED
- * = Relationships in primary unique identifier.

Unique Identifiers:

- VCPA PK

Primary

Y
- MUST BE provides adjustment of one and only one FOREST COVER OBJECT

Entity Name:	VEGETATION COVER POLYGON ESTIMA			Short Name:	VCPE
Plural:	VEGETATION COVER POLYGON EST				
Init. Volume:	3800000	Avg. Volume:	4000000	Max. Volume:	4200000
				Annual Growth Rate:	5%

Description:

Describes a Forest Cover Object that has been successfully integrated from the staging area, by means of the update process. This provides the core attribution associated with the stand or plot, as it was collected (estimated) in the field. When an estimated polygon is loaded, an exact copy of the data will be copied (with all related attribution) to the adjusted area. This represents a middle stage in the life cycle of a Forest Cover Object, as they are integrated from the staging area into the estimated and/or adjusted areas.

The structure of the entity has been intentionally made to parallel other entities of similar names in the other components of the system. This was done in order to ease transition of data between the components, as the polygon transitions through its life cycle.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
INPUT DATE	DATE TIME	Y	DATE	
The date the vegetation cover information was entered into the Provincial Data Base.				
VRI DEAD STEMS PER HA	STEM COUNT	Y	NUMBER	4,0
The number of standing dead trees visible to the photo interpreter in the dominant, codominant and high intermediate crown positions in each tree layer. Snag frequency is expressed as stems per hectare for each tree layer. The snag frequency provides a direct estimate of snags per hectare that can be used for wildlife and fire management.				
Note: Dominant trees have well-developed crowns that extend above the general level of the trees around them. Codominant trees have crowns forming the general level of trees around them. High intermediate trees have smaller crowns slightly below but extending into the general level of trees around them.				
SHRUB HEIGHT	HEIGHT - SHRUB	Y	NUMBER	4,1
The average height of the shrubs contained in the polygon as interpreted from medium scale photography.				
SHRUB CROWN CLOSURE	PERCENTAGE 3,0	Y	NUMBER	3,0
Shrub crown closure is the percentage of ground area covered by the vertically projected crowns of the shrub cover visible to the photo interpreter. Shrub crown closure is expressed as a percentage of the entire polygon.				
HERB COVER PCT	PERCENTAGE 3,0	Y	NUMBER	3,0
Herb cover percent is the percentage of ground area covered by herbaceous cover visible to the photo interpreter. Herb cover percent is analogous to tree and shrub crown closures and is expressed as a percentage of the entire polygon.				
BRYOID COVER PCT	PERCENTAGE 3,0	Y	NUMBER	3,0
The percent cover of Bryoids: includes bryophytes (mosses, liverworts, hornworts) and non-crustose lichens.				
REFERENCE YEAR	NUMERIC YEAR	Y	NUMBER	4,0
The year of the photo or source survey that was used to generate the VRI attributes.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				

* = Attributes in primary unique identifier.

Relationships:

Entity Name:	VEGETATION COVER POLYGON ESTIMA (cont'd)	Short Name:	VCPE
--------------	--	-------------	------

Each Occurrence Of This Entity:

- MAY BE has alpine designation one and only one ALPINE DESIGNATION CODE
- MAY BE has first BCLCS level one and only one BCLCS LEVEL1 CODE
- MAY BE has second BCLCS level one and only one BCLCS LEVEL2 CODE
- MAY BE has third BCLCS level one and only one BCLCS LEVEL3 CODE
- MAY BE has fourth BCLCS level one and only one BCLCS LEVEL4 CODE
- MAY BE has fifth BCLCS level one and only one BCLCS LEVEL5 CODE
- MAY BE in bec zone one and only one BEC ZONE CODE
- MAY BE has herb cover pattern one and only one COVER PATTERN CODE
- MAY BE has shrub pattern one and only one COVER PATTERN CODE
- MAY BE ecosystem class sourced from one and only one DATA SOURCE ECOSYS CLASS CODE
- * MUST BE provides estimation of one and only one FOREST COVER OBJECT
- MAY BE has herb cover type one and only one HERB COVER TYPE CODE
- MAY BE describes soil makeup through one or more LAND COVER COMPONENT EST
- MAY BE has modifying process one and only one MODIFYING PROCESS CODE
- MAY BE has non-productive VDYP descriptor one and only one NON PRODUCTIVE CODE
- MAY BE has non-productive descriptor one and only one NON PRODUCTIVE DESCRIPTOR CODE
- MAY BE shows non-veg coverage through one or more NON VEGETATIVE COVER EST
- MAY BE has site position meso one and only one SITE POSITION MESO CODE
- MAY BE has soil nutrient regime one and only one SOIL NUTRIENT REGIME CODE
- MAY BE has surface expression one and only one SURFACE EXPRESSION CODE
- MAY BE divided vertically into one or more TREE COVER LAYER ESTIMATED

* = Relationships in primary unique identifier.

Unique Identifiers:

- VCPE PKPrimary Y
- MUST BE provides estimation of one and only one FOREST COVER OBJECT

Entity Name: VEGETATION COVER POLYGON PROJEC**Short Name:**

VCP

Plural: VEGETATION COVER POLYGON PRJ**Init. Volume:** 3800000**Avg. Volume:** 4000000**Max. Volume:** 4200000**Annual Growth Rate:** 5%**Description:**

Describes a Forest Cover Object that has been projected into the future, by means of the projection process. A projection is always made based on data from the adjustment area and is used to forecast growth of coverage, as represented by the polygon. This represents a late stage in the life cycle of a Forest Cover Object, as they are projected from the adjustment area into the projected area.

The structure of the entity has been intentionally made to parallel other entities of similar names in the other components of the system. This was done in order to ease transition of data between the components, as the polygon transitions through its life cycle.

The projected area does however contain additional attribution that is used by the Labelling Process (also referred to as map notation), which takes fields such as "LINE 1 OPENING NUMBER" and "LABEL HEIGHT" and uses them to render additional information on map images/print outs. These attributes represent reformatted data that is present in other tables, but has been altered for display. Due to the nature of the label size and orientations being calculated from the polygon's geometry, it is necessary to store this information, as not all clients will be able to render and calculate the information on their own.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
INPUT DATE	DATE TIME	Y	DATE	
The date the vegetation cover information was entered into the Provincial Data Base.				
VRI DEAD STEMS PER HA	STEM COUNT	Y	NUMBER	4,0
The number of standing dead trees visible to the photo interpreter in the dominant, codominant and high intermediate crown positions in each tree layer. Snag frequency is expressed as stems per hectare for each tree layer. The snag frequency provides a direct estimate of snags per hectare that can be used for wildlife and fire management.				
Note: Dominant trees have well-developed crowns that extend above the general level of the trees around them. Codominant trees have crowns forming the general level of trees around them. High intermediate trees have smaller crowns slightly below but extending into the general level of trees around them.				
SHRUB HEIGHT	HEIGHT - SHRUB	Y	NUMBER	4,1
The average height of the shrubs contained in the polygon as interpreted from medium scale photography.				
SHRUB CROWN CLOSURE	PERCENTAGE 3,0	Y	NUMBER	3,0
Shrub crown closure is the percentage of ground area covered by the vertically projected crowns of the shrub cover visible to the photo interpreter. Shrub crown closure is expressed as a percentage of the entire polygon.				
HERB COVER PCT	PERCENTAGE 3,0	Y	NUMBER	3,0
Herb cover percent is the percentage of ground area covered by herbaceous cover visible to the photo interpreter. Herb cover percent is analogous to tree and shrub crown closures and is expressed as a percentage of the entire polygon.				
BRYOID COVER PCT	PERCENTAGE 3,0	Y	NUMBER	3,0
The percent cover of Bryoids: includes bryophytes (mosses, liverworts, hornworts) and non-crustose lichens.				
STOCKABILITY	STOCKABILITY	Y	NUMBER	4,1
An estimate of the percentage of polygon area that will eventually be stocked by trees. For example, a stockability value of 80% indicates that 20% of the area will never support tree growth.				
YIELD FACTOR	YIELD FACTOR	Y	NUMBER	5,3
An input to FIPSTART or VRISTART, two VDYP7 programs that generate the stand description that is required to project the polygon.				
REFERENCE YEAR	NUMERIC YEAR	Y	NUMBER	4,0
The year of the photo or source survey that was used to generate the VRI attributes.				

Entity Name: VEGETATION COVER POLYGON PROJEC (cont'd)			Short Name:	VCPP
ADJUSTED IND	INDICATOR	N	VARCHAR2	1
Indicates the Polygon has been adjusted.				
LINE 1 OPENING NUMBER	POLY LABEL LINE	Y	VARCHAR2	100
The opening number to which this label applies.				
LINE 1 OPENING SYMBOL CODE	POLY LABEL LINE	Y	VARCHAR2	100
The value here must be mapped to the drawn hexagon.				
The opening symbol code is represented as one of the following characters: 'x', ' ', or '~'. If the opening number is null, line 1 is not populated, so there is no opening symbol. If the adjoining NTS map number is in the form "num num num char num / char", it is an NTS number, the corresponding opening symbol is a hexagon with an 'N' in it, and is represented here by '~'. If the adjoining NTS map number is in the form "num num num char num num num", it is a BCGS number, the corresponding opening symbol is a hexagon with an 'X' in it, and is represented here by ' '. Otherwise the opening symbol is an empty hexagon, and is represented here by 'x'.				
LINE 2 POLYGON ID	POLY LABEL LINE	Y	VARCHAR2	100
The polygon ID for which this is the label. This is followed by /L (a multi-layered stand) or /S (a separate silviculture description is available in the data base).				
LINE 3 TREE SPECIES	POLY LABEL LINE	Y	VARCHAR2	100
A list of major species (minor species), ordered by percentage. The species symbols are F (Douglas fir), C (western red cedar), H (hemlock), B (balsam), S (spruce), Sb (black spruce), Yc (yellow cedar), Pw (western white pine), Pa (whitebark pine), Pf (limber pine), Pl (lodgepole pine), Pj (jack pine), Py (yellow pine), L (larch), Ac (cottonwood), D (red alder), Mb (broadleaf maple), E (birch), Al (aspen).				
LINE 4 CLASSES INDEXES	POLY LABEL LINE	Y	VARCHAR2	100
Line 4 is made up of 4 numerical characters followed by a hyphen, the site index, a slash, and the estimated site index. The four numerical characters represent age class, height class, stocking class, and crown closure class in that order.				
LINE 5 VEGETATION COVER	POLY LABEL LINE	Y	VARCHAR2	100
The non-productive descriptor (npd) or a list of what covers the ground ordered from most to least common. Possible values in the list are sh (shrub), he (herb), by (bryoid), or ri (non-vegetative cover), ordered by pct cover.				
LINE 6 SITE PREP HISTORY	POLY LABEL LINE	Y	VARCHAR2	100
The site preparation history represented by a list of abbreviations for the techniques used, followed by the years each technique was used. Possible values for the abbreviations are B (broadcast burn) C (chemical), G (grass seeded), H (hand preparation), RB (range management burn), S (spot burn), M (mechanical), MS (mechanical and spot burn), and W (windrow). Silviculture techniques with dates where silviculture base = SI.				
LINE 7A STAND TENDING HISTORY	POLY LABEL LINE	Y	VARCHAR2	100
The stand tending history represented by a list of abbreviations for the techniques used followed by the years each technique was used. Possible values for the abbreviations are F (fertilization), H (hand and squirt), J (juvenile spacing), M (mistletoe control), P (pruning), R (conifer realize), S (sanitation spacing), T (commercial thinning), W (brushing and weeding). Silviculture techniques with dates where silviculture base = ST.				
LINE 7 ACTIVITY HIST SYMBOL	POLY LABEL LINE	Y	VARCHAR2	100
A symbol representing what techniques where used in the labelled area. The symbol is a circle with 0 to 4 radius lines. Each line represents a technique applied to the labelled area.If RESOURCE_INVENTORY_HISTORY.SILV_BASE = ST(stand tending) then and draw as circle with a radius line pointing leftIf RESOURCE_INVENTORY_HISTORY.SILV_BASE = SI(regeneration/site preparation) then % draw as circle with a radius line pointing (up/down)If RESOURCE_INVENTORY_HISTORY.SILV_BASE = DI(disturbance) then \$ draw as circle with a radius line pointing rightIf RESOURCE_INVENTORY_HISTORY.SILV_BASE = PL(regeneration/site preparation) then % draw as circle with a radius line pointing (up/down)If RESOURCE_INVENTORY_HISTORY.SILV_BASE = ST and SI then < draw as				

Entity Name: VEGETATION COVER POLYGON PROJEC (cont'd)

Short Name:

VCP

combination of the above circles and radius linesIf
 RESOURCE_INVENTORY_HISTORY.SILV_BASE = ST and DI then ` draw as
 combination of the above circles and radius linesIf
 RESOURCE_INVENTORY_HISTORY.SILV_BASE = ST and PL then : draw as
 combination of the above circles and radius linesIf
 RESOURCE_INVENTORY_HISTORY.SILV_BASE = SI and DI then * draw as
 combination of the above circles and radius linesIf
 RESOURCE_INVENTORY_HISTORY.SILV_BASE = SI and PL then X draw as
 combination of the above circles and radius linesIf
 RESOURCE_INVENTORY_HISTORY.SILV_BASE = DI and PL then ; draw as
 combination of the above circles and radius linesIf
 RESOURCE_INVENTORY_HISTORY.SILV_BASE = ST and PL and DI then ? draw as
 combination of the above circles and radius linesIf
 RESOURCE_INVENTORY_HISTORY.SILV_BASE = ST and SI and DI then @ draw as
 combination of the above circles and radius linesIf
 RESOURCE_INVENTORY_HISTORY.SILV_BASE = PL and ST and SI then [draw as
 combination of the above circles and radius linesIf
 RESOURCE_INVENTORY_HISTORY.SILV_BASE = SI and DI and PL then \ draw as
 combination of the above circles and radius linesIf
 RESOURCE_INVENTORY_HISTORY.SILV_BASE = ST and SI and DI an
 d PL then ^ draw as combination.

The value here must be mapped to the drawn history symbol.

LINE 7B DISTURBANCE HISTORY	POLY LABEL LINE	Y VARCHAR2	100
-----------------------------	-----------------	------------	-----

The disturbance history described as a list of abbreviations for the techniques along with the years each technique was employed. Possible values are B (wildfire), BE (escaped burn), BG (ground burn), BR (range burn), BW (wildlife burn), D (disease), F (flooding), I (insect), K (fume kill), L (logging), L% (logged with percentage), R (site rehabilitation), S (slide), and W (wind throw). Silviculture techniques with dates and percentages where silviculture base = DI.

LINE 8 PLANTING HISTORY	POLY LABEL LINE	Y VARCHAR2	100
-------------------------	-----------------	------------	-----

The planting (or regeneration) history described as a list of years during which artificial planting was performed. Silviculture techniques with dates where silviculture base = PL.

SMALL LABEL	POLY LABEL LINE 200	N VARCHAR2	200
-------------	---------------------	------------	-----

The two-line (or Format 3) version of the label. This label contains, at most, 2 lines build from the line 1 and 2 attributes. A back slash represents a carriage return.

FULL LABEL	POLY LABEL LINE 1000	N VARCHAR2	1000
------------	----------------------	------------	------

The full label. It is at most 8 lines. Back slashes represent carriage returns.

PRINTABLE IND	INDICATOR	N VARCHAR2	1
---------------	-----------	------------	---

Indicates that the label for the (projected) vegetation cover polygon is to be visually displayed (printed).

LABEL WIDTH	LABEL DIMENSION	Y NUMBER
-------------	-----------------	----------

The width of the full label for a 1:15,000 map presentation in meters. It is calculated as 18 times the number of characters in the longest line.

LABEL HEIGHT	LABEL DIMENSION	Y NUMBER
--------------	-----------------	----------

The height of the full label for a 1:15,000 map presentation in meters. It is calculated as 30 times the number of lines in the full label.

AVAIL LABEL WIDTH	LABEL DIMENSION	Y NUMBER
-------------------	-----------------	----------

The available width for a label, in meters for a 1:15,000 map presentation. This is derived during the label generation process to calculate if the VRI label will fit within a polygon shape or be written the map side. Currently equal to the diameter of the largest circle that can be placed in the polygon.

AVAIL LABEL HEIGHT	LABEL DIMENSION	Y NUMBER
--------------------	-----------------	----------

The available height for a label, in meters for a 1:15,000 map presentation. This is derived during the label generation process to calculate if the VRI label will fit within a polygon shape or be written the map side. Currently equal to the diameter of the largest circle that

Entity Name: VEGETATION COVER POLYGON PROJEC (cont'd)**Short Name:**

VCP

can be placed in the polygon.

LABEL CENTRE X	COORDINATE POINT BASIC	Y	NUMBER
----------------	------------------------	---	--------

The horizontal ("X") co-ordinate of the suggested centre of the label.

LABEL CENTRE Y	COORDINATE POINT BASIC	Y	NUMBER
----------------	------------------------	---	--------

The vertical ("Y") co-ordinate of the suggested centre of the label.

YEAR PROJECTED TO	NUMERIC YEAR	Y	NUMBER	4,0
-------------------	--------------	---	--------	-----

The projection year to which time dependent stand information, such as age and height, is projected.

ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE
-----------------	-----------------	---	------

Entry date/time

ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
--------------	--------------	---	----------	----

Entry by userid

UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE
------------------	-----------------	---	------

Update date/time

UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
---------------	--------------	---	----------	----

Updated by userid

* = Attributes in primary unique identifier.

Relationships:Each Occurrence Of This Entity:

MAY BE has alpine designation one and only one ALPINE DESIGNATION CODE

MAY BE has first BCLCS level one and only one BCLCS LEVEL1 CODE

MAY BE has second BCLCS level one and only one BCLCS LEVEL2 CODE

MAY BE has third BCLCS level one and only one BCLCS LEVEL3 CODE

MAY BE has fourth BCLCS level one and only one BCLCS LEVEL4 CODE

MAY BE has fifth BCLCS level one and only one BCLCS LEVEL5 CODE

MAY BE in BEC Zone one and only one BEC ZONE CODE

MAY BE has herb cover pattern one and only one COVER PATTERN CODE

MAY BE has shrub pattern one and only one COVER PATTERN CODE

MAY BE ecosystem data sourced from one and only one DATA SOURCE ECOSYS CLASS CODE

* MAY BE provides projection of one and only one FOREST COVER OBJECT

MAY BE has herb cover type one and only one HERB COVER TYPE CODE

MAY BE soil makeup described through one or more LAND COVER COMPONENT PRJ

MAY BE is modified by process one and only one MODIFYING PROCESS CODE

MAY BE has non-productive VDYP descriptor one and only one NON PRODUCTIVE CODE

MAY BE has non productive descriptor one and only one NON PRODUCTIVE DESCRIPTOR CODE

MAY BE shows non vegetative coverage through one or more NON VEGETATIVE COVER PRJ

MAY BE has site position meso one and only one SITE POSITION MESO CODE

MAY BE in soil nutrient regime one and only one SOIL NUTRIENT REGIME CODE

MAY BE surface expression described by one and only one SURFACE EXPRESSION CODE

MAY BE divided vertically into one or more TREE COVER LAYER PROJECTED

MAY BE has meta-information one and only one VEGETATION METADATA PROJECTED

* = Relationships in primary unique identifier.

Unique Identifiers:

VCP	PK	Primary	Y
-----	----	---------	---

MAY BE provides projection of one and only one FOREST COVER OBJECT

Entity Name: VEGETATION COVER POLYGON STAGIN**Short Name:**

VCPS

Plural: VEGETATION COVER POLYGON STG**Init. Volume:** 30000**Avg. Volume:** 30000**Max. Volume:** 120000**Annual Growth Rate:** 0%**Description:**

Describes the attribution of a Forest Cover Object that is currently being staged, in preparation for integration into the Estimated and Adjusted areas. This represents the first and last stage in the life cycle of a Forest Cover Object, as they are loaded into and extracted from the staging area.

The structure of the entity has been intentionally made to parallel other entities of similar names in the other components of the system. This was done in order to ease transition of data between the components, as the polygon transitions through its life cycle.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
INPUT DATE	DATE TIME	Y	DATE	
The date the vegetation cover information was entered into the Provincial Data Base.				
VRI DEAD STEMS PER HA	STEM COUNT	Y	NUMBER	4,0
The number of standing dead trees visible to the photo interpreter in the dominant, codominant and high intermediate crown positions in each tree layer. Snag frequency is expressed as stems per hectare for each tree layer. The snag frequency provides a direct estimate of snags per hectare that can be used for wildlife and fire management.				
Note: Dominant trees have well-developed crowns that extend above the general level of the trees around them. Codominant trees have crowns forming the general level of trees around them. High intermediate trees have smaller crowns slightly below but extending into the general level of trees around them.				
SHRUB HEIGHT	HEIGHT - SHRUB	Y	NUMBER	4,1
The average height of the shrubs contained in the polygon as interpreted from medium scale photography.				
SHRUB CROWN CLOSURE	PERCENTAGE 3,0	Y	NUMBER	3,0
Shrub crown closure is the percentage of ground area covered by the vertically projected crowns of the shrub cover visible to the photo interpreter. Shrub crown closure is expressed as a percentage of the entire polygon.				
HERB COVER PCT	PERCENTAGE 3,0	Y	NUMBER	3,0
Herb cover percent is the percentage of ground area covered by herbaceous cover visible to the photo interpreter. Herb cover percent is analogous to tree and shrub crown closures and is expressed as a percentage of the entire polygon.				
BRYOID COVER PCT	PERCENTAGE 3,0	Y	NUMBER	3,0
The percent cover of Bryoids: includes bryophytes (mosses, liverworts, hornworts) and non-crustose lichens.				
STOCKABILITY	STOCKABILITY	Y	NUMBER	4,1
An estimate of the percentage of polygon area that will eventually be stocked by trees. For example, a stockability value of 80% indicates that 20% of the area will never support tree growth.				
YIELD FACTOR	YIELD FACTOR	Y	NUMBER	5,3
An input to FIPSTART or VRISTART, two VDYP7 programs that generate the stand description that is required to project the polygon.				
REFERENCE YEAR	NUMERIC YEAR	Y	NUMBER	4,0
The year of the photo or source survey that was used to generate the VRI attributes.				
ADJUSTED IND	INDICATOR	N	VARCHAR2	1
Indicates the Polygon has been adjusted.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30

Entity Name:	VEGETATION COVER POLYGON STAGIN (cont'd)	Short Name:	VCPS
---------------------	--	--------------------	------

Entry by userid			
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE
Update date/time			
UPDATE USERID	AUDIT USERID	N	VARCHAR2 30
Updated by userid			

* = Attributes in primary unique identifier.

Relationships:

Each Occurrence Of This Entity:

- MAY BE adjusted by factor one or more ADJUSTMENT FACTOR STAGING
 - MAY BE provides adjustment for one or more ADJUSTMENT INPUT STAGING
 - MAY BE has alpine designation one and only one ALPINE DESIGNATION CODE
 - MAY BE has first BCLCS level one and only one BCLCS LEVEL1 CODE
 - MAY BE has second BCLCS level one and only one BCLCS LEVEL2 CODE
 - MAY BE has third BCLCS level one and only one BCLCS LEVEL3 CODE
 - MAY BE has fourth BCLCS level one and only one BCLCS LEVEL4 CODE
 - MAY BE has fifth BCLCS level one and only one BCLCS LEVEL5 CODE
 - MAY BE in BEC zone one and only one BEC ZONE CODE
 - MAY BE has herb cover pattern one and only one COVER PATTERN CODE
 - MAY BE has shrub pattern one and only one COVER PATTERN CODE
 - MAY BE ecosystem class sourced from one and only one DATA SOURCE ECOSYS CLASS CODE
 - * MUST BE provides staging for one and only one FOREST COVER OBJECT STAGING
 - MAY BE has herb cover type one and only one HERB COVER TYPE CODE
 - MAY BE soil makeup described through one or more LAND COVER COMPONENT STG
 - MAY BE summarized by one and only one LAYER SUMMARIZATION CODE
 - MAY BE process described by one and only one MODIFYING PROCESS CODE
 - MAY BE has non-productive VDYP descriptor one and only one NON PRODUCTIVE CODE
 - MAY BE has non-productive descriptor one and only one NON PRODUCTIVE DESCRIPTOR CODE
 - MAY BE shows non-veg coverage through one or more NON VEGETATIVE COVER STG
 - MAY BE adjusted by one or more SAMPLES USED STAGING
 - MAY BE has site position meso one and only one SITE POSITION MESO CODE
 - MAY BE has soil nutrient regime one and only one SOIL NUTRIENT REGIME CODE
 - MAY BE polygon for one or more STRATA POLYGON STAGING
 - MAY BE has surface expression one and only one SURFACE EXPRESSION CODE
 - MAY BE divided vertically into one or more TREE COVER LAYER STAGING
 - MAY BE has metadata one and only one VEGETATION METADATA STAGING
- * = Relationships in primary unique identifier.

Unique Identifiers:

VCPS PK	Primary	Y
MUST BE provides staging for one and only one FOREST COVER OBJECT STAGING		

Entity Name: VEGETATION METADATA ADJUSTED				Short Name:	VMA
Plural:	VEGETATION METADATA ADJUSTED				
Init. Volume:	3800000	Avg. Volume:	4000000	Max. Volume:	4200000
				Annual Growth Rate:	5%

Description:

The table that maintains the version number for VDYP at the time of the meta data's creation, as well as additional VDYP specific metadata for an adjusted polygon. Metadata may not always be present, but when it is, it refers to a specific polygon.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* VDYP VERSION	VERSION NUMBER	N	VARCHAR2	5
Version number for VDYP at the time of the meta data's creation.				
SINDEX VERSION	VERSION NUMBER	Y	VARCHAR2	5
The version of the software used to adjust/project the polygon data.				
LAST VDYP METADATA DATE	DATE TIME	Y	DATE	
The date the VDYP meta data was last updated.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MAY BE further describes one or more VEGETATION COVER POLYGON ADJ

* = Relationships in primary unique identifier.

Unique Identifiers:

VMA PK	Primary	Y
VDYP VERSION		

Entity Name:	VEGETATION METADATA PROJECTED			Short Name:	VMP
Plural:	VEGETATION METADATA PROJECTED				
Init. Volume:	3800000	Avg. Volume:	4000000	Max. Volume:	4200000
				Annual Growth Rate:	5%

Description:

The table that maintains the version number for VDYP at the time of the meta data's creation, as well as additional VDYP specific metadata for a projected polygon. Metadata may not always be present, but when it is, it refers to a specific polygon.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* VDYP VERSION Version number for VDYP at the time of the meta data's creation.	VERSION NUMBER	N	VARCHAR2	5
SINDEX VERSION The version of the software used to project the polygon data.	VERSION NUMBER	Y	VARCHAR2	5
LAST VDYP METADATA DATE The date the VDYP meta data was last updated.	DATE TIME	Y	DATE	
ENTRY TIMESTAMP Entry date/time	AUDIT TIMESTAMP	N	DATE	
ENTRY USERID Entry by userid	AUDIT USERID	N	VARCHAR2	30
UPDATE TIMESTAMP Update date/time	AUDIT TIMESTAMP	N	DATE	
UPDATE USERID Updated by userid	AUDIT USERID	N	VARCHAR2	30
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MAY BE further describes one or more VEGETATION COVER POLYGON PRJ

* = Relationships in primary unique identifier.

Unique Identifiers:

VMP PK	Primary	Y
VDYP VERSION		

Entity Name: VEGETATION METADATA STAGING				Short Name:	VMS
Plural:	VEGETATION METADATA STAGING				
Init. Volume:	30000	Avg. Volume:	30000	Max. Volume:	120000
				Annual Growth Rate:	0%

Description:

The table that maintains the version number for VDYP at the time of the meta data's creation, as well as additional VDYP specific metadata for a staged polygon. Metadata may not always be present, but when it is, it refers to a specific polygon.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* VDYP VERSION	VERSION NUMBER	N	VARCHAR2	5
Version number for VDYP at the time of the meta data's creation.				
SINDEX VERSION	VERSION NUMBER	Y	VARCHAR2	5
The version of the software used to adjust/project the polygon data.				
LAST VDYP METADATA DATE	DATE TIME	Y	DATE	
The date the VDYP meta data was last updated.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MAY BE provides metadata for one or more VEGETATION COVER POLYGON STG

* = Relationships in primary unique identifier.

Unique Identifiers:

VMS PK	Primary	Y
VDYP VERSION		

Entity Name: VERTICAL COMPLEXITY CODE			Short Name:	VCC
Plural:	VERTICAL COMPLEXITY CODE			
Init. Volume:	10	Avg. Volume:	10	Max. Volume: 20
			Annual Growth Rate:	10%

Description:

A list that describes a subjective classification that in turn describes the form of each tree layer, as indicated by the relative uniformity of the height of the forest canopy, as it appears on mid-scale aerial photographs. Vertical complexity is influenced by stand age, species (succession as it relates to shade tolerance) and degree and age of past disturbances. The tree height range is calculated as the total difference in height between the tallest and shortest visible dominant, co-dominant, and high intermediate trees. To most adequately represent the tree layer of interest, occasional occurrences of either very tall or very short trees should be ignored so that the vertical complexity indicated is for the majority of stems in the dominant, co-dominant, and highintermediate portion of each tree layer.

- Eg. 0 - Undetermined
1 - Very uniform
2 - Uniform
3 - Moderately uniform
4 - Non-uniform
5 - Very non-uniform

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* VERTICAL COMPLEXITY CODE	CODETABLE CODE	N	VARCHAR2	10
The subjective classification that describes the form of each tree layer as indicated by the relative uniformity of the height of the forest canopy as it appears on mid-scale aerial photographs. Vertical complexity is influenced by stand age, species (succession as it relates to shade tolerance) and degree and age of past disturbances. The tree height range is calculated as the total difference in height between the tallest and shortest visible dominant, co-dominant, and high intermediate trees. To most adequately represent the tree layer of interest, occasional occurrences of either very tall or very short trees should be ignored so that the vertical complexity indicated is for the majority of stems in the dominant, co-dominant, and highintermediate portion of each tree layer. Vertical complexity is a subjective classification that describes the form of each tree layer as indicated by the relative uniformity of the forest canopy as it appears on midscale aerial photographs.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

- MAY BE vertical complexity for one or more TREE COVER LAYER ADJUSTED
MAY BE vertical complexity for one or more TREE COVER LAYER ESTIMATED
MAY BE vertical complexity for one or more TREE COVER LAYER PROJECTED
MAY BE vertical complexity for one or more TREE COVER LAYER STAGING
* = Relationships in primary unique identifier.

Unique Identifiers:

VCC PK	Primary	Y
VERTICAL COMPLEXITY CODE		

Entity Name: VRIMS AUDIT STATE CODE			Short Name:	VASC
Plural:	VRIMS AUDIT STATE CODE			
Init. Volume:	5	Avg. Volume:	5	Max. Volume: 10
			Annual Growth Rate:	10%

Description:

A list of codes that describe the degree to which an entry has been audited and any resulting action.

- Eg. AUT - Automatically Accepted
- DEF - Deferred
- MAN - Manually Accepted
- NAU - Not Audited
- REJ - Rejected

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* VRIMS AUDIT STATE CODE	CODETABLE CODE	N	VARCHAR2	10
Stores the code for the audit state.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Last known date for an update.				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MAY BE audit state described by one or more VRIMS PACKAGE TRANSACTION

* = Relationships in primary unique identifier.

Unique Identifiers:

VASC PK	Primary	Y
VRIMS AUDIT STATE CODE		

Entity Name: VRIMS BATCH PROCESS			<i>Short Name:</i>	VBP
<i>Plural:</i>	VRIMS BATCH PROCESS			
<i>Init. Volume:</i>	2	<i>Avg. Volume:</i>	4	<i>Max. Volume:</i> 10
			<i>Annual Growth Rate:</i>	0%

Description:

Represents a collection of polygons that will be manipulated by a scheduled process. This includes the Projection and Replication processes. A batch will be run only a few times per year, with a purge following its completion shortly thereafter.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* VRIMS BATCH PROCESS ID	NUMERIC IDENTIFIER	N	NUMBER	10
Primary unique numeric identifier for a batch job that will be used process a set of polygons.				
DESCRIPTION	CODETABLE DESCRIPTION	Y	VARCHAR2	120
Description of the batch.				
START TIME	DATE TIME	Y	DATE	
Date/Time at which the process started processing its batch of polygons.				
END TIME	DATE TIME	Y	DATE	
Date/Time at which the process completed processing its batch of polygons.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MUST BE processes one or more VRIMS BATCH PROCESS POLYGON

MUST BE modified by one and only one VRIMS SYSTEM MODE CODE

* = Relationships in primary unique identifier.

Unique Identifiers:

VBPP PK	Primary	Y
VRIMS BATCH PROCESS ID		

Entity Name: VRIMS BATCH PROCESS POLYGON				Short Name:	VBPP
Plural:	VRIMS BATCH PROCESS POLYGON				
Init. Volume:	3800000	Avg. Volume:	4000000	Max. Volume:	4200000
				Annual Growth Rate:	5%

Description:

Represents a single polygon that may be manipulated as part of a system process, such as the Replication or Projection process. The polygon collection will be populated only during a new batch of processing and will be purged shortly following its completion.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* VRIMS BATCH PROCESS POLYGON ID	NUMERIC IDENTIFIER	N	NUMBER	10
Primary unique numeric identifier for a polygon that will be manipulated by a scheduled process.				
STATUS_MESSAGE	STATUS MESSAGE	Y	VARCHAR2	200
Message returned by the modifying process, following its attempt to process the polygon. When multiple messages are returned, the most critical message will be saved; error messages will be stored in preference over warnings and warnings in preference over informational messages.				
ENTRY_TIMESTAMP	AUDIT_TIMESTAMP	N	DATE	
Entry date/time				
ENTRY_USERID	AUDIT_USERID	N	VARCHAR2	30
Entry by userid				
UPDATE_TIMESTAMP	AUDIT_TIMESTAMP	N	DATE	
Update date/time				
UPDATE_USERID	AUDIT_USERID	N	VARCHAR2	30
Updated by userid				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MUST BE identifies for processing one and only one FOREST COVER OBJECT

MUST BE processed by one and only one VRIMS BATCH PROCESS

MUST BE has status one and only one VRIMS PROCESSING STATE CODE

* = Relationships in primary unique identifier.

Unique Identifiers:

VBPP PK	Primary	Y
VRIMS BATCH PROCESS POLYGON ID		

Entity Name: VRIMS COMPOSITE R1 TREE COVER**Short Name:** VCTC**Plural:** VRIMS_COMPOSITE_R1_TREE_COVER**Init. Volume:****Avg. Volume:****Max. Volume:****Annual Growth Rate:****Description:**

Composition of VRIMS data for use within RESULTS; the data consists of a mash-up of spatial overlays with the results of projection using the Variable Density Yield Prediction (VDYP) Model. This data is restricted to the 'Rank 1' Layers.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u> <u>Format</u>	<u>Length</u>
* FEATURE ID		N NUMBER	38
Provincially unique identifier for an instance of a spatial feature.			
LAYER ID		N VARCHAR2	10
The unique business identification of a layer, or horizontal stratum, in a stand. Each layer is normally characterized as a distinct canopy containing a common forest cover structure with timber of similar ages (at least 40 years between layers) and heights (at least 10 meters between layers). Layers are assigned from the tallest layer downward.			
OPENING ID		Y NUMBER	10,0
System generated value uniquely identifying the opening.			
MAP ID		N VARCHAR2	7
Identifies the Forest Cover Map corresponding to the FIP file. It is the British Columbia Geographic System's (BCGS) Key Reference Number of the Forest Cover Map. The mapsheet most commonly used is the 6' X 12' BCGS mapsheet.			
POLYGON ID		N NUMBER	9,0
The polygon number is a reference number (non unique) assigned to each Vegetated or Non-Vegetated polygon after it is delineated. The polygon number provides a link between the graphic and descriptive files. The business assigned unique identifier for a polygon. Typically this has been uniquely assigned within a BCGS 6 X 12 Mapsheet.			
PROJECTED DATE		Y DATE	
The date to which time dependent stand information is projected. Attributes that are projected to a future date include: - Age, - Age Class, - Height, - Height Class, - Type Identity, - Stocking Class, etc.			
HARVEST DATE		Y DATE	
The date the forest cover information was entered into the Provincial Data Base.			
EARLIEST NONLOGGING DIST TYPE		Y VARCHAR2	10
Represents the polygons earliest non-logging disturbance type.			
EARLIEST NONLOGGING DIST DATE		Y DATE	
Represents the polygons earliest non-logging disturbance date.			
POLYGON AREA		Y NUMBER	10,3
The area of a polygon; usually derived from geographic information system processing software. The total area, in hectares, of the forest cover polygon. The total area should be equal to the sum of the areas for all resultants in that polygon.			
BEC ZONE		Y VARCHAR2	10
A code uniquely identifying a Biogeoclimatic Zone of interest to MOF.			
BEC SUBZONE		Y VARCHAR2	3
A code uniquely identifying a Biogeoclimatic SubZone of interest to MOF. A code used to designate a division of a specific biogeoclimatic Zone; a geographic area with a fairly uniform regional climate and a typical pattern of vegetation and soils. Subzones are not unique. They are only meaningful in conjunction with a Zone.			
BEC VARIANT		Y VARCHAR2	1
A one digit number used to denote a division of a specific biogeoclimatic subzone; A geographic area with a more specific regional climate. A variant has a specific pattern of vegetation and soils. Variants are only meaningful within a Zone			
ORG UNIT NO		Y NUMBER	10,0

Entity Name: VRIMS COMPOSITE R1 TREE COVER (cont'd)		Short Name:	VCTC
Number from Org Unit code table representing the organization that collected the data.			
ORG UNIT CODE	Y VARCHAR2	6	
Identifies any office within the ministry. First character identifies Exec, HQ branch, Region, or District. Next two chars identify the office name; next two the section (HQ Branch) or program (Region or District); last char identifies the subsection.			
REGION	Y VARCHAR2	6	
Identifies any region within the province. first character identifies exec, hq branch, region, or district. next two chars identify the office name; next two the section (hq branch) or program (region or district); last char identifies the subsection.			
OWNERSHIP	Y NUMBER	9	
A code indicating the generalised ownership value.			
MANAGED FOREST	Y VARCHAR2	6	
A code indicating that the polygon contributes to the managed forest land base for BC.			
MGMT UNIT ID	Y VARCHAR2	4	
The MGMT UNIT ID the polygon resides within. This is used in conjunction with Management Unit Type Code.			
MGMT UNIT TYPE CODE	Y VARCHAR2	1	
The MGMT UNIT TYPE CODE identifies the general type of administrative unit. This is often used with Management Unit Id to make reference to MOF administrative management unit. This is auto-generated through tenure linkage based on the prime licence associated with the opening. Eg. U-Timber Supply Area; V-Timber Supply Block; T-Tree Farm Licence; F-Woodlot, etc.			
SITE INDEX	Y NUMBER	4,1	
Site index is an estimate of site productivity for tree growth (height in metres at breast height age of 50 years). The mean height of the dominant and codominant trees will attain at a base index age used for the purposes of estimating forest site growth capability. The site index is based on a normalized set of coefficients calibrated to reflect the range of heights for a given tree species.			
SPECIES CD 1	Y VARCHAR2	10	
The code indicating the type of tree species predominate or leading in the tree layer. A "leading" species is identified as being the highest percent basal area or, if a very young stand, the relative number of stems per hectare. Species are described in terms of Genus, Species and variety.			
SPECIES PCT 1	Y NUMBER	5,2	
Percentages of the layer that the leading species occupies. For older stands, tree species percentage is based on percent basal area or, if a very young stand, the relative number of stems per hectare. Tree species percentage is estimated to the nearest percent for all living trees above a specified diameter.			
SPECIES CD 2	Y VARCHAR2	10	
The code indicating the type of tree species second most dominate in the tree layer. A "second" species is identified in descending order of species percent from the "leading" species. Species are described in terms of Genus, Species and variety.			
SPECIES PCT 2	Y NUMBER	5,2	
Percentages of the layer that the second most dominate species occupies. For older stands, tree species percentage is based on percent basal area or, if a very young stand, the relative number of stems per hectare. Tree species percentage is estimated to the nearest percent for all living trees above a specified diameter.			
SPECIES CD 3	Y VARCHAR2	10	
The code indicating the type of tree species third most dominate in the tree layer. A "third" species is identified in descending order of species percent from the "leading" species. Species are described in terms of Genus, Species and variety.			
SPECIES PCT 3	Y NUMBER	5,2	
Percentages of the layer that the third most dominate species occupies. For older stands, tree species percentage is based on percent basal area or, if a very young stand, the relative			

Entity Name: VRIMS COMPOSITE R1 TREE COVER (cont'd)		Short Name:	VCTC
number of stems per hectare. Tree species percentage is estimated to the nearest percent for all living trees above a specified diameter.			
SPECIES CD 4	Y VARCHAR2	10	
The code indicating the type of tree species fourth most dominate in the tree layer. The "fourth" species is identified in descending order of species percent from the "leading" species. Species are described in terms of Genus, Species and variety.			
SPECIES PCT 4	Y NUMBER	5,2	
Percentages of the layer that the fourth most dominate species occupies. For older stands, tree species percentage is based on percent basal area or, if a very young stand, the relative number of stems per hectare. Tree species percentage is estimated to the nearest percent for all living trees above a specified diameter.			
SPECIES CD 5	Y VARCHAR2	10	
The code indicating the type of tree species fifth most dominate in the tree layer. The "fifth" species is identified in descending order of species percent from the "leading" species. Species are described in terms of Genus, Species and variety.			
SPECIES PCT 5	Y NUMBER	5,2	
Percentages of the layer that the fifth most dominate species occupies. For older stands, tree species percentage is based on percent basal area or, if a very young stand, the relative number of stems per hectare. Tree species percentage is estimated to the nearest percent for all living trees above a specified diameter.			
SPECIES CD 6	Y VARCHAR2	10	
The code indicating the type of tree species sixth most dominate in the tree layer. The "sixth" species is identified in descending order of species percent from the "leading" species. Species are described in terms of Genus, Species and variety.			
SPECIES PCT 6	Y NUMBER	5,2	
Percentages of the layer that the sixth most dominate species occupies. For older stands, tree species percentage is based on percent basal area or, if a very young stand, the relative number of stems per hectare. Tree species percentage is estimated to the nearest percent for all living trees above a specified diameter.			
PROJECTED AGE 1	Y NUMBER	4,0	
The age projected to the adjustment area ground sample date, for Species 1.			
PROJECTED AGE 2	Y NUMBER	4,0	
The age projected to the adjustment area ground sample date, for Species 2.			
PROJECTED AGE CLASS	Y NUMBER	4,0	
The projected age class for species 1.			
PROJECTED HEIGHT CLASS	Y NUMBER	4,0	
The projected height class for species 1.			
TOTAL VOL PER HA 125	Y NUMBER	8,3	
Total net volume per hectare determined by percent basal area of the tree layer at the 12.5 cm utilization level. net volume per hectare is determined as gross volume less decay, waste, and breakage. depending on the magnitude of the species' decay, waste and breakage, the net volume for the leading species may be lower than volume for other species in the stand. net volumes are calculated for rank 1 layers only, typid 1 through 3.			
TOTAL VOL PER HA 175	Y NUMBER	8,3	
Total net volume per hectare determined by percent basal area of the tree layer at the 17.5 cm utilization level. net volume per hectare is determined as gross volume less decay, waste, and breakage. depending on the magnitude of the species' decay, waste and breakage, the net volume for the leading species may be lower than volume for other species in the stand. net volumes are calculated for rank 1 layers only, typid 1 through 3.			
TOTAL VOL PER HA 225	Y NUMBER	8,3	
Total net volume per hectare determined by percent basal area of the tree layer at the 22.5 cm utilization level. net volume per hectare is determined as gross volume less decay, waste, and breakage. depending on the magnitude of the species' decay, waste and breakage, the net volume for the leading species may be lower than volume for other			

Entity Name:	VRIMS COMPOSITE R1 TREE COVER (cont'd)	<i>Short Name:</i>	VCTC
---------------------	--	--------------------	------

species in the stand. net volumes are calculated for rank 1 layers only, typid 1 through 3.

ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				

* = *Attributes in primary unique identifier.*

Unique Identifiers:

VCTC PK	Primary	Y
FEATURE ID		

Notes:

This table contains a static cut of the VRI data projected to current year and will be updated annually. It is intended for strategic level resource analysis using the current GIS tools.

This is a denormalized summary table combining fields from the following tables: FOREST_COVER_OBJECT, VEGETATION_COVER_POLYGON_PRJ, TREE_COVER_LAYER_PRJ, TREE_SPECIES_PRJ, DISTURBANCE_EVENT and ORG_UNIT; the processing will be performed offsite and may include application code to perform some operations such as spatial overlays.

Entity Name: VRIMS DISTURBANCE CODE			Short Name:	DSCD
Plural:	VRIMS DISTURBANCE CODE			
Init. Volume:	1	Avg. Volume:	1	Max. Volume: 5
			Annual Growth Rate:	10%

Description:

A list of codes that describe the particular event that indicates that a disturbance has occurred. While only one code has been defined for this table at this time, it is expected that new codes will be added in future revisions of the application.

E.g. DI - Disturbance

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* VRIMS DISTURBANCE CODE	CODETABLE CODE	N	VARCHAR2	10
Describes the particular event that indicates that a disturbance has occurred.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MAY BE source of disturbance for one or more DISTURBANCE EVENT
MAY BE source of disturbance for one or more FOREST COVER OBJECT
MAY BE disturbs one or more FOREST COVER OBJECT STAGING
* = Relationships in primary unique identifier.

Unique Identifiers:

DSCD PK	Primary	Y
VRIMS DISTURBANCE CODE		

Entity Name:	VRIMS ERROR CONTEXT CODE			Short Name:	VECC
Plural:	VRIMS ERROR CONTEXT CODE				
Init. Volume:	5	Avg. Volume:	5	Max. Volume:	10
				Annual Growth Rate:	10%

Description:

A list of codes that describe the context of an error that was produced by the application.

Eg. POLY - Polygon
TRAN - Transaction
SRVC - Service

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* VRIMS ERROR CONTEXT CODE	CODETABLE CODE	N	VARCHAR2	10
Code representation of the error context.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MAY BE error type for one or more VRIMS ERROR LOG
* = Relationships in primary unique identifier.

Unique Identifiers:

VECC PK	Primary	Y
VRIMS ERROR CONTEXT CODE		

Entity Name:	VRIMS ERROR LEVEL CODE			Short Name:	VELC
Plural:	VRIMS ERROR LEVEL CODE				
Init. Volume:	5	Avg. Volume:	5	Max. Volume:	10
				Annual Growth Rate:	10%

Description:

A list of codes that describe the level (degree of severity) of an error message that was produced by the application.

Eg. WARN - Warning
ERR - Error
INFO - Information

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* VRIMS ERROR LEVEL CODE	CODETABLE CODE	N	VARCHAR2	10
Code representation of the error level.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MAY BE error type for one or more VRIMS ERROR LOG

* = Relationships in primary unique identifier.

Unique Identifiers:

VELC PK	Primary	Y
VRIMS ERROR LEVEL CODE		

Entity Name: VRIMS ERROR LOG				Short Name:	VEL
Plural:	VRIMS ERROR LOG				
Init. Volume:	20000	Avg. Volume:	30000	Max. Volume:	40000
				Annual Growth Rate:	0%

Description:

Provides a container for writing business and system errors. As this table acts as a queriable, historical log, entries within it will never be updated. When required, the table may be purged.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* VRIMS ERROR LOG ID	NUMERIC IDENTIFIER	N	NUMBER	10
Primary unique identifier for an error entry.				
ERROR MESSAGE	COMMENTS	N	VARCHAR2	2000
Contains the application text error.				
TIME STAMP	AUDIT TIMESTAMP	N	DATE	
The date and time that the error occurred, which could be slightly different than the time the error was logged.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MAY BE tracks errors from one and only one FOREST COVER OBJECT STAGING

MUST BE of error type one and only one VRIMS ERROR CONTEXT CODE

MUST BE of error type one and only one VRIMS ERROR LEVEL CODE

MUST BE of error type one and only one VRIMS ERROR TYPE CODE

MUST BE tracks errors from one and only one VRIMS PACKAGE TRANSACTION

* = Relationships in primary unique identifier.

Unique Identifiers:

VEL PK	Primary	Y
VRIMS ERROR LOG ID		

Entity Name: VRIMS ERROR TYPE CODE			<i>Short Name:</i>	VETC
<i>Plural:</i>	VRIMS ERROR TYPE CODE			
<i>Init. Volume:</i>	5	<i>Avg. Volume:</i>	5	<i>Max. Volume:</i> 10
			<i>Annual Growth Rate:</i>	10%

Description:

A list of codes that describe a type of error produced during polygon processing.

Eg. PRO - Processing Error
SPA - Spatial
BRV - Business Rule Validation
DAT - Database

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* VRIMS ERROR TYPE CODE	CODETABLE CODE	N	VARCHAR2	10
Code representation of the error type.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MAY BE error type for one or more VRIMS ERROR LOG
* = Relationships in primary unique identifier.

Unique Identifiers:

VETC PK	Primary	Y
VRIMS ERROR TYPE CODE		

Entity Name: VRIMS MAPSHEET LINK**Short Name:** VML**Plural:** VRIMS MAPSHEET LINK**Init. Volume:** 3800000**Avg. Volume:** 4000000**Max. Volume:** 4200000**Annual Growth Rate:** 5%**Description:**

This entity represents the relationship between the VRIMS spatial data brought forward from the INCOSADA spatial data.

This entity is to be used for historical purposes to determine where the old data in INCOSADA has been mapped into VRIMS.

Once the entity has been populated after the data conversion no additional updates will take place.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* OBJECT VERSION SKEY		N	NUMBER	
Unique identifier for a version of an INCOSADA spatial data polygon.				
POLYGON ID		N	NUMBER	6
The POLYGON_ID is a human readable identifier and comes from INCOSADA. The polygon id is unique to a MAP_ID and assigned to every polygon found with a BCGS 1:20K mapsheet. Identifiers start from 1 and increment to the number of polygons found within a single mapsheet.				
MAP ID		N	VARCHAR2	7
The MAP_ID is a mapsheet name using the provincial definition of BCGS 1:20K mapsheet naming conventions. Typical mapsheets names would be 082E001 through to 082E100, 094F001 etc.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				
* = Attributes in primary unique identifier.				

Relationships:Each Occurrence Of This Entity:

MAY BE converted from one and only one FOREST COVER OBJECT

* = Relationships in primary unique identifier.

Unique Identifiers:

VML_2	Primary	Y
OBJECT VERSION SKEY		

Entity Name: VRIMS PACKAGE TRANSACTION*Short Name:*

VPKT

Plural: VRIMS PACKAGE TRANSACTION*Init. Volume:* 1000*Avg. Volume:* 1500*Max. Volume:* 25000*Annual Growth Rate:* 10%**Description:**

This entity represents a package made up of polygons that have been processed in a single transaction. The package can contain one or many polygons and can be from an update, re-inventory or RESULTS.

As the need to update a Package Transaction entry will occur very infrequently (if ever), a process of deletion and reinsertion will be performed. Only new entries are ever expected to be added to this entity.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* VRIMS PACKAGE TRANSACTION ID	RESULTS OPENING ID	N	NUMBER	10,0
Primary unique numeric identifier for a package made up of polygons.				
OPENING_ID		Y	NUMBER	10
The OPENING_ID is the identifier from RESULTS.				
FILE NAME	FILE NAME	Y	VARCHAR2	64
The name of the file for the package.				
AUDITOR	USERID	Y	VARCHAR2	30
The name of the user performing the Audit. This is not necessarily the same as the Entry UserID.				
AUDIT DATE	AUDIT TIMESTAMP	Y	DATE	
The date when Audited [VIEW_STATE = T].				
VIEWED IND	INDICATOR	N	VARCHAR2	1
Indicates whether or not a package has been viewed in the transaction audit tool.				
ESTIMATED PROCESS DURATION	DURATION	Y	NUMBER	10
The estimated number of seconds it will take to process this transaction.				
NUMBER OF POLYGONS	COUNTER	Y	NUMBER	10
The total number of polygons that are in the transaction. This is used to calculate the average processing time per polygon.				
PROCESSING PRIORITY	PRIORITY - USER DEFINED	Y	NUMBER	3,0
The priority by which the item is to be queued for processing. Lower valued items indicate a higher priority and will be processed sooner than lower priority items.				
CHECKED OUT BY	USERID	Y	VARCHAR2	30
This is the account that has checked out this group of polygons.				
DATE CHECKED IN	DATE TIME	Y	DATE	
This is the date that the this group of polygons were checked in to the database.				
DATE CHECKED OUT	DATE TIME	Y	DATE	
This is the date that this group of polygons were checked out of the database.				
RESULTS SUBMISSION ID	NUMERIC IDENTIFIER	Y	NUMBER	10
Numeric identifier for the RESULTS system submission that is associated with this transaction. This identifier provides means to reconcile the package with its source RESULTS submission.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				

VPKT

VRIMS PACKAGE TRANSACTION ID

Entity Name: VRIMS POLYGON TRANSACTION			<i>Short Name:</i>	VPLT
<i>Plural:</i>	VRIMS POLYGON TRANSACTION			
<i>Init. Volume:</i>	30000	<i>Avg. Volume:</i>	60000	<i>Max. Volume:</i> 120000
			<i>Annual Growth Rate:</i>	10%

Description:

This entity represents a polygon that has been extracted from the database, as part of a transaction. A polygon can be the result of an update, re-inventory or be sourced from RESULTS.

As the need to update a Polygon Transaction entry will occur very infrequently (if ever), a process of deletion and reinsertion will be performed. Only new entries are ever expected to be added to this entity.

This entity maintains the association that allows a polygon to be checked out multiple times, by different users, before being checked in again during a new transaction.

When a FOREST COVER OBJECT is split into two polygons or is deleted, a POLYGON TRANSACTION is still created, resulting in no corresponding Staging area polygon.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* VRIMS POLYGON TRANSACTION ID	NUMERIC IDENTIFIER	N	NUMBER	10
Primary unique numeric identifier that identifies a polygon that is contained within a package transaction.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

- MUST BE extracts one and only one FOREST COVER OBJECT
 - MAY BE processes one or more FOREST COVER OBJECT STAGING
 - MUST BE grouped for processing by one and only one VRIMS PACKAGE TRANSACTION
- * = Relationships in primary unique identifier.

Unique Identifiers:

VPLT UK	Primary	N
MUST BE extracts one and only one FOREST COVER OBJECT		
MUST BE grouped for processing by one and only one VRIMS PACKAGE TRANSACTION		
VPLT PK	Primary	Y
VRIMS POLYGON TRANSACTION ID		

Entity Name: VRIMS PROCESSING STATE CODE			<i>Short Name:</i>	VPSC
<i>Plural:</i>	VRIMS PROCESSING STATE CODE			
<i>Init. Volume:</i>	20	<i>Avg. Volume:</i>	20	<i>Max. Volume:</i> 30
			<i>Annual Growth Rate:</i>	10%

Description:

A list of codes that describes the state in which the package is being transacted.

- Eg. BI - Being Integration
- BP - Being Prepared
- CO - Checked Out
- FI - Failed Integration
- FP - Failed Preparation
- INBOX - Inbox
- INT - Integrated
- MI - Marked for Integration
- MP - Marked for Purge
- MS - Marked for Resubmit
- MT - Marked for Retry
- NEW - New
- PG - Purged
- PRE - Prepared
- REJ - Rejected
- RS - Resubmit

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* VRIMS PROCESSING STATE CODE	CODETABLE CODE	N	VARCHAR2	10
Describes the state in which the package is being transacted.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

- MAY BE status for one or more VRIMS BATCH PROCESS POLYGON
- MAY BE in processing state one or more VRIMS PACKAGE TRANSACTION
- * = Relationships in primary unique identifier.

Unique Identifiers:

VPSC PK	Primary	Y
VRIMS PROCESSING STATE CODE		

VRIMS SERVICE CODE

Entity Name: VRIMS SERVICE STATE CODE			<i>Short Name:</i>	VSTC
<i>Plural:</i>	VRIMS SERVICE STATE CODE			
<i>Init. Volume:</i>	5	<i>Avg. Volume:</i>	5	<i>Max. Volume:</i> 10
			<i>Annual Growth Rate:</i>	10%

Description:

A list of codes used to identify the status of a system service.

E.g.: Idle, Processing, etc.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* VRIMS SERVICE STATE CODE	CODETABLE CODE	N	VARCHAR2	10
A code representation of the state of the system service.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MAY BE service state for one or more VRIMS SYSTEM SERVICE STATUS

* = Relationships in primary unique identifier.

Unique Identifiers:

VSTC PK	Primary	Y
VRIMS SERVICE STATE CODE		

Entity Name: VRIMS SYSTEM MODE CODE			Short Name:	VSMC
Plural:	VRIMS SYSTEM MODE CODE			
Init. Volume:	5	Avg. Volume:	5	Max. Volume: 10
			Annual Growth Rate:	10%

Description:

A code list that represents the mode in which that the system is operating.

E.g.: Automatic, Manual, etc.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* VRIMS SYSTEM MODE CODE	CODETABLE CODE	N	VARCHAR2	10
A code representation of the system mode.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MAY BE processes one or more VRIMS BATCH PROCESS

MAY BE current mode for one or more VRIMS SYSTEM STATUS

MAY BE desired mode for one or more VRIMS SYSTEM STATUS

* = Relationships in primary unique identifier.

Unique Identifiers:

VSMC PK	Primary	Y
VRIMS SYSTEM MODE CODE		

Entity Name: VRIMS SYSTEM PREFERENCE			<i>Short Name:</i>	VSP
<i>Plural:</i>	VRIMS SYSTEM PREFERENCE			
<i>Init. Volume:</i>	15	<i>Avg. Volume:</i>	20	<i>Max. Volume:</i> 50
			<i>Annual Growth Rate:</i>	10%

Description:

Describes various application configuration parameters that may need to be changeable at runtime, possibly by either the system administrator or by agent processes. This provides a single point of configuration for all agent processes, without requiring redundant code to handle configuration, as well as the ability to change the values without restarting the agent processes.

- Some preferences include:
- number of times a service should attempt to read a personal geodatabase
 - time at which the backend process should stop processing each day
 - maximum number of polygons to be counted in calculating the average processing time

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* PREFERENCE NAME	PREFERENCE NAME	N	VARCHAR2	100
Unique textual identifier of the preference.				
VALUE	PREFERENCE VALUE	N	VARCHAR2	250
Value of the preference, when provided. When the value is NULL, it indicates that the preference has not been set, but is still used by the system in some context.				
DESCRIPTION	PREFERENCE DESCRIPTION	N	VARCHAR2	200
Textual description of the value, particularly in regards to its use within the system and valid values for it.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				
* = Attributes in primary unique identifier.				

Unique Identifiers:

VSP PK	Primary	Y
PREFERENCE NAME		

Entity Name:	VRIMS SYSTEM SERVICE STATUS			Short Name:	VSSS
Plural:	VRIMS SYSTEM SERVICE STATUS				
Init. Volume:	5	Avg. Volume:	5	Max. Volume:	20
				Annual Growth Rate:	10%

Description:

This describes a service that runs as a component of the overall application. The service status stores metrics about a service that has been processing VRIMS data, including attributes about its operational status.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
ENABLED IND	INDICATOR	N	VARCHAR2	1
Indicates when the service is enabled.				
AVERAGE PROCESSING TIME	DURATION - PRECISE	N	NUMBER	6,3
The average time in seconds that it takes to process a polygon for the service.				
NUMBER OF POLYGONS IN AVERAGE	COUNTER 38	N	NUMBER	38
The number of polygons used to calculate the Average Processing Time for the service.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MAY BE monitors processing of one and only one VRIMS PACKAGE TRANSACTION

* MUST BE monitors status of one and only one VRIMS SERVICE CODE

MUST BE has service state one and only one VRIMS SERVICE STATE CODE

* = Relationships in primary unique identifier.

Unique Identifiers:

VSSS PK	Primary	Y
MUST BE monitors status of one and only one VRIMS SERVICE CODE		

Entity Name: VRIMS SYSTEM STATE CODE			Short Name:	VSSC
Plural:	VRIMS SYSTEM STATE CODE			
Init. Volume:	5	Avg. Volume:	5	Max. Volume: 10
			Annual Growth Rate:	10%

Description:

A lsit of codes that denote a state for the system. For example the system may be in a state of retrieving all results datasets, therefore no other processing may take place. This state will be checked by the various services that will be required to retrieve and process data.

Eg. CM - Changing Mode
ERR - Halted on Error
RUN - Running
ST - Starting Up
WAIT - Waiting for Operating Window

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* VRIMS SYSTEM STATE CODE	CODETABLE CODE	N	VARCHAR2	10
A code that denotes a state for the system. For example the system may be in a state of retrieving all results datasets, therefore no other processing may take place. This state will be checked by the various services that will be required to retrieve and process data.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE_DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY_DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE_TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MAY BE state for one or more VRIMS SYSTEM STATUS

* = Relationships in primary unique identifier.

Unique Identifiers:

VSSC PK	Primary	Y
VRIMS SYSTEM STATE CODE		

Entity Name: VRIMS SYSTEM STATUS			Short Name:	VSYS
Plural:	VRIMS SYSTEM STATUS			
Init. Volume:	1	Avg. Volume:	1	Max. Volume: 1
			Annual Growth Rate:	0%

Description:

This maintains a single entry that denotes a state for the entire application. For example, the system may be in a state of retrieving all results datasets, therefore no other processing may take place. This state will be checked by the various services that will be required to retrieve and process data. The state status entry is a permanent data row that is loaded once when the system is created and should never be deleted. There is no direct user manipulation of the data; instead, the attribution of the row is modified by service components of the application.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* VRIMS SYSTEM STATUS ID	NUMERIC IDENTIFIER	N	NUMBER	10
Primary unique numeric identifier for the status of the system.				
LAST ACTIVE TIMESTAMP	DATE TIME	Y	DATE	
The date/time that the service was last able to update this field, proving to external viewers that is still active. This attribute acts as a heartbeat, helping to determine if a disconnected, headless service (i.e. lacking a user interface) is still active.				
ENTRY TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Entry date/time				
ENTRY USERID	AUDIT USERID	N	VARCHAR2	30
Entry by userid				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
UPDATE USERID	AUDIT USERID	N	VARCHAR2	30
Updated by userid				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

- MAY BE controlled by one and only one VRIMS SERVICE CODE
 - MUST BE has current mode one and only one VRIMS SYSTEM MODE CODE
 - MUST BE transitioning to mode one and only one VRIMS SYSTEM MODE CODE
 - MUST BE describes system state one and only one VRIMS SYSTEM STATE CODE
- * = Relationships in primary unique identifier.

Unique Identifiers:

VSYS PK	Primary	Y
VRIMS SYSTEM STATUS ID		

Notes:

There is no sequence associated with this entity, as it will only ever have a single entry. The row should always have SYSTEM STATUS ID = 1.

Entity Name:	VRIMS TRANSACTION TYPE CODE			Short Name:	VTTC
Plural:	VRIMS TRANSACTION TYPE CODE				
Init. Volume:	5	Avg. Volume:	5	Max. Volume:	10
				Annual Growth Rate:	10%

Description:

A list of valid codes that describes the type of transaction.

Eg. ADJ - Adjustment
REI - Reinventory
RES - Results

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* VRIMS TRANSACTION TYPE CODE	CODETABLE CODE	N	VARCHAR2	10
A code that describes the type of transaction.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120
Provides the description for the code. This is the human readable form of the code.				
EFFECTIVE DATE	DATE TIME	N	DATE	
Effective date/time				
EXPIRY DATE	DATE TIME	N	DATE	
Expiry date/time				
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N	DATE	
Update date/time				
* = Attributes in primary unique identifier.				

Relationships:

Each Occurrence Of This Entity:

MAY BE transaction type for one or more VRIMS PACKAGE TRANSACTION

* = Relationships in primary unique identifier.

Unique Identifiers:

VTTC PK	Primary	Y
VRIMS TRANSACTION TYPE CODE		

Entity Name: VRIMS TREE SPECIES CODE*Short Name:*

TSC

Plural: VRIMS TREE SPECIES CODE*Init. Volume:* 100*Avg. Volume:* 120*Max. Volume:* 140*Annual Growth Rate:* 10%**Description:**

A list of codes that describe the leading commercial species or brush species in the layer. The species with the highest percent composition (e.g. gross volume or, if a very young stand, the relative number of stems per hectare) is identified as the leading commercial species. Species must be above a specified diameter to be recognized in the species composition of the layer.

Leading species are described in terms of Genus, Species and Subspecies. There are currently 27 commercial tree species, and five genus values recognized in the Province. The code may also be used to describe brush species in cases where the Non-Productive Descriptor is NPBR or the Non-Forest Descriptor is NCBR.

Eg. A - Poplar

AC - Poplar

ACB - Balsam Poplar

ACT - Black Cottonwood

AT - Trembling Aspen

AX - Poplar Hybrid

B - True Fir

BA - Amabilis Fir

BB - Balsam Fir

BG - Grand Fir

BL - Subalpine Fir

BN - Noble Fir

C - Cedar

CW - Western Red Cedar

D - Alder

DG - Green/Sitka Alder (N)

DM - Mountain Alder (N)

DR - Red Alder

E - Birch

EA - Alaska Paper Birch

EB - Scrub Birch

EP - Paper Birch

ES - Swamp Birch

EW - Water Birch

EX - Birch Hybrid]

EXP - Alaska Paper X Paper

EXW - Water X Paper

F - Douglas-Fir

FD - Douglas-Fir

FDC - Douglas-Fir (Coast)

FDI - Douglas-Fir (Interior)

G - Dogwood (N)

GP - Flowering Dogwood (N)

GR - Red-Osier Dogwood

H - Hemlock

HM - Mountain Hemlock

HW - Western Hemlock

HX - Hemlock Hybrid

HXM - Western X Mountain

J - Juniper (N)

JD - Common Juniper

JH - Creeping Juniper

JR - Rocky Mountain Juniper (N)

K - Cascara (N)

KC - Cascara (N)

L - Larch

LA - Alpine Larch

LD - Dahurian Larch

LS - Siberian Larch

LT - Tamarack

Entity Name:	VRIMS TREE SPECIES CODE (cont'd)	Short Name:	TSC
---------------------	----------------------------------	-------------	-----

LW - Western Larch
M - Maple
MB - Bigleaf Maple
MR - Douglas Maple (N)
MV - Vine Maple (N)
P - Pine
PA - Whitebark Pine
PF - Limber Pine
PJ - Jack Pine
PL - Lodgepole Pine
PLC - Lodgepole Pine (Coast)
PLI - Lodgepole Pine (Interior)
PR
- Red Pine
PW - Western White Pine
PX - Pine Hybrid
PXJ - Lodgepole X Jack
PY - Yellow Pine
Q - Oak
QG - Garry Oak
RA - Arbutus (N)
S - Spruce
SA - Norway Spruce
SB - Black Spruce
SE - Engelmann Spruce
SS - Sitka Spruce
SW - White Spruce
SX - Spruce Hybrid
SXB - White X Black
SXE - Engelmann X Sitka
SXL - White X Sitka (Picea X Lutzii)
SXS - Sitka X Unknown Hybrid
SXW - White X Engelmann
SXX - White X Engelmann X Sitka
T - Yew
TW - Western Yew
UP - Pacific Crab Apple (Malus Fusca)
V - Cherry (N)
VB - Bitter Cherry (N)
VP - Pin Cherry
VW - Choke Cherry
W - Willow
WA - Barclay's Willow
WB - Bebb's Willow
WD - Grey-Leaved Willow
WS - Scouler's Willow
WT - Tea-Leaved Willow
Y - Cypress
YC - Yellow Cedar

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* VRIMS TREE SPECIES CODE	CODETABLE CODE	N	VARCHAR2	10
A code indicating the type of tree species in the layer. A "leading" species is identified as being the highest percent composition based on basal area or, if a very young stand, the relative number of stems per hectare. Species must be above a specified diameter to be recognized in the species composition of the layer. Species are described in terms of Genus, Species and variety.				
DESCRIPTION	CODETABLE DESCRIPTION	N	VARCHAR2	120

Entity Name:	VRIMS TREE SPECIES CODE (cont'd)	Short Name:	TSC
---------------------	----------------------------------	-------------	-----

Provides the description for the code. This is the human readable form of the code.		
EFFECTIVE DATE	DATE TIME	N DATE
Effective date/time		
EXPIRY DATE	DATE TIME	N DATE
Expiry date/time		
UPDATE TIMESTAMP	AUDIT TIMESTAMP	N DATE
Update date/time		
* = Attributes in primary unique identifier.		

Relationships:

Each Occurrence Of This Entity:

MAY BE est site index species for one or more TREE COVER LAYER ADJUSTED
MAY BE est site index species for one or more TREE COVER LAYER ESTIMATED
MAY BE est site index species for one or more TREE COVER LAYER PROJECTED
MAY BE est site index species for one or more TREE COVER LAYER STAGING
MAY BE leading commercial/brush species for one or more TREE SPECIES ADJUSTED
MAY BE leading commercial/brush species for one or more TREE SPECIES ESTIMATED
MAY BE leading commercial/brush species for one or more TREE SPECIES PROJECTED
MAY BE leading commercial/brush species for one or more TREE SPECIES STAGING
* = Relationships in primary unique identifier.

Unique Identifiers:

TSC PK	Primary	Y
VRIMS TREE SPECIES CODE		

Entity Name: VRIMS_FCO_TO_2006CONVERTED_FID			Short Name: VFT2F		
Plural: VRIMS_FCO_TO_2006CONVERTED_FID					
Init. Volume: 3800000		Avg. Volume: 4000000		Max. Volume: 4200000	
			Annual Growth Rate: 5%		

Description:

This table associates the old INCOSADA 2006 Forest Cover Polygons ID's (FID's) to the new VRIMS Forest Cover Object ID's (FCO ID's) after conversion.

Attributes:

<u>Name</u>	<u>Domain</u>	<u>Opt</u>	<u>Format</u>	<u>Length</u>
* GUID		N	VARCHAR2	32
An INCOSADA Provincially unique identifier for an instance of a spatial feature.				
FOREST_COVER_OBJECT_ID		Y	NUMBER	38
A VRIMS Provincially unique identifier for an instance of a spatial feature.				
OBJECT_VERSION_SKEY		Y	NUMBER	
A unique identifier for the object instance				
MAP_ID		Y	VARCHAR2	7
The polygon number is a reference number (non unique) assigned to each Vegetated or Non-Vegetated polygon after it is delineated. The polygon number provides a link between the graphic and descriptive files. The business assigned unique identifier for a polygon. Typically this has been uniquely assigned within a BCGS 6 X 12 Mapsheet.				
POLYGON_ID		Y	NUMBER	6
Identifies the Forest Cover Map corresponding to the FIP file. It is the British Columbia Geographic System's (BCGS) Key Reference Number of the Forest Cover Map. The mapsheet most commonly used is the 6' X 12' BCGS mapsheet.				
* = Attributes in primary unique identifier.				

Unique Identifiers:

VFT2CF PK	Primary	Y
GUID		

Index

ADJUSTMENT ATTRIBUTE CODE, 1
ADJUSTMENT ATTRIBUTE SET ADJUSTED, 2
ADJUSTMENT ATTRIBUTE SET STAGING, 3
ADJUSTMENT FACTOR ADJUSTED, 4
ADJUSTMENT FACTOR STAGING, 5
ADJUSTMENT INPUT ADJUSTED, 6
ADJUSTMENT INPUT STAGING, 8
ADJUSTMENT PROJECT ADJUSTED, 10
ADJUSTMENT PROJECT STAGING, 11
ALPINE DESIGNATION CODE, 12
BCLCS LEVEL1 CODE, 13
BCLCS LEVEL2 CODE, 14
BCLCS LEVEL3 CODE, 15
BCLCS LEVEL4 CODE, 16
BCLCS LEVEL5 CODE, 17
BEC ZONE CODE, 19
COVER PATTERN CODE, 20
DATA CAPTURE METHOD CODE, 22
DATA SOURCE AGE CODE, 23
DATA SOURCE BASAL AREA CODE, 24
DATA SOURCE ECOSYS CLASS CODE, 25
DATA SOURCE HEIGHT CODE, 26
DATA SOURCE INTERPRETED CODE, 27
DATA SRC VRI LIVE STEM HA CODE, 29
DISTURBANCE EVENT, 30
DISTURBANCE TYPE CODE, 31
ESTIMATED SINDEXT SOURCE CODE, 32
FOREST COVER OBJECT, 35
FOREST COVER OBJECT STAGING, 37
FOREST COVER RANK CODE, 39
HERB COVER TYPE CODE, 40
INVENTORY STANDARD CODE, 41
LAND COVER CLASS CODE, 42
LAND COVER COMPONENT ADJUSTED, 44
LAND COVER COMPONENT ESTIMATED, 45
LAND COVER COMPONENT PROJECTED, 46
LAND COVER COMPONENT STAGING, 47
LAND COVER LEVEL CODE, 48
LAYER LEVEL CODE, 49
LAYER SUMMARIZATION CODE, 50
MODIFYING PROCESS CODE, 51
NON FOREST DESCRIPTOR CODE, 52
NON PRODUCTIVE CODE, 53
NON PRODUCTIVE DESCRIPTOR CODE, 55
NON VEGETATIVE COVER ADJUSTED, 57
NON VEGETATIVE COVER ESTIMATED, 58
NON VEGETATIVE COVER PROJECTED, 59
NON VEGETATIVE COVER STAGING, 60
NON VEGETATIVE COVER TYPE CODE, 61
PROJECTED YIELD, 63
PROJECTION LAYER CODE, 65
SAMPLES USED ADJUSTED, 66
SAMPLES USED STAGING, 67
SITE POSITION MESO CODE, 68
SOIL MOISTURE REGIME CODE, 69
SOIL NUTRIENT REGIME CODE, 70
STRATA ADJUSTED, 71
STRATA POLYGON ADJUSTED, 72
STRATA POLYGON STAGING, 73
STRATA STAGING, 74
SURFACE EXPRESSION CODE, 75
TREE COVER LAYER ADJUSTED, 76
TREE COVER LAYER ESTIMATED, 78
TREE COVER LAYER PROJECTED, 80
TREE COVER LAYER STAGING, 82
TREE SPECIES ADJUSTED, 84
TREE SPECIES ESTIMATED, 86
TREE SPECIES PROJECTED, 88
TREE SPECIES STAGING, 90
VEG COMP LAYER, 92
VEG COMP POLY, 100
VEGETATION COVER POLYGON ADJUSTED, 109
VEGETATION COVER POLYGON ESTIMATED, 111
VEGETATION COVER POLYGON PROJECTED, 113
VEGETATION COVER POLYGON STAGING, 117
VEGETATION METADATA ADJUSTED, 119
VEGETATION METADATA PROJECTED, 120
VEGETATION METADATA STAGING, 121
VERTICAL COMPLEXITY CODE, 122
VRIMS AUDIT STATE CODE, 123
VRIMS BATCH PROCESS, 124
VRIMS BATCH PROCESS POLYGON, 125
VRIMS COMPOSITE R1 TREE COVER, 126
VRIMS DISTURBANCE CODE, 130
VRIMS ERROR CONTEXT CODE, 131
VRIMS ERROR LEVEL CODE, 132
VRIMS ERROR LOG, 133
VRIMS ERROR TYPE CODE, 134
VRIMS MAPSHEET LINK, 135
VRIMS PACKAGE TRANSACTION, 136
VRIMS POLYGON TRANSACTION, 138
VRIMS PROCESSING STATE CODE, 139
VRIMS SERVICE CODE, 140
VRIMS SERVICE STATE CODE, 141
VRIMS SYSTEM MODE CODE, 142
VRIMS SYSTEM PREFERENCE, 143
VRIMS SYSTEM SERVICE STATUS, 144
VRIMS SYSTEM STATE CODE, 145
VRIMS SYSTEM STATUS, 146
VRIMS TRANSACTION TYPE CODE, 147
VRIMS TREE SPECIES CODE, 148
VRIMS_FCO_TO_2006CONVERTED_FID, 151