

Using Macros for Repetitive Tasks

(APMisc1 *)

Talk prepared by
Wendy Bergerud

February 2004

Research Branch, B.C. Ministry of Forests
P. O. Box 9519 Stn. Prov. Govt.
Victoria, B.C., V8W 9C2
PH: 250-387-5676 FAX: 250-387-0046

e-mail: Wendy.Bergerud@gems8.gov.bc.ca
<http://www.for.gov.bc.ca/hre/topics/biomet.htm>



* Annotated Programs - Miscellaneous topics - Document #1

Running similar SAS code many times

- Copy the code many times.
- Change a few variable and/or dataset names;

OR

- Set up a simple macro.
- Use macro variables to represent the changing variable and/or data set names.
- Run the macro many times.

Macro Definition

- `%macro macroname;`
 - starts the macro definition, giving the name for the macro.

Sas code including macro variables.

- `%mend; or %mend macroname;`
 - ends the macro, the macroname is optional.

Macro Variables 1

- `%let macrovar = text values;`
 - Defines the value to be used for the macro variable.
 - The values are treated as text.
Working with numbers as numbers requires additional macro statements and functions.
 - Macro variables retain their value until assigned a new value.

Macro Variables 2

- `%let macrovar = text values;`
 - A null value will be assigned if there is no text after the equals sign.
 - Macro variables inside quotes must be inside double quotes to be resolved properly.
 - Macro variables will work outside of defined macros.

Calling the Macro

- **`%macroname;`**
 - calls the macro and runs the code after resolving any macro variables within the macro.
- You may have noticed that macro statements can be identified by the fact that they start with a percent (%) sign.

Example 1: Producing printer plots for different pairs of variables

- Want several plots of various y-variables against different x-variables.
- The following program plots **yvar** versus **xvar** using the first digit of the treat values as the plotting symbol.
- The names of the variables are included in a title statement so that they will appear at the top of the graphical printout.

Example 1: Producing printer plots for different pairs of variables

```
/** Macro for plotting pairs of variables */  
  
%macro plots;      *<< Starting the macro defn;  
  
title "For &yvar against &xvar";  
  
proc plot;  
    plot &yvar*&xvar = treat; run;  
  
%mend;              *<< Macro end;
```

Example 1: Producing printer plots for different pairs of variables

```
** Calling the macro three times;
```

```
*** plots y1 vs y2;
```

```
%let yvar = y1; %let xvar = y2; %plots;
```

```
*** plots y1 vs x1;
```

```
%let xvar = x1; %plots;
```

```
*** plots y2 vs x1;
```

```
%let yvar = y2; %plots;
```

Example 2: Producing printer plots for different subsets of the data

- Suppose that we want to produce plots as in example 1, but we want to do this for subsets of the data.
- Use another variable to define the different subsets, e.g. zone.

Example 2: Producing printer plots for different subsets of the data

```
/** Macro for plotting pairs of variables **/
```

```
%macro plots;      *<< Starting the macro defn;
```

```
title  "For &yvar against &xvar";
```

```
title2 "For zones: &zonevals";
```

```
*** Must use double quotes in the titles!;
```

```
proc plot; where zone in(&zonevals);*by zone;
```

```
  plot &yvar*&xvar = treat; run;
```

```
%mend plots;
```

```
*<< Macro end;
```

Example 2: Producing printer plots for different subsets of the data

```
** Calling the macro twice;
```

```
*** plots y1 vs y2 for zones 2 & 3;
```

```
%let yvar = y1; %let xvar = y2;
```

```
%let zonevals = 2,3; %plots;
```

```
*** plots y1 vs x1 for zones 3, 4 & 5;
```

```
%let xvar = x1;
```

```
%let zonevals = 3 4 5; %plots;
```

Example 5: Reading in many tables from an *ACCESS* database

- We want to convert data from a number of tables in an *ACCESS* database into permanent *SAS* datasets.
- First use the import wizard to create a simple program using `PROC IMPORT`.
- Build macro around that code.
- Program allows speedy recreation of *SAS* datasets as errors in original data require starting again.

Example 5: Reading in many tables from an ACCESS database

```
/** Importing individual tables
                                from Access Database */
libname wildlife "H:\Projects\Data";

%macro import;

PROC IMPORT OUT= WILDLIFE.&name DBMS=ACCESS97
  REPLACE DATATABLE= "&name";
DATABASE="H:\Projects\Data\wtppdb1f_d5.mdb";
RUN;

%mend;
```

Example 5: Reading in many tables from an *ACCESS* database

**** Calling the macro many times;**

```
%let name = AppCompInfo;           %import;  
%let name = block;                 %import;  
%let name = plot;                  %import;  
%let name = reserve;               %import;  
%let name = reserveDetail;         %import;  
%let name = reserveSample;         %import;  
%let name = reserveTree;           %import;  
%let name = sample;                %import;  
%let name = tree;                  %import;
```

Example 6: Reading and concatenating many data files into one SAS dataset

- Want to read in several data files with very similar layouts and merge into one large SAS data set.
- Need to be able to add or delete one variable name in the input for each data file depending upon data file.
- Create the final SAS data set with the first file read in, and then concatenate following data files as they are read in.

Example 6: Reading and concatenating many data files into one SAS dataset

```
%macro readin;  
data &dsn;  
    infile "&inf" dsd firstobs = 2 missover;  
    input inst $ blk plt splt can &inpt lay $  
          spp $ percov modht ;  
run;  
  
%if &flag = 1 %then %do; *<< First data set;  
    data all; set &dsn;      run; %end;  
%else %do;               *<< subsequent datasets;  
    data all; set all &dsn; run; %end;  
%mend;
```

Example 6: Reading and concatenating many data files into one SAS dataset

**** Calling the macro many times;**

%let flag = 1; *<< For first data set;

%let dsn = b1a; %let inf = aaa.csv;

%let inpt = ; %readin;

%let flag = 2; *<< For subsequent datasets;

%let dsn = b1b; %let inf = bbb.csv;

%let inpt = regen \$; %readin;

%let dsn = b1c; %let inf = ccc.csv;

%let inpt = ; %readin;

%let dsn = b1d; %let inf = ddd.csv;

%let inpt = regen \$; %readin;

Example 6a: Reading and concatenating many data files into one SAS dataset

**** Calling the macro many times;**

%let flag = 1; *<< For first data set;

%let dsn = bla; %let inf = aaa.csv;

%let inpt = ; %readin;

%let flag = 2; *<< For subsequent datasets;

%let inf = bbb.csv;

%let inpt = regen \$; %readin;

%let inf = ccc.csv;

%let inpt = ; %readin;

%let inf = ddd.csv;

%let inpt = regen \$; %readin;

Dealing with Errors

- If possible, start with ordinary and working SAS code.
- Go slow - build macro in small pieces.
- Use a **%put** statement to print values of macro variables to the SAS Log.
 - These are also useful for monitoring the progress of a long SAS job.
- List all macro variables to SAS Log with **%put _user_;**

Use SAS debugging options

- SYMBOLGEN – the values of the macro variables are written to the SAS log as the program is run.
- MPRINT – as the SAS statements are generated by the macro, they are written to the SAS log.
 - To turn on: `options symbolgen mprint;`
 - To turn off: `options nosymbolgen nomprint;`
- Can greatly increase the size of the SAS log.

The End